

We measure it.



# Mini temperature measuring instruments

Small and handy,  
big on measurement

---

Universally applicable

---

Self-explanatory and robust

---

Ready for use at the press of a button

---



The mini and surface thermometers fit into any jacket pocket. They are small, convenient and always ready for use anywhere: whether in the food sector, the pharmaceutical industry or in the heating and ventilation

business. The great advantage is that the mini thermometers record temperature in the air as well as in soft or powdery substances and in liquids.

[www.testo.com](http://www.testo.com)

## The waterproof mini-thermometer

### Switch on, measure, finished

#### Waterproof mini-thermometer

Waterproof mini thermometer, length 120 mm, up to +230 °C, with protective sleeve for probe shaft incl. calibration protocol

Part no. 0560 1113



After use, for example in a temperature measurement on foods, the waterproof mini-thermometer can simply be cleaned under running water or in a dishwasher.

#### Technical features:

- Waterproof, protection class IP67
- Measuring range from -20 to +230 °C
- Switch between °C and °F at the press of a button
- Battery charging level display
- MAX/MIN and HOLD button
- Easily exchangeable battery
- Probe shaft length 120 mm
- Protective sleeve as a holder

## Technical data

	Waterproof mini-thermometer	Standard mini penetration thermometer	Mini penetration thermometer with extended probe shaft	Mini surface thermometer
Measuring range	-20 to +230 °C	-50 to +150 °C	-50 to +250 °C	-50 to +300 °C
	120 mm	133 mm	213 mm	120 mm
Accuracy ±1 digit	±1 °C (-20 to +53.9 °C) ±0.8 °C (+54 to +90 °C) ±1 °C (+90.1 to +180 °C) ±1.5 °C (+180.1 to +230 °C)	±1 °C (-10 to +99.9 °C) ±2 °C (-30 to -10.1 °C) ±2% of m.v. (+100 to +150 °C)	±1 °C (-10 to +99.9 °C) ±2% of m.v. (+100 to +199.9 °C) ±3% of m.v. (+200 to +250 °C)	±1 °C (-30 to +250 °C) ±2 °C (remaining range)
Resolution	0.1 °C (-19.9 to +199.9 °C) 1 °C (remaining range)	0.1 °C (-19.9 to +150 °C) 1 °C (remaining range)	0.1 °C (-19.9 to +199.9 °C) 1 °C (remaining range)	0.1 °C (-19.9 to +199.9 °C) 1 °C (remaining range)
Operating temperature	-10 to +50 °C			
Battery type	Button cell LR44			
Display	LCD, 1 line			
Warranty	2 years			



For temperature spot-check measurements in food production



Dishwasher-safe



The protective sleeve with a clip holder. Always on you and ready to hand.



Simply rinse under running water when dirty.

## Your mini experts for every imaginable temperature measuring task



### Common technical features

- Easily legible display
- Battery charging level indicator
- Fast, easy battery replacement
- Switch between °C and °F at the press of a button
- Protective sleeve as a holder

### Standard mini penetration thermometer

Mini penetration thermometer up to 150 °C, length 133 mm, with protective sleeve for probe shaft, easily legible display, incl. batteries and calibration protocol

Part no. 0560 1110



#### Additional technical features

##### Standard mini penetration thermometer:

- Measuring range from -50 to +150 °C
- Probe shaft length 133 mm

### Mini penetration thermometer with extended probe shaft

Mini penetration thermometer up to 250 °C, length 213 mm, with protective sleeve for probe shaft, easily legible display, incl. batteries and calibration protocol

Part no. 0560 1111



#### Additional technical features

##### Mini penetration thermometer with extended probe shaft:

- Extended 213 mm probe shaft
- Measuring range from -50 to +250 °C

### Mini surface thermometer

Mini surface thermometer up to 300 °C, length 120 mm, broad measurement tip, easily legible display, incl. batteries


Part no. 0560 1109



#### Additional technical features

##### Mini surface thermometer:

- Universally applicable for surface measurement
- Probe shaft length 120 mm
- Diameter of measurement tip 15 mm
- Measuring range from -50 to +300 °C





Mini temperature measuring instruments



0981 9394/msp/A/01.2016

Subject to change without notice.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Testo manufacturer:](#)*

Other Similar products are found below :

[206 PH1](#) [TESTO 175-H1 0572 1754](#) [TESTO 316-1 0632 0316](#) [TESTO 770-1 0590 7701](#) [TESTO 770-3 0590 7703](#) [TESTO 905-T1 0560 9055](#)  
[0572 0500](#) [0602 4592](#) [0590 0008](#) [0590 0018](#) [0628 0020](#) [TESTO 416 0560 4160](#) [TESTO 755-2 0590 7552](#) [TESTO 770-2 0590 7702](#) [TESTO](#)  
[869 + TESTO 745](#) [TESTO 869 + TESTO 750-3](#) [0613 1912](#) [0602 1793](#) [816-1](#) [410-2](#) [606-2](#) [460](#) [0572 6172](#) [0590 0001](#) [0614 2272](#) [TESTO](#)  
[417 0560 4170](#) [0609 7072](#) [0628 7503](#) [TESTO 176-P1](#) [TESTO 835-T2](#) [TESTO 605-H1](#) [TESTO 103](#) [TESTO 622](#) [TESTO 477](#) [0563 0510](#)  
[0563 4403](#) [0590 7702](#) [TESTO 435-3 0560 4353](#) [TESTO 760-2 0590 7602](#) [TESTO 760-3 0590 7603](#) [0590 0013](#) [0590 0017](#) [0602 0645](#) [0602](#)  
[4892](#) [TESTO 635-2 0563 6352](#) [TESTO 750-3 0590 7503](#) [TESTO 760-1 0590 7601](#) [6462532](#) [417](#) [110](#)