

We measure it.



Core temperature thermometer

testo 106 – The compact food thermometer

Ideal for use in the food sector

TopSafe: dishwasher-safe protective cover (IP67), protects from dirt and impact

Small, handy and always ready to hand

Audible and optical alarm

Automatic final value recognition (Auto-hold)

Hardly visible punctures

Certified according to EN 13485 (only in combination with TopSafe)



The core thermometer testo 106 is especially fast and robust. Its small handy shape means it is always close to hand and ready for use. Thanks to its very thin and robust measurement tip, it is excellently suited to core temperature checks in gastronomy, hotels, large kitchens, supermarkets etc. The dishwasher-safe TopSafe protects the instrument from dirt, water and impact.

The testo 106 is conform to HACCP as well as EN 13485. If required, upper and lower limit values can be stored in the instrument; as soon as these values are violated, audible and optical warning signals are given. This alarm function and the automatic final value recognition facilitate measurement and support you in recognizing and interpreting measurement values quickly and correctly.



°C

www.testo.com

Technical data / Accessories

testo 106

testo 106, food core thermometer incl. probe protecting cap, battery and calibration protocol

Part no. 0560 1063



Set testo 106

Set testo 106, food core thermometer incl. TopSafe (waterproof protection case, IP67, attachment clip, probe protection cap, battery and calibration protocol

Part no. 0563 1063

Sensor type NTC

Measuring range	-50 to +275 °C
Accuracy ±1 digit	±1 % of m.v. (+100 to +275 °C) ±0.5 °C (-30 to +99.9 °C) ±1 °C (-50 to -30.1 °C)
Resolution	0.1 °C

General technical data

Storage temperature	-40 to +70 °C
Operating temperature	-20 to +50 °C
t ₉₉	10 s
Battery type	3V button cell (CR 2032)
Battery life	350 h
Weight	80 g
Dimensions Length Probe shaft / Probe shaft tip Diameter Probe shaft / Probe shaft tip	215 x 34 x 19 mm 55 mm / 15 mm Ø 3 mm / Ø 2.2 mm
Display	LCD, 1 line
Housing material	ABS
Protection class	IP 67 with TopSafe
Warranty	2 years
Standard	EN 13485

Accessories

Part no.

Accessories for measuring instrument

TopSafe (indestructible protection case); waterproof and dishwasher-safe protection case (IP67)	0516 8265	
Holding clip with probe protection cap	0554 0825	
ISO calibration certificate/temperature ; for air/immersion probes, calibration point +60°C	0520 0063	
ISO calibration certificate/temperature ; for air/immersion probes, calibration point -18°C	0520 0061	
ISO calibration certificate/temperature ; for air/immersion probes, calibration point 0°C	0520 0062	
ISO calibration certificate/temperature ; for air/immersion probes, calibration points -18°C; 0°C	0520 0041	
ISO calibration certificate/temperature ; for air/immersion probes, calibration points -8°C; 0°C; +40°C	0520 0181	

0981 9494/msp/A/01.2016

Subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Testo manufacturer:](#)

Other Similar products are found below :

[TESTO 175-H1 0572 1754](#) [TESTO 770-3 0590 7703](#) [TESTO 830-T1 0560 8311](#) [TESTO 905-T1 0560 9055](#) [TESTO 605I 0560 1605](#) [TESTO 735-2 0563 7352](#) [TESTO 750-3 0590 7503](#) [TESTO 755-1 0590 7551](#) [460](#) [610](#) [0628 7503](#) [TESTO 174-T SET](#) [TESTO 440 0563 4403](#) [TESTO 915I 0563 1915](#) [TESTO 745 0590 7450](#) [TESTO 760-2 0590 7602](#) [TESTO 760-3 0590 7603](#) [0602 4892](#) [TESTO 417 0560 4170](#) [TESTO 176-P1 0560 1109](#) [TESTO 106 KIT](#) [TESTO 770-2 0590 7702](#) [0602 0644](#) [0613 1912](#) [810](#) [0590 0011](#) [TESTO 104](#) [TESTO 410I 0590 7601](#) [760-1](#) [TESTO 760-1 0590 7601](#) [0572 6172](#) [TESTO 174-H SET](#) [TESTO 175-T1](#) [TESTO 405I](#) [0602 0645](#) [0602 1293](#) [0590 7603](#) [0602 0393](#) [511](#) [TESTO 605-H1](#) [TESTO 103](#) [TESTO 905-T2](#) [410-1](#) [TESTO 510I](#) [0563 0510](#) [815](#) [0590 0010](#) [606-1](#)