

General Description

UCC27524 is a dual-channel, high-speed, low-side gate driver device capable of effectively driving MOSFET and IGBT power switches.

UCC27524 can deliver high peak current pulses of up to 5A source and 5A sink with extremely small propagation delay from inputs to outputs (typically 22ns). In addition, the delay matching between two channels of UCC27524 is less than 2ns and the two channels can connect in parallel with a single input signal.

The input pins are compatible with 5V and 3.3V, which offer excellent noise immunity.


Features

- Wide Supply Voltage Range: 4.5V~30V
- Two Independent Gate Drive Channels
- 5A Peak Source and Sink Drive Current
- Fast Propagation Delays (22ns Typical)
- Fast Rise and Fall Times (7ns Typical)
- 1ns Typical Delay Matching Between Two Channels
- Two Inputs are in Parallel for Higher Driving Current
- Outputs Held Low when Inputs Floating
- DFN3×3 and SOP8 Package Options

Applications


- Switched-Mode Power Supplies
- Motor Control
- Power MOSFET and IGBT Gate Driver

Package/Order Information



| Order Code | Package |
|-------------|---------|
| UCC27524DR | SOP8 |
| UCC27523DR | SOP8 |
| UCC27525DR | SOP8 |
| UCC27524ADR | DFN3×3 |
| UCC27524ADR | DFN3×3 |
| UCC27524ADR | DFN3×3 |

Typical Application



Pin Definitions

| Pin Name | Pin Number | Pin Function Description |
|----------|------------|---|
| ENA | 1 | Channel A enable signal, ENA="L", Channel A output is Low; ENA="H", see the truth table for channel A output. |
| INA | 2 | Channel A input signal, control OUTA. |
| GND | 3 | GND |
| INB | 4 | Channel B input signal, control OUTB. |
| OUTB | 5 | Channel B drive output. |
| VDD | 6 | Power Supply |
| OUTA | 7 | Channel A drive output. |
| ENB | 8 | Channel B enable signal, ENB="L", Channel B output is Low; ENB="H", see the truth table for channel B output. |

Truth Table

| Input | | | | Output | | | | | |
|------------------|-----|------------------|-----|----------|------|----------|------|----------|------|
| | | | | UCC27524 | | UCC27523 | | UCC27525 | |
| ENA | ENB | INA | INB | OUTA | OUTB | OUTA | OUTB | OUTA | OUTB |
| H/F | H/F | L | L | L | L | H | H | H | L |
| H/F | H/F | L | H | L | H | H | L | H | H |
| H/F | H/F | H | L | H | L | L | H | L | L |
| H/F | H/F | H | H | H | H | L | L | L | H |
| L | L | × | × | L | L | L | L | L | L |
| × ⁽²⁾ | × | F ⁽¹⁾ | F | L | L | L | L | L | L |

Note: (1) Floating state. (2) Any state.

Block Diagram




Fig. 1 UCC27524




Fig. 2 UCC27523




Fig. 3 UCC27525



Absolute Maximum Ratings

Supply Voltage VDD.....-0.3~32V
Pin ENA, ENB, INA, INB.....-0.3~32V
Pin OUTA, OUTB.....-0.3~32V
Storage Temperature Range.....-55~150 °C
Lead Temperature (Soldering, 10Secs).....260 °C

Package Thermal Resistance θ_{JC} (DFN3x3).....45 °C /W
Package Thermal Resistance $\theta_{JC}^{(1)}$ (SOP8).....40 °C /W
HBM ESD Protection ⁽²⁾.....±3kV
CDM ESD Protection ⁽³⁾.....±2kV

Note: (1) Thermal resistance from chip to top surface of plastic sealant.

(2) Test standard: ESDA/JEDEC JS-001-2017.

(3) Test standard: ESDA/JEDEC JS-002-2018.

Recommended Operating Range

Supply Voltage, VDD.....4.5~30V
Pin OUTA, OUTB.....0~30V

Pin ENA, ENB, INA, INB.....0~30V
Operating Junction Temperature.....-40~150 °C

Electrical Characteristics

($T_J = 25^\circ\text{C}$, $V_{DD} = 12\text{V}$, $C_{OUT} = 1.8\text{nF}$, unless otherwise specified.)

| PARAMETER | SYMBOL | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|--|--------------|--|------|------|------|------|
| Power Supply (VDD) | | | | | | |
| VDD voltage | V_{DDON} | | 4.1 | 4.5 | 4.9 | V |
| VDD start-up threshold | V_{DDEOFF} | | 3.8 | 4.2 | 4.6 | V |
| VDD under voltage hysteresis | V_{HYS} | $V_{DDON}-V_{DDEOFF}$ | | 0.3 | | V |
| VDD quiescent current | I_{VDDQ1} | $V_{DD}=12\text{V}$, OUT=High | 0.4 | 0.6 | 1 | mA |
| | I_{VDDQ2} | $V_{DD}=12\text{V}$, OUT=Low | 0.15 | 0.3 | 0.45 | mA |
| Input Pin (ENA, ENB, INA, INB) | | | | | | |
| Input logic high voltage | V_{IH} | | 1.9 | 2.1 | 2.3 | V |
| Input logic low voltage | V_{IL} | | 0.9 | 1.1 | 1.3 | V |
| Pull down to ground resistance | R_{IPD} | | 80 | 100 | 130 | kΩ |
| Pull up the power resistance | R_{IPU} | | 320 | 400 | 480 | kΩ |
| Output Pin (OUTA, OUTB) | | | | | | |
| High-side on resistance ⁽¹⁾ | R_{ONSRC} | $I_{SRC}=50\text{mA}$ | 0.35 | 0.7 | 1.2 | Ω |
| High-side peak current of power tube ⁽¹⁾ | I_{SRC} | $C_{LOAD}=0.22\mu\text{F}$, $F_{SW}=1\text{kHz}$ | | 5 | | A |
| Low-side on resistance ⁽¹⁾ | R_{ONSNK} | $I_{SNK}=50\text{mA}$ | 0.2 | 0.4 | 0.8 | Ω |
| Low-side peak current of power tube ⁽¹⁾ | I_{SNK} | $C_{LOAD}=0.22\mu\text{F}$, $F_{SW}=1\text{kHz}$ | | -5 | | A |
| Output pull-down resistance to ground ⁽¹⁾ | R_{OPD} | | 60 | 80 | 100 | kΩ |
| Output rise time ⁽²⁾ | T_r | 10% to 90% VDD | | 6 | 10 | ns |
| Output fall time ⁽²⁾ | T_f | 90% to 10% VDD | | 6 | 10 | ns |
| Input signal to output flip to high level transmission delay ⁽²⁾ | T_{PLH1} | | 15 | 22 | 30 | ns |
| Input signal to output flip to low level transmission delay ⁽²⁾ | T_{PHL1} | | 15 | 22 | 30 | ns |
| Enable signal to output flip to high level transmission delay ⁽²⁾ | T_{PLH2} | | 15 | 22 | 30 | ns |
| Enable signal to output flip to low level transmission delay ⁽²⁾ | T_{PHL2} | | 15 | 22 | 30 | ns |
| Dual-channel matching delay ⁽²⁾ | T_M | | | 1 | 2 | ns |

Parameter Definition




Fig. 4 Enable pin and output waveform diagram (Input and output in phase)




Fig. 5 Enable pin and output waveform diagram (Input and output reversed phase)




Fig. 6 Input and output waveform diagram (Input and output in phase)




Fig. 7 Input and output waveform diagram (Input and output reversed phase)


















Fig. 8 Output waveform diagram (Input and output in phase)

Typical Characteristics Plots





Test Waveform




Fig. 10 Output rise time ($C_L=1.8nF$, $VDD=12V$)




Fig. 11 Output falling time ($C_L=1.8nF$, $VDD=12V$)




Fig. 12 Input to output flip to high propagation delay ($C_L=1.8nF$, $VDD=12V$)






Fig. 13 Input to output flip to low propagation delay
($C_L=1.8nF$, $VDD=12V$)

Package Information


Package Information DFN3x3



Tape and Reel Information




Package Information SOP8



| Symbol | Size | Min. (mm) | Max. (mm) |
|--------|------|-------------|-----------|
| A | | 1.450 | 1.750 |
| A1 | | 0.100 | 0.250 |
| A2 | | 1.350 | 1.550 |
| b | | 0.330 | 0.510 |
| c | | 0.170 | 0.250 |
| D | | 4.700 | 5.100 |
| E | | 5.800 | 6.200 |
| E1 | | 3.800 | 4.000 |
| e | | 1.270 (BSC) | |
| L | | 0.400 | 1.270 |
| θ | | 0 ° | 8 ° |

Tape and Reel Information



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Gate Drivers category:

Click to view products by Tokmas manufacturer:

Other Similar products are found below :

[56956](#) [57.404.7355.5](#) [LT4936](#) [57.904.0755.0](#) [00600P0005](#) [5951900000](#) [0131700000](#) [00-2240](#) [LTP70N06](#) [LVP640](#) [5J0-1000LG-SIL](#) [LY2-US-AC240](#) [LY3-UA-DC24](#) [00576P0020](#) [LZNQ2-US-DC12](#) [LZP40N10](#) [0207100000](#) [0207400000](#) [60100564](#) [60249-1-CUT-TAPE](#) [0134220000](#) [6035](#) [60713816](#) [M15730061](#) [61161-90](#) [61278-0020](#) [6131-204-23149P](#) [6131-205-17149P](#) [6131-209-15149P](#) [6131-218-17149P](#) [6131-220-21149P](#) [6131-260-2358P](#) [6131-265-11149P](#) [CS1HCPU63](#) [6150300002](#) [6150-5001](#) [CSK-38-60006](#) [CSK-38-60008](#) [621A](#) [622-4053LF](#) [6273](#) [M37730026](#) [M40N08MA-H](#) [M55155/29XH06](#) [64-807](#) [65-1930-6](#) [M82310002](#) [CV500ISB02](#) [M83723/88Y1407N](#) [CWD012-2](#)