Unit: mm

TOSHIBA Diode Silicon Epitaxial Schottky Barrier Type

1SS294

Low Voltage High Speed Switching

- AEC-Q101 Qualified (Note1)
- Low forward voltage $V_{\rm F}(3) = 0.54 V (typ.)$
- Low reverse surrent $I_{R} = 5\mu A (max)$
- Small package : SC-59

Characteristic

Maximum (peak) reverse voltage

Reverse voltage

Note1: For detail information, please contact to our sales.

| | - | |
|---|---------|--|
| | | 0.4 +0.4 0.4 +0.4 0.4 +0.4 0.4 +0.4 0.4 +0.4 0.4 +0.4 0.4 +0.4 0.4 +0.4 0.4 +0.4 |
| - | | ³ 1. ANODE 2. N.C 3. CATHODE |
| | JEDEC | TO-236MOD |
| | JEITA | SC-59 |
| _ | TOSHIBA | |
| | | 2-3F1S |

2.9±0.2

Absolute Maximum Ratings (Ta = 25°C)

| Maximum (peak) forward current | I _{FM} | 300 | mA | S-MINI |
|--------------------------------|------------------|------------|----|--------------------|
| Average forward current | lo | 100 | mA | JEDEC |
| Power dissipation | Р | 150 | mW | JEITA |
| Junction temperature | Tj | 125 | °C | TOSHIBA |
| Storage temperature range | T _{stg} | -55 to 125 | °C | Weight: 12 mg (typ |

Symbol

VRM

 V_{R}

/p.)

oltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.

Rating

45

40

Unit

V


V

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Electrical Characteristics (Ta = 25°C)


| Characteristic | Symbol | Test Condition | Min | Тур. | Max | Unit |
|-------------------|--------|--------------------------------|-----|------|------|------|
| | VF (1) | IF = 1mA | _ | 0.28 | _ | V |
| Forward voltage | VF (2) | IF = 10mA | _ | 0.36 | _ | |
| | VF (3) | IF = 100mA | _ | 0.54 | 0.60 | |
| Reverse current | IR | VR = 40V | _ | _ | 5 | μΑ |
| Total capacitance | CT | V _R = 0 V, f = 1MHz | _ | 18 | 25 | pF |

Marking



Start of commercial production 1986-03

TOSHIBA



<u>TOSHIBA</u>

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as "TOSHIBA". Hardware, software and systems described in this document are collectively referred to as "Product".

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.
- PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE"). Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT. For details, please contact your TOSHIBA sales representative.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without
 limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile
 technology products (mass destruction weapons). Product and related software and technology may be controlled under the
 applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the
 U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited
 except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.

TOSHIBA ELECTRONIC DEVICES & STORAGE CORPORATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schottky Diodes & Rectifiers category:

Click to view products by Toshiba manufacturer:

Other Similar products are found below :

MA4E2039 MA4E2508M-1112 MBR10100CT-BP MBR1545CT MMBD301M3T5G GS1JE-TP RB160M-50TR BAS 3010S-02LRH E6327 BAT 54-02LRH E6327 NSR05F40QNXT5G NSVR05F40NXT5G NTE555 JANS1N6640 SB07-03C-TB-H SBS818-TL-E SK310-T SK33A-TP SK34B-TP SS3003CH-TL-E PDS3100Q-7 GA01SHT18 CRS10I30A(TE85L,QM MA4E2501L-1290 MBRB30H30CT-1G DMJ3940-000 SB007-03C-TB-E SK32A-TP SK33B-TP SK35A-TP SK38B-LTP SK38B-TP NRVBM120LT1G NTE505 NTSB30U100CT-1G SS0503SH-TL-E VS-6CWQ10FNHM3 CRG04(T5L,TEMQ) ACDBA1100LR-HF ACDBA1200-HF ACDBA2100-HF ACDBA240-HF ACDBA3100-HF CDBQC0530L-HF ACDBA260LR-HF ACDBA1100-HF MA4E2502L-1246 10BQ060-M3/5BT NRVB130LSFT1G CRS08TE85LQM PMAD1108-LF