



BNC to BNC COAX CABLE ASSEMBLIES

50 Ohm, 75 Ohm, 93 Ohm

- ## Features
- UL Listed Cable: Ensures quality and consistency in the cable construction.
 - Boot is molded to cable connector for added strength: Limits the amount of bending the cable is exposed to at the connector to prevent cable breakage.
 - Gold center pins: Ensures that there is a high quality connection maintaining the best return loss in high definition applications.
 - Machined Brass Connectors: Unlike die-cast connectors, machined brass connectors have more precise tolerances, strength and positive mating meaning low signal loss for precise video and data applications.
 - 95% Shielding: Keeps unwanted RF interference from infiltrating your signal giving you nice, clean output.
 - 80° temperature rating: Applicable to any application found indoors.
 - Lengths Available up to 100 ft.: Easily route cables into other rooms or floors.
 - Individually bagged

Specifications

| Conductor | | Insulation | | Braided Shielding | | Jacket | | General | |
|---------------|-------------|---------------|--------------------------|-------------------|-------------|---------------------|--------------------------|----------------------------|------|
| Material | Bare Copper | Material | Low Density Polyethylene | Material | Bare Copper | Material | Polyvinyl Chloride (PVC) | Tensile Strength | 93 |
| No./mm | 1/0.813 | No./mm | 16/7/0.12 | No./mm | 16/7/0.12 | Thickness (mm) | 0.9 | Nominal Impedance (Ohm) | 53.5 |
| Diameter (mm) | 2.95 | Diameter (mm) | 3.71 | Diameter (mm) | 2.95 | Color | Black | Nominal Capacitance (pF/m) | 68.9 |
| | | | | | | Outer Diameter (mm) | 4.95 ±0.15 | Attenuation 100MHz (dB/km) | 138 |
| | | | | | | Color | Black | Voltage Rating | 30V |
| | | | | | | | | UL Standard | 1354 |
| | | | | | | | | | |

12 to 36 inch cables = +/- 1 inch
Cables above 36 inches = +/- 1.5 inches



| Molded BNC to BNC Cable Assemblies | | |
|--|---------|-----------|
| RG58/U, BNC Male to Male | 50 Ohm | Part No. |
| 58-012-1M | 12 inch | 58-012-1M |
| 58-024-1M | 24 inch | 58-024-1M |
| 58-036-1M | 36 inch | 58-036-1M |
| 58-048-1M | 48 inch | 58-048-1M |
| 58-060-1M | 60 inch | 58-060-1M |
| RG59/U, BNC Male to Male/Video & General | 75 Ohm | Part No. |
| 59-012-1M | 12 inch | 59-012-1M |
| 59-024-1M | 24 inch | 59-024-1M |
| 59-036-1M | 36 inch | 59-036-1M |
| 59-048-1M | 48 inch | 59-048-1M |
| 59-060-1M | 60 inch | 59-060-1M |
| RG62/U, BNC Male to Male/Computer & Lab | 93 Ohm | Part No. |
| 62-012-1M | 12 inch | 62-012-1M |
| 62-024-1M | 24 inch | 62-024-1M |
| 62-036-1M | 36 inch | 62-036-1M |
| 62-048-1M | 48 inch | 62-048-1M |
| 62-060-1M | 60 inch | 62-060-1M |

| Assembled BNC to BNC Cable Assemblies | | |
|---------------------------------------|----------|------------|
| RG58/U, BNC Male to Male | 50 Ohm | Part No. |
| 58-012-1M | 12 inch | 58-012-1M |
| 58-024-1M | 24 inch | 58-024-1M |
| 58-030-1M | 25 feet | 58-030-1M |
| 58-600-1M | 50 feet | 58-600-1M |
| 58-900-1M | 75 feet | 58-900-1M |
| 58-1200-1M | 100 feet | 58-1200-1M |
| BNC Cable Assemblies | 50 Ohm | Part No. |
| RG58/U, BNC Male to Male | 50 Ohm | 58-024-1A |
| | | 24 inch |
| | | 58-036-1A |
| | | 36 inch |
| | | 58-048-1A |
| | | 48 inch |
| | | 58-060-1A |
| | | 60 inch |



Features

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [tpi](#) manufacturer:

Other Similar products are found below :

[3M201-NB](#) [TLS2021](#) [3M301R-NB](#) [635](#) [A006](#) [50](#) [TLS2030](#) [A402](#) [510](#) [105-52-000](#) [565C1](#) [TPI-4022](#) [A202](#) [TPI-4024WIFI](#) [120086](#) [F6-50B](#)
[59-1200-1M](#) [505](#) [TPI-5000A](#) [F6-75B](#) [A900](#) [A403](#) [62-024-1M](#) [TLS2011](#) [A401](#) [LEADRACK](#) [59-600-1M](#) [F6-25B](#) [FX13B](#) [59-060-1M](#)
[3M701-NB](#) [F6-6B](#) [TPI-3000A](#) [3C350-NB](#) [LEADRACKSM](#) [59-180-1M](#) [59-048-1M](#) [59-024-1M](#) [A057](#) [A345](#) [58-900-1M](#) [FK26M](#) [58-1200-1M](#) [59-120-1M](#) [58-600-1M](#) [A346](#) [A044](#) [A039](#) [59-300-1M](#) [59-036-1M](#)