



## TLS2030 MODULAR TEST LEAD KIT

***For use with test equipment having 4mm diameter input jacks***

- **Back Probes** - for non-intrusive testing, slide into terminal blocks or weather tight seals.
- **Modular Test leads** - 48 inches long, silicone insulation and 90° or 180° modular ends enable quick test-probe changes
- **Crocodile Clips** - for hands free testing
- **Piercing Probes** - screw into wires for positive connection
- **Grabbers** - 7 inch long, spring loaded jaws provide a sure grip
- **Modular Prods** - perform typical probing requirements
- **Spring Hooks** - 7 inch long, spring loaded for gripping connections and hard to reach wires or terminals
- **Black Nylon Pouch** - folds up for protected transport and storage



Copyright © 2013 Test Products International, Inc.

<b>Voltage Rating</b>	1000 V
<b>Amperage Rating</b>	10 Amp
<b>Insulation Material</b>	Test lead: Silicone Adapters: PVC
<b>Dimensions</b>	Lead Length: 48 inches (30cm)
<b>Type</b>	4mm banana plug ends and sockets

**Voltage / Amperage Rating**  
**Category Rating**  
**Type**  
**Dimensions**  
**Insulation Material**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [tpi](#) manufacturer:*

Other Similar products are found below :

[3M201-NB](#) [TLS2021](#) [3M301R-NB](#) [635](#) [A006](#) [50](#) [TLS2030](#) [A402](#) [510](#) [105-52-000](#) [565C1](#) [TPI-4022](#) [A202](#) [TPI-4024WIFI](#) [120086](#) [F6-50B](#)  
[59-1200-1M](#) [505](#) [TPI-5000A](#) [F6-75B](#) [A900](#) [A403](#) [62-024-1M](#) [TLS2011](#) [A401](#) [LEADRACK](#) [59-600-1M](#) [F6-25B](#) [FX13B](#) [59-060-1M](#)  
[3M701-NB](#) [F6-6B](#) [TPI-3000A](#) [3C350-NB](#) [LEADRACKSM](#) [59-180-1M](#) [59-048-1M](#) [59-024-1M](#) [A057](#) [A345](#) [58-900-1M](#) [FK26M](#) [58-1200-1M](#) [59-120-1M](#) [58-600-1M](#) [A346](#) [A044](#) [A039](#) [59-300-1M](#) [59-036-1M](#)