

- Compact metal package
- Ultra wide 4:1 input voltage ranges  
9–36, 18–75, 43–160 VDC
- EN 50155 approval for railway applications
- Very high efficiency up to 91%
- No minimum load
- Soft start
- Under voltage lock-out circuit
- Adjustable output voltage +10 / -20%
- Sense line



The TEP 200WIR Series is a family of isolated high performance DC/DC converter modules with ultra-wide 4:1 input voltage ranges. They come in rugged, sealed industry standard half brick package. A very high efficiency allows full power operation at 25°C with only 100 LFM air flow cooling and operation at 60°C with only 40% power derating. The very wide input voltage range and reverse input voltage protection make these converters interesting solution for battery operated systems. Typical applications are in telecom/datacom, industry control and railway systems for onboard power distribution.

Models				
Order Code	Input Voltage Range	Output Voltage nom.	Output Current max.	Efficiency typ.
TEP 200-2412WIR	9 - 36 VDC (24 VDC nom.)	12 VDC	15'000 mA	89 %
TEP 200-2413WIR		15 VDC	12'000 mA	90 %
TEP 200-2415WIR		24 VDC	7'500 mA	90 %
TEP 200-2416WIR		28 VDC	6'500 mA	90 %
TEP 200-2418WIR		48 VDC	3'700 mA	89 %
TEP 200-4812WIR	18 - 75 VDC (48 VDC nom.)	12 VDC	18'000 mA	90 %
TEP 200-4813WIR		15 VDC	14'000 mA	91 %
TEP 200-4815WIR		24 VDC	9'000 mA	90 %
TEP 200-4816WIR		28 VDC	7'500 mA	91 %
TEP 200-4818WIR		48 VDC	4'500 mA	90 %
TEP 200-7212WIR	43 - 160 VDC (110 VDC nom.)	12 VDC	20'000 mA	89 %
TEP 200-7213WIR		15 VDC	16'000 mA	90 %
TEP 200-7215WIR		24 VDC	10'000 mA	89 %
TEP 200-7216WIR		28 VDC	8'500 mA	90 %
TEP 200-7218WIR		48 VDC	5'000 mA	89 %

### Options

<b>TEP-HS1</b>	- Optional Heat Sink: <a href="http://www.tracopower.com/products/tep-hs1.pdf">www.tracopower.com/products/tep-hs1.pdf</a>
<b>on demand</b> (backorder with MOQ non stocking item)	<ul style="list-style-type: none"> <li>- Optional model with 3.3 VDC / 50'000 mA Output and 9 - 36 VDC Input</li> <li>- Optional model with 5 VDC / 36'000 mA Output and 9 - 36 VDC Input</li> <li>- Optional model with 3.3 VDC / 50'000 mA Output and 18 - 75 VDC Input</li> <li>- Optional model with 5 VDC / 40'000 mA Output and 18 - 75 VDC Input</li> <li>- Optional model with 53 VDC / 3'800 mA Output and 33 - 75 VDC Input</li> <li>- Optional model with 3.3 VDC / 57'000 mA Output and 43 - 160 VDC Input</li> <li>- Optional model with 5 VDC / 44'000 mA Output and 43 - 160 VDC Input</li> <li>- 2:1 Input models</li> <li>- Negative (passive = Off) Remote On/Off function</li> <li>- Sync pin to synchronize switching frequency of up to 3 units (EMC reason)</li> </ul>

### Input Specifications

Input Current	- At no load	24 Vin models: <b>35 mA typ.</b> 48 Vin models: <b>20 mA typ.</b> 110 Vin models: <b>10 mA typ.</b>
Surge Voltage		24 Vin models: <b>50 VDC max.</b> (1 s max.) 48 Vin models: <b>100 VDC max.</b> (1 s max.) 110 Vin models: <b>185 VDC max.</b> (1 s max.)
Under Voltage Lockout		24 Vin models: <b>7.3 VDC min. / 7.7 VDC typ. / 8.1 VDC max.</b> 48 Vin models: <b>15.5 VDC min. / 16 VDC typ. / 16.3 VDC max.</b> 110 Vin models: <b>33 VDC min. / 34.5 VDC typ. / 36 VDC max.</b>
Recommended Input Fuse		24 Vin models: <b>32'000 mA</b> (fast acting) 48 Vin models: <b>20'000 mA</b> (fast acting) 110 Vin models: <b>10'000 mA</b> (fast acting) (The need of an external fuse has to be assessed in the final application.)
Input Filter		<b>Internal Pi-Type</b>

### Output Specifications

Output Voltage Adjustment		<b>-20% to +10%</b> (By external trim resistor) See application note: <a href="http://www.tracopower.com/overview/tep200wir">www.tracopower.com/overview/tep200wir</a> Output power must not exceed rated power!
Voltage Set Accuracy		<b>±1% max.</b>
Regulation	- Input Variation (Vmin - Vmax) - Load Variation (0 - 100%)	<b>0.1% max.</b> <b>0.1% max.</b>
Ripple and Noise (20 MHz Bandwidth)		3.3 Vout models: <b>75 mVp-p max.</b> (w/ 1 µF X7R // 25 µF poscap) 5 Vout models: <b>75 mVp-p max.</b> (w/ 1 µF X7R // 25 µF poscap) 12 Vout models: <b>100 mVp-p max.</b> (w/ 1 µF X7R // 25 µF poscap) 15 Vout models: <b>100 mVp-p max.</b> (w/ 1 µF X7R // 25 µF poscap) 24 Vout models: <b>200 mVp-p max.</b> (w/ 4.7 µF X7R) 28 Vout models: <b>200 mVp-p max.</b> (w/ 4.7 µF X7R) 48 Vout models: <b>300 mVp-p max.</b> (w/ 2.2 µF X7R)

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Capacitive Load	- 24 Vin input	3.3 Vout models:	151'000 µF max.	
		5 Vout models:	72'000 µF max.	
		12 Vout models:	12'500 µF max.	
		15 Vout models:	8'000 µF max.	
			24 Vout models:	3'100 µF max.
			28 Vout models:	2'300 µF max.
			48 Vout models:	770 µF max.
			3.3 Vout models:	151'000 µF max.
	- 48 Vin input	5 Vout models:	80'000 µF max.	
		12 Vout models:	15'000 µF max.	
		15 Vout models:	9'300 µF max.	
		24 Vout models:	3'700 µF max.	
		28 Vout models:	2'600 µF max.	
		48 Vout models:	930 µF max.	
		3.3 Vout models:	172'000 µF max.	
		5 Vout models:	88'000 µF max.	
- 110 Vin input	12 Vout models:	16'600 µF max.		
	15 Vout models:	10'600 µF max.		
	24 Vout models:	4'100 µF max.		
	28 Vout models:	3'000 µF max.		
		48 Vout models:	1'000 µF max.	
Minimum Load		Not required		
Temperature Coefficient		±0.02 %/K max.		
Start-up Time		75 ms typ.		
Short Circuit Protection		Continuous, Automatic recovery		
Output Current Limitation		120 - 150% of Iout max.		
Oversvoltage Protection		115 - 130% of Vout nom.		
Transient Response	- Response Time	200 µs typ. / 250 µs max. (25% Load Step)		

### Safety Specifications

Safety Standards	- IT / Multimedia Equipment	EN 60950-1
		EN 62368-1
		IEC 60950-1
		IEC 62368-1
		UL 60950-1
		UL 62368-1
	- Railway Applications	EN 50155
	- Certification Documents	<a href="http://www.tracopower.com/overview/tep200wir">www.tracopower.com/overview/tep200wir</a>
Pollution Degree		PD 2
Over Voltage Category		OVC II

### EMC Specifications

EMI Emissions	- Conducted Emissions	EN 55011 class B (with external filter)
		EN 55032 class B (with external filter)
	- Radiated Emissions	EN 55011 class B (with external filter)
		EN 55032 class B (with external filter)
		External filter proposal: <a href="http://www.tracopower.com/overview/tep200wir">www.tracopower.com/overview/tep200wir</a>

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

<b>EMS Immunity</b>		<b>EN 50155</b> (Railway Applications) <b>EN 50121-3-2</b> (EMC for Rolling Stock) Air: <b>EN 61000-4-2, ±8 kV, perf. criteria A</b> Contact: <b>EN 61000-4-2, ±6 kV, perf. criteria A</b> <b>EN 61000-4-3, 20 V/m, perf. criteria A</b> <b>EN 61000-4-4, ±2 kV, perf. criteria A</b> <b>EN 61000-4-5, ±2 kV, perf. criteria A</b> Ext. input component: 24 & 48 Vin models: 2 x KY 20 µF 110 Vin models: 2 x KXJ 150 µF <b>EN 61000-4-6, 10 Vrms, perf. criteria A</b> Continuous: <b>EN 61000-4-8, 100 A/m, perf. criteria A</b> 1 s: <b>EN 61000-4-8, 1000 A/m, perf. criteria A</b>
- Electrostatic Discharge		
- RF Electromagnetic Field		
- EFT (Burst) / Surge		
- Conducted RF Disturbances		
- PF Magnetic Field		

<b>General Specifications</b>		
<b>Relative Humidity</b>		<b>95% max.</b> (non condensing)
<b>Temperature Ranges</b>	- Operating Temperature	<b>-40°C to +75°C</b>
	- Case Temperature	<b>+105°C max.</b>
	- Storage Temperature	<b>-55°C to +125°C</b>
<b>Power Derating</b>	- High Temperature	See application note: <a href="http://www.tracopower.com/overview/tep200wir">www.tracopower.com/overview/tep200wir</a>
<b>Over Temperature Protection Switch Off</b>	- Protection Mode	<b>115°C typ.</b> (Automatic recovery at 105°C typ.)
	- Measurement Point	<b>Base-Plate</b>
<b>Cooling System</b>		<b>Natural convection</b> (20 LFM)
<b>Sense Function</b>		<b>10% max. of Vout nom.</b> (Sense line to be connected to the output either at the module or at the load under regard of polarity.)
<b>Remote Control</b>	- Voltage Controlled Remote	<b>On: 3.0 to 12 VDC or open circuit</b> <b>Off: 0 to 1.2 VDC or short circuit</b> <b>Refers to 'Remote' and '-Vin' Pin</b>
	- Off Idle Input Current	<b>3 mA typ.</b>
	- Remote Pin Input Current	<b>-0.5 to 1.0 mA</b>
<b>Altitude During Operation</b>		<b>2'000 m max.</b> (for reinforced insulation) <b>5'000 m max.</b> (for functional insulation)
<b>Switching Frequency</b>		<b>225 - 275 kHz</b> (PWM) <b>250 kHz typ.</b> (PWM)
<b>Insulation System</b>		<b>Reinforced Insulation</b> (110 Vin models only) <b>Functional Insulation</b> (other models)
<b>Working Voltage</b> (rated)		<b>145 VAC</b> (3.3 and 5 Vout models) <b>185 VAC</b> (48 and 53 Vout models) <b>172 VAC</b> (other output models)
<b>Isolation Test Voltage</b>	- Input to Output, 60 s	<b>3'000 VAC</b> (110 Vin models) <b>3'000 VDC</b> (other models)
	- Input to Case, 60 s	<b>1'500 VAC</b> (110 Vin models) <b>1'600 VDC</b> (other models)
	- Output to Case, 60 s	<b>1'500 VAC</b> (110 Vin models) <b>1'600 VDC</b> (other models)
<b>Isolation Resistance</b>	- Input to Output, 500 VDC	<b>1'000 MΩ min.</b>
<b>Isolation Capacitance</b>	- Input to Output, 100 kHz, 1 V	<b>2'500 pF max.</b>
<b>Reliability</b>	- Calculated MTBF	<b>300'000 h</b> (MIL-HDBK-217F, ground benign)
<b>Environment</b>	- Vibration	<b>MIL-STD-810F</b> <b>EN 61373</b>
	- Mechanical Shock	<b>MIL-STD-810F</b> <b>EN 61373</b>
	- Thermal Shock	<b>MIL-STD-810F</b> <b>EN 50155</b>

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Housing Material	Alu base-plate w. metal case (24 and 48 Vin models) Alu base-plate w. plastic case (110 Vin models)
Base Material	Non-conductive FR4 (UL 94 V-0 rated) (24 and 48 Vin models only)
Potting Material	Silicone (UL 94 V-0 rated)
Pin Material	Copper
Pin Foundation Plating	Nickel (2 - 3 µm)
Pin Surface Plating	Tin (3 - 5 µm), matte
Housing Type	Metal Case (24 and 48 Vin models) Plastic Case (110 Vin models)
Mounting Type	PCB Mount
Connection Type	THD (Through-Hole Device)
Footprint Type	Half-Brick
Weight	105 g
Thermal Impedance	6.1 K/W 4.6 K/W (with Heat Sink)
Environmental Compliance	<p>- REACH Declaration <a href="http://www.tracopower.com/info/reach-declaration.pdf">www.tracopower.com/info/reach-declaration.pdf</a> REACH SVHC list compliant REACH Annex XVII compliant</p> <p>- RoHS Declaration <a href="http://www.tracopower.com/info/rohs-declaration.pdf">www.tracopower.com/info/rohs-declaration.pdf</a> Exemptions: 7a, 7c-1 (RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule). The SCIP number is provided on request.)</p> <p>- Flammability (EN 45545-2) <a href="http://www.tracopower.com/info/en45545-declaration.pdf">www.tracopower.com/info/en45545-declaration.pdf</a></p>

## Supporting Documents

Overview Link (for additional Documents)

[www.tracopower.com/overview/tep200wir](http://www.tracopower.com/overview/tep200wir)

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Isolated DC/DC Converters](#) category:*

*Click to view products by [TRACO Power](#) manufacturer:*

Other Similar products are found below :

[ESM6D044440C05AAQ](#) [FMD15.24G](#) [PSL486-7LR](#) [Q48T30020-NBB0](#) [JAHW100Y1](#) [SPB05C-12](#) [SQ24S15033-PS0S](#) [18952](#) [19-130041](#)  
[CE-1003](#) [CE-1004](#) [GQ2541-7R](#) [RDS180245](#) [MAU228](#) [J80-0041NL](#) [DFC15U48D15](#) [XGS-0512](#) [XGS-1205](#) [XGS-1212](#) [XGS-2412](#) [XGS-](#)  
[2415](#) [XKS-1215](#) [06322](#) [NCT1000N040R050B](#) [SPB05B-15](#) [SPB05C-15](#) [L-DA20](#) [DCG40-5G](#) [QME48T40033-PGB0](#) [XKS-2415](#) [XKS-2412](#)  
[XKS-1212](#) [XKS-1205](#) [XKS-0515](#) [XKS-0505](#) [XGS-2405](#) [XGS-1215](#) [XGS-0515](#) [PS9Z-6RM4](#) [73-551-5038I](#) [AK1601-9RT](#) [VI-N61-CM](#) [VI-](#)  
[R5022-EXWW](#) [PSC128-7iR](#) [RPS8-350ATX-XE](#) [DAS1004812](#) [PQA30-D24-S24-DH](#) [VI-M5F-CQ](#) [VI-LN2-EW](#) [VI-PJW01-CZY](#)