


Features

- ◆ Single-in-line (SIL) package
- ◆ Isolated single and dual output models
- ◆ I/O isolation 3'000 VDC
- ◆ Unregulated device
- ◆ High Efficiency up to 81%
- ◆ Extended temperature range
-40°C to +85°C
- ◆ Pin-compatible with other manufacturers
- ◆ 100% Burn-in (8 h)
- ◆ Lead free design, RoHS compliant
- ◆ 3-year product warranty



The TMV series are miniature, isolated 1 W DC/DC-converters with high isolation in a Single-in-Line package (SIP). Requiring only 1.2 cm² board space they offer the ideal solution in many space critical applications for board level power distribution. The use of SMD-technology makes it possible to offer a product with high performance at low cost.

Models				
Ordercode	Input voltage	Output voltage	Output current max.	Efficiency typ.
TMV 0505S	5 VDC ±10%	5 VDC	200 mA	71 %
TMV 0509S		9 VDC	110 mA	76 %
TMV 0512S		12 VDC	84 mA	78 %
TMV 0515S		15 VDC	67 mA	78 %
TMV 0505D		± 5 VDC	±100 mA	72 %
TMV 0512D		±12 VDC	±42 mA	78 %
TMV 0515D		±15 VDC	±34 mA	79 %
TMV 1205S	12 VDC ±10%	5 VDC	200 mA	73 %
TMV 1212S		12 VDC	84 mA	80 %
TMV 1215S		15 VDC	67 mA	80 %
TMV 1205D		± 5 VDC	±100 mA	74 %
TMV 1212D		±12 VDC	±42 mA	81 %
TMV 1215D		±15 VDC	±34 mA	81 %
TMV 2405S	24 VDC ±10%	5 VDC	200 mA	71 %
TMV 2412S		12 VDC	84 mA	78 %
TMV 2415S		15 VDC	67 mA	79 %
TMV 2405D		± 5 VDC	±100 mA	72 %
TMV 2412D		±12 VDC	±42 mA	79 %
TMV 2415D		±15 VDC	±34 mA	80 %

Input Specifications

Input current no load /full load	5 Vin models	30 mA / 270 mA typ.
	12 Vin models	12 mA / 110 mA typ.
	24 Vin models	7 mA / 55 mA typ.
Surge voltage (1 s max.)	5 Vin models	9 V max.
	12 Vin models	18 V max.
	24 Vin models	30 V max.
Reflected input ripple current	can be reduced by ext. 1–3.3 µF polyester film capacitor	
Input filter	internal capacitor	

Output Specifications

Voltage set accuracy	±1 % typ. / ±3 % max.	
Voltage balance (dual output models, balanced loads)	±0.1 % typ. / ±1 % max.	
Regulation	– Input variation (1 % change of Vin)	1.2 % typ. / 1.5 % max.
	– Load variation (20 – 100 %)	5 to 10 % max.
Ripple and noise (20 MHz Bandwidth)	65 mVp-p typ. / 100 mVp-p max.	
Temperature coefficient	±0.01 %/K typ. / ±0.02 %/K max.	
Short circuit protection	limited 0.5 s max.	
Capacitive load	single output models:	220 µF max.
	dual output models:	100 µF max. (each output)

General Specifications


Temperature Ranges	– Operating	3.3, 5 & ±5 Vout models:	–40°C to +85°C
		all other output models:	–40°C to +90°C
	– Case temperature		+95°C max.
	– Storage		–50°C to +125°C
Derating		3.3, 5 & ±5 Vout models:	4 %/K above 75 °C
		all other output models:	4 %/K above 80 °C
Humidity (non condensing)	95 % rel H max.		
Reliability, calculated MTBF (MIL-HDBK-217F at +25°C, ground benign)	>2'000'000 h		
Isolation Test Voltage (Input/Output, 60 s)	3'000 VDC		
Insulation System	Functional		
Isolation Capacitance (Input/Output)	60 pF typ. / 100 pF max.		
Isolation Resistance (Input/Output)	>10 GOhm		
Switching Frequency	70 to 120 kHz (Frequency modulation)		
Environmental Compliance	– Reach	www.tracopower.com/info/reach-declaration.pdf	
	– RoHS	RoHS directive 2011/65/EU	

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Physical Specifications

Casing material	non conductive plastic (UL 94V-0 rated)	
Package weight	5 & 12 Vin models:	2.1 g (0.07 oz)
	24 Vin models:	2.6 g (0.09 oz)
Soldering temperature	max. 265°C / 10 s	

Outline Dimensions mm (inches)



Pin-Out		
Pin	Single	Dual
1	+Vin (Vcc)	+Vin (Vcc)
2	-Vin (GND)	-Vin (GND)
5	-Vout	-Vout
6	No pin	Common
7	+Vout	+Vout

Dimensions in [mm], () = Inch
Tolerances: ±0.25 (±0.01)
Pins: ±0.05 (±0.002)

Specifications can be changed without notice! Make sure you are using the latest documentation, downloadable at www.tracopower.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Isolated DC/DC Converters](#) category:

Click to view products by [TRACO Power](#) manufacturer:

Other Similar products are found below :

[ESM6D044440C05AAQ](#) [FMD15.24G](#) [PSL486-7LR](#) [Q48T30020-NBB0](#) [JAHW100Y1](#) [SPB05C-12](#) [SQ24S15033-PS0S](#) [18952](#) [19-130041](#)
[CE-1003](#) [CE-1004](#) [GQ2541-7R](#) [RDS180245](#) [MAU228](#) [J80-0041NL](#) [DFC15U48D15](#) [XGS-0512](#) [XGS-1205](#) [XGS-1212](#) [XGS-2412](#) [XGS-](#)
[2415](#) [XKS-1215](#) [06322](#) [NCT1000N040R050B](#) [SPB05B-15](#) [SPB05C-15](#) [L-DA20](#) [DCG40-5G](#) [QME48T40033-PGB0](#) [XKS-2415](#) [XKS-2412](#)
[XKS-1212](#) [XKS-1205](#) [XKS-0515](#) [XKS-0505](#) [XGS-2405](#) [XGS-1215](#) [XGS-0515](#) [PS9Z-6RM4](#) [73-551-5038I](#) [AK1601-9RT](#) [VI-N61-CM](#) [VI-](#)
[R5022-EXWW](#) [PSC128-7iR](#) [RPS8-350ATX-XE](#) [DAS1004812](#) [PQA30-D24-S24-DH](#) [VI-M5F-CQ](#) [VI-LN2-EW](#) [VI-PJW01-CZY](#)