

Provides all the features required to troubleshoot any type of fibre optic cabling.

Fiber Optic Power Meter

dB/Ca

FiberMASTER 33-927

dBm



FiberMASTER[™] MM/SM Fiber Optic Test Kit

Measure fibre optic power in milliwatts (mW) and decibel-milliwatts (dBm) to test and troubleshoot active LANs.

Quickly measure cabling loss with the automatic calibration feature that stores reference power from any light source for quick dB loss calculations.

Plus, the 1490nm wavelength measurement mode is perfect for troubleshooting emerging Fibre To The Home cabling systems.

Key Features

- 850, 1300, 1310, 1490 and 1550 wavelength measurement capability on power meter
- 850, 1300, 1310, 1550nm laser light source (33-931 kit)
- Power measurement in dBm and µW, loss display in dB
- Includes universal adaptor for power meter and ST, SC and FC adaptors for light source
- Unique "docking" light source and easy three button operation make this the perfect fibre tester for use in the field

For more information please call (0)1925 428 380 or visit www.trend-networks.com

Multi-Mode/Single Mode Light Source

FiberMASTER[™] MM/SM

Fiber Optic Test Kit

The TREND **FiberMASTER™** fibre optic testing kit allows the user to measure absolute power and calculate the loss of fibre optic links at several wavelengths.

Absolute power measurements are helpful when trouble shooting equipment that may not be operating properly.

The dB calibration feature allows the operator to set a reference level to the light source and directly read the loss of fibre optic links without needing to manually calculate the values.

The unique form factor allows the light source to be docked neatly within the power meter.

This makes the kit compact for easy storage while still allowing full operation of both the source and meter.

- **33-929** Light source, 850, 1300, 1310, 1550 laser light source with ST, SC and FC adaptors
- **33-927** Power meter, 4 wavelength with universal 2.5mm and fixed FC adaptor
- 2x SC-SC 50µm multimode cables
- 1 SC calibration coupler
- Carrying case
- User Manual in English, Spanish, German, French, Portuguese, Italian and Chinese


FiberMASTER Kit Includes:

Power Meter Specifications	
Wavelength	850, 1300, 1310, 1490, 1550nm
Detector	InGaAs
Measurement Range	-60 to +3dBm
Accuracy	±5%
Display Resolution	.01
Connector	Universal 2.5mm w/ FC adapter
Power Supply	AAA Alkaline Battery x 3
Operating Time	360 hours
Operating Temp	-10 to +60°C
Light Source Specifications	
Wavelength	850, 1300, 1310, 1550nm laser diode
Output Power	-6 to -7 dBm Typical
Stability	.05dB after 15min, 0.1dB over 8 hrs
Connector	2.5mm w/ ST, SC, FC adapters
Power Supply	AAA Alkaline Battery x 3
Operating Time	40 hours
Operating Temp	-10 to +60°C
Storage Temp	-25 to +70°C
Cat. No.	Description
33-928	MM/SM power meter with 850nm light source only
33-929	Four wavelength MM/SM light source only
33-931	FiberMASTER Fibre Optic Test Kit

TREND NETWORKS

TREND NETWORKS

Stokenchurch House, Oxford Road, Stokenchurch, High Wycombe, Buckinghamshire, HP14 3SX, UK. Tel. +44 (0)1925 428 380 | Fax. +44 (0)1925 428 381 uksales@trend-networks.com



www.trend-networks.com



Specification subject to change without notice. E&OE © TREND NETWORKS 2021 Publication no.: 164828

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LAN/Telecom/Cable Testing category:

Click to view products by Trend Networks manufacturer:

Other Similar products are found below :

 1673606-1
 SEFRAM95
 TCT-1620
 TCT-2210
 TCT-680
 150050
 150059
 150060
 158051
 158053
 TCT-2690PRO
 TCT

 700
 TESTER-MS6811
 TESTER-MS6812
 262
 N044-000-R
 MCT-468
 TM-901N
 TM-903
 LAN-1
 24-517
 CT20
 40180
 TG20

 GBE FIBRE KIT LX
 GBE FIBRE KIT SX
 CLM-1000E
 CLM-1000
 HDMI-100
 TEP-100
 KE301
 KE3150
 KE401
 KE501

 KE7000
 KE701
 KE8000
 KE801
 KE850
 VDV501-851
 LANXPLORER PRO
 LC-90
 NAVITEK NT
 NAVITEK NT PLUS

 NAVITEK NT PRO
 KE701
 KE8000
 KE801
 KE850
 VDV501-851
 LANXPLORER PRO
 LC-90
 NAVITEK NT
 NAVITEK NT PLUS