

POWER TRANSFORMER PC Mount: Single Primary

F-132P

Electrical Specifications (@25C)

1. Maximum Power: 1.5 VA 2. Primary: 115V 50/60 Hz

3. Secondary: Series: 15.0V CT @ 0.100 Amps Parallel: 7.5V CT @ 0.200 Amps

Description:

The F-132P is part of a wide selection of plug-in types that meet the needs of PC boards and solid state power supply design. This transformer can satisfy power as well as control and instrumentation applications.

Construction:

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

Safety:

These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings.


Unite: In inches

Dimensions:

Dillicitatoria.			Offices. Iff ifficines	
Α	В	С	D	Е
1.187	1.390	1.562	0.312	1.00

Pin length: 0.187 in.
Pin size: 0.20 x .041 in.
Weight: 3.5 oz

Schematic:



Primary: 1 to 2

Secondary: Series - 3 to 6, Jumper 4 to 5


Parallel - 3 to 6, Jumper 3 to 5 and 4 to 6


RoHS Compliance: As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.


*Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics website for the most current version. For soldering and washing information please see http://www.triadmagnetics.com/faq.html











Publish Date: May 21, 2019

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Transformers category:

Click to view products by Triad manufacturer:

Other Similar products are found below:

ET-030A F-102X F-120X F-14X-1 F-181U F-18A F-199U F-19X F-202U F-204U F-206U F-227X F-238U F-239U-1 F-23U F24-250-B
F-242U F-245U F-264U F-265U F-267U F-281U F-283U F-290X F-295Z F-296Z F-298Z F-3143P F-3298Z F-33U F-346X F-35U F364U F-392A F-395X F-397U F-412X F-47U F-55X-1 F-60U F-68U F-71U F-72Z F-74U F-83A F-84AC F-85U F-86U F-9U PCT-02