

POWER TRANSFORMER **PC Mount: Single Primary**

F-159XP

Electrical Specifications (@25C)

1. Maximum Power: 7.5 VA 2. Primary: 115V 50/60 Hz

3. Secondary: Series: 12.6V CT @ 0.60 Amps Parallel: 6.3V CT @ 1.20 Amps

Description:

The F-159XP is part of a wide selection of plug-in types that meet the needs of PC boards and solid state power supply design. This transformer can satisfy power as well as control and instrumentation applications.

Construction:

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

Safety:


These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings.

Dimensions:

Dimensions:					Units: In inches	
	Α	В	С	D	Е	F
	1.625	2.812	1.468	2.375	0.406	1.312

Mounting hole: 0.187 in. Pin length: 0.187 in. Pin size: 0.20 x .041 in. Weight: 10.5 oz

Schematic:



Primary: 1 to 2


Series - 3 to 6, Jumper 4 to 5 Secondary:


Parallel - 3 to 6, Jumper 3 to 5 and 4 to 6


RoHS Compliance: As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

*Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics website for the most current version. For soldering and washing information please see http://www.triadmagnetics.com/faq.html









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Triad manufacturer:

Other Similar products are found below:

F36-170-C2-B D-105 D-164 D-205 D-238 D-245 D-267 D-281 D-285 D-311 D-323 D-343 D-355F D-365F D-371 D-373 D-378F D-379F D-380F MCB-9 F-178SX F-191U F-212Z F-23U F-264U F-283U F-346X F-44X F-47U F-60U FIRCH-5 FP88-130 G-336 G-388 PL-20 A-112X A-114X A-118X A-14J A-300X A-301X A-304X A-42Z A-54X A-68J A-6X A-77J A-95X R-104B R-124BC