

## POWER TRANSFORMER Chassis Mount: Single Secondary

## F-40X

## **Electrical Specifications (@25C)**

1. Maximum Power: 26.8 VA 2. Primary: 115V 60 Hz

3. Secondary: 26.8VCT @ 1.00 Amps

4. Voltage Regulation: 15 % TYP @ full load to no load 5. Temperature Rise: 35C TYP (45C MAX allowed)

### **Description:**

The F-40X is part of a series which has a long history of reliable service in the field, made from a proven design and constructed with UL recognized materials.

#### **Construction:**

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

### Safety:

These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings as well as between the primary / secondary windings and the core.


**Dimensions:** Units: In inches

А	В	С	D
1.937	3.312	2.00	2.812

Mounting Hole Diameter: .187 in Lead length: 7.0 inches + 1 inch

Weight: 1.30 lbs

### **Schematic:**





Primary: Black to Black Secondary: Red to Red


**RoHS Compliance:** As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

\* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.









# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Transformers category:

Click to view products by Triad manufacturer:

Other Similar products are found below:

ET-030A F-102X F-120X F-14X-1 F-181U F-18A F-199U F-19X F-202U F-204U F-206U F-227X F-238U F-239U-1 F-23U F24-250-B
F-242U F-245U F-264U F-265U F-267U F-281U F-283U F-290X F-295Z F-296Z F-298Z F-3143P F-3298Z F-33U F-346X F-35U F364U F-392A F-395X F-397U F-412X F-47U F-55X-1 F-60U F-68U F-71U F-72Z F-74U F-83A F-84AC F-85U F-86U F-9U PCT-02