

POWER TRANSFORMER CHASSIS MOUNT: Isolation

N-53MG

Electrical Specifications (@25°C)

1. Maximum Power: 85 VA

Input Voltage: 115 V, 50 / 60 Hz
 Output Voltage: 115V <u>+</u> 5%

4. Full Secondary Load: 0.74 Amps RMS

5. Voltage Regulation: 10 % TYP @ full load to no load



The N-53MG is a power transformer for isolating equipment from direct connection to the powerline. The primary and secondary coils are concentrically wound providing excellent magnetic coupling. Having good magnetic coupling between windings helps reduce leakage flux and phase shift.

Safety

These units are designed with 1500V isolation between winding to winding and between winding and core. Materials and construction are rated for Class B insulation system.

Dimensions: Unit: In inches


А	В	С	D	Ш
3.593	2.968	3.750	2.250	2.875

Weight: 4.70 lbs

Mounting Holes: .375 x .187


Connections: 6 ft. long cord, 5-15P NEMA Plug, 5-15R NEMA Receptacle


Schematic:




RoHS Compliance: As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.









^{*} Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Transformers category:

Click to view products by Triad manufacturer:

Other Similar products are found below:

ET-030A F-102X F-120X F-14X-1 F-181U F-18A F-199U F-19X F-202U F-204U F-206U F-227X F-238U F-239U-1 F-23U F24-250-B
F-242U F-245U F-264U F-265U F-267U F-281U F-283U F-290X F-295Z F-296Z F-298Z F-3143P F-3298Z F-33U F-346X F-35U F364U F-392A F-395X F-397U F-412X F-47U F-55X-1 F-60U F-68U F-71U F-72Z F-74U F-83A F-84AC F-85U F-86U F-9U PCT-02