

POWER TRANSFORMER CHASSIS MOUNT: Autotransformer

N-7M

Electrical Specifications (@25°C)

1. Maximum Power: 600 VA

2. Input Voltage: 230 V, 50 / 60 Hz
3. Output Voltage: 115V ± 5%
4. Full Secondary Load: 5.22 Amps RMS



The N-7M is part of the line of Auto-Transformers that are single winding transformers in which the secondary coil is a fraction of the entire winding for voltage step-down. This causes part of the power to be transferred conductively through the windings, rather than all of the power being transferred by induction.

Safety:

These units are designed with 1500V isolation between the winding and the core. Materials and construction are rated for Class B insulation system.

Dimensions: Unit: In inches


А	В	С	D	E
4.625	3.937	5.00	3.00	3.875

Weight: 12.0 lbs

Mounting Holes: .375 x .187

Connections: 6 ft. long cord, 1-15P NEMA Plug, 1-15R NEMA Receptacle


Schematic:





RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Autotransformers category:

Click to view products by Triad manufacturer:

Other Similar products are found below:

ARM-2.0/3 ESS 104 ESS 120 ARM-3.0/1 ARM-5.0/1 ATS1000VA-230/110V U ATS1500VA-230/110V U ATS1500VA-230V/115V-001 TS90-230V/115V-002 UP-500VA OIEA1 OIEA1 OIEA1 OIEA3 OIEA8 VP-2000VA VP-1000VA N-1000MG N-3MG N-5MG N-6U N-150MG N-2X N-9MG 110-0F 120-0F 1150-0F 1150-0F 150-0F 150-0F 115-0F 112-0F ATS1500-230V/115V-001 ATS25-230V/115V-001 ATST1500-230V/115V-001 ATST1500-230V/115V-001 ATST1500-230V/115V-001 ATST1500-230V/115V-001 ATST2500-230V/115V-001 ATST3000-230V/115V-001 ATST3000-23