

**Driver LCO 300W 200–1400mA flexC 0-10V NF L SNC3**  
essence NFC outdoor series

New



#### Product description

- \_ Constant current LED driver
- \_ Tested acc. to salt spray test (ISO 9227)
- \_ Dimmable via 0 ... 10 V interface (incl. stand-by)
- \_ Dimming range 1 to 100 %
- \_ Adjustable output current between 200 and 1,400 mA via NFC
- \_ Max. output power 300 W
- \_ Up to 92 % efficiency
- \_ Nominal lifetime 45,000 h
- \_ 5 years guarantee

#### Housing properties

- \_ Casing: metal, black
- \_ Type of protection IP67 and IP66

#### Functions

- \_ Adjustable output current in 1-mA-steps (NFC)
- \_ AUX output
- \_ Fade-off time programmable
- \_ Configurable external temperature management (ETM)
- \_ Protective features (overtemperature, short-circuit, overload, no-load)

#### Benefits

- \_ Operating window for maximum compatibility
- \_ Added energy savings with dimming via 0 ... 10 V interface
- \_ Configurable via NFC
- \_ Tailor your dimming response with either Linear, Logarithmic or Square Dimming Curves

#### Typical applications

- \_ For parking lot, high bay, street and road applications
- \_ For linear or area lighting in industry applications

#### Website

<http://www.tridonic.com/28003560>



Spotlights



Downlights



Linear



Area



Floor | Wall



Free-standing



Street



Decorative



High bay



## Standards

EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61347-1, EN 61347-2-13, EN 61547, EN 62384, EN 60598-1, FCC PART 15

## Specific technical data

Type	Article number	Output current <sup>①</sup>	Min. forward voltage	Max. forward voltage	Max. output power	Typ. power consumption (at 230 V, 50 Hz, full load)	Typ. current consumption (at 230 V, 50 Hz, full load)	tc point max.	Ambient temperature ta
LCO 300/200-1400 flexC 0-10V NF L SNC3	28003560	200 mA	85 V	457 V	91.4 W	105.0 W	481 mA	90 °C	-40 ... +60 °C
LCO 300/200-1400 flexC 0-10V NF L SNC3	28003560	500 mA	85 V	457 V	228.5 W	246.6 W	1,084 mA	90 °C	-40 ... +60 °C
LCO 300/200-1400 flexC 0-10V NF L SNC3	28003560	800 mA	85 V	375 V	300.0 W	317.8 W	1,391 mA	90 °C	-40 ... +60 °C
LCO 300/200-1400 flexC 0-10V NF L SNC3	28003560	1,100 mA	85 V	272 V	299.2 W	318.5 W	1,394 mA	90 °C	-40 ... +60 °C
LCO 300/200-1400 flexC 0-10V NF L SNC3	28003560	1,400 mA	85 V	214 V	299.6 W	320.7 W	1,403 mA	90 °C	-40 ... +60 °C

① Valid at 100 % dimming level.

② Depending on the selected output current.

③ With load on AUX port higher.

④ Output current is mean value.

⑤ The table only lists a number of possible operating points but does not cover each single point. The output current can be set within the total value range in 1-mA-steps.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Power Supplies](#) category:*

*Click to view products by [Tridonic](#) manufacturer:*

Other Similar products are found below :

[ESS015W-1000-12](#) [PDA-WIFI](#) [PIFC-K250F](#) [PITB-K222A](#) [ALD-514012PJ134](#) [LB240S24KH](#) [LMH020-SPLC-0000-0000001](#) [79534](#) [79535](#)  
[EUG-200S210DT](#) [ESS030W-1050-21](#) [ESS030W-0900-32](#) [BPOXL 4-12-035](#) [ESS010W-0350-24](#) [ESM060W-1400-42](#) [PDA080B-1A0G](#)  
[PDA150B-S1A5G](#) [SLM140W-1.05-130-ZA](#) [ESS015W-0700-18](#) [EUD-150S350DVA](#) [LWA320-C420-ARK-B](#) [HVG-240-48AB](#) [HVG-320-36AB](#) [HVG-320-54AB](#) [ELG-240-C1400AB](#) [EUK-150S105DV](#) [BXCS-12Z-N2P-B1-A](#) [BXPR-WN-01-A](#) [BXCS-12D-N2P-01-A](#) [BXCS-12W-N2P-01-A](#) [LC 50W 200-350ML 170V FLEXC LP SNC4](#) [LC 25W 200-350ML 70V FLEXC LP SNC4](#) [LC 35W 200-350ML 121V FLEXC LP SNC4](#) [LC 10W 250MA FIXC SC SNC2](#) [LC 35W 800MA FIXC SR ADV2](#) [LC 38W 900MA FIXC SR ADV2](#) [LC 34W 800MA FIXC SC ADV2](#) [LC 44W 1050MA FIXC SC ADV2](#) [LC 38W 900MA 42V FIXC SRL ADV2](#) [HVG-320-48AB](#) [CNB50W-1200-42-CAS](#) [CNB30W-0600-42-CAS](#) [LCI 100W 1400MA TEC C](#) [LCI 100W 2100MA TEC C](#) [LCI 150W 1750MA TEC C](#) [LCI 150W 2100MA TEC C](#) [87500284](#) [87500447](#) [LC 50W 1200MA FIXC SR SNC](#) [87500554](#)