

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Cat5e 350 MHz Snagless Molded Slim (UTP) Ethernet Cable (RJ45 M/M) - Blue, 5 ft. (1.52 m)

MODEL NUMBER: N001-S05-BL





Connects network components like printers, computers, copiers, routers, servers, modems and switches. Ideal for high-density data centers. Slim design increases airflow in tight spaces.

Features

Perfect Solution for Your Networking Needs

- Ideal for connecting components like printers, computers, copiers, routers, servers, modems and switches in high-density data centers
- Designed for fast transmission and excellent signal quality
- Ensures peak performance throughout your LAN
- Delivers speeds up to 350 MHz/1 Gbps

Special Slim Design

- More than 25% smaller in diameter than standard Cat5e cable
- · Increases airflow in tight spaces
- Extra flexible for installing around corners and through cable management panels

Premium Construction for Superior Performance

- Made from 28 AWG copper wire
- PVC 4-pair stranded UTP
- RJ45 male connectors
- Integral strain relief for long life

Snagless Connectors

· Molded snagless boots prevent locking tabs from damage

Highlights

- Over 25% slimmer than standard Cat5e cables
- Rated for 350 MHz/1 Gbps communications
- Snagless RJ45 male connectors
- Easy to route through cable management panels
- High-quality 28 AWG copper wire

Package Includes

 N001-S05-BL Cat5e 350 MHz Snagless Molded Slim UTP Patch Cable (RJ45 M/M), 5 ft.



Specifications

| OVERVIEW | |
|---------------------------------|----------------------|
| UPC Code | 037332193018 |
| Technology | Cat5/5e |
| PHYSICAL | |
| Color | Blue |
| Cable Shielding | UTP |
| Cable Jacket Material | PVC |
| Number of Conductors | 4 Pair |
| Cable Outer Diameter (OD) | 3.5mm |
| Conductor Material | Stranded Copper |
| Conductor Gauge | 28 AWG |
| Cable Length (ft.) | 5 |
| Cable Length (m) | 1.5 |
| Cable Length (in.) | 60 |
| Cable Length (cm) | 152.4 |
| Shipping Dimensions (hwd / cm) | 17.78 x 22.86 x 1.27 |
| Shipping Dimensions (hwd / in.) | 7.00 x 9.00 x 0.50 |
| Shipping Weight (kg) | 0.05 |
| Shipping Weight (lbs.) | 0.12 |
| COMMUNICATIONS | |
| Bandwidth per TIA Standard | 100 MHz |
| Maximum Bandwidth as Tested | 350 MHz |
| Network Speed | 1Gbps |
| CONNECTIONS | |
| Side A - Connector 1 | RJ45 (MALE) |
| Side B - Connector 1 | RJ45 (MALE) |
| Crossover Wiring | No |
| Contact Plating | Gold |
| Connector Type | Molded; Snagless |
| Wiring Configuration | EIA/TIA 568B |
| SPECIAL FEATURES | |



| IP68 Rated | No | |
|--|---------------------------|--|
| Antibacterial | No | |
| | | |
| STANDARDS & COMPLIANCE | | |
| Certifications | RoHS, REACH | |
| | | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ethernet Cables / Networking Cables category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below :

 73-6670-7
 73-6680-15
 73-7797-25
 MCJB2-10P6Q7-120
 84909-0204
 1200700174
 1200860368
 E16A06002M030
 E200102-009-S1

 AX105346-EW
 MT14-187L
 17-103530
 ERWPAB3002M005
 190-038045-01
 NK5EPC18RDY
 NK5EPC18VLY
 NK5EPC18YLY

 NK5EPC1GRY
 NK5EPC4Y
 NK5EPC6YLY
 NK5EPC8BLY
 NK5EPC9YLY
 1969343-6
 C501100010
 C501106002
 C501106007

 C501106015
 C501106025
 C601102010
 C601104010
 C601106007
 C601106015
 2142758-2
 2168427-2
 CAT1106007
 21949-1
 2J1866A

 RJF SFTP 5E 0500
 AX100351
 MN14CEC/ST
 C501106004
 C501106010
 C551108007
 C601104004
 C601106004

 CA21106004
 CA21106010
 CA21106015
 CA21109007
 C601104004
 C601106004