


Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Duplex Singlemode 8.3/125 Fiber Patch Cable (LC/LC), 10M (33 ft.)

MODEL NUMBER: N370-10M



Description

Tripp Lite's 10M (32.8-ft.), singlemode duplex fiber optic LC/LC patch cable is manufactured from 8.3/125 zipcord fiber. The cable has LC connectors on one end, LC connectors on the other, a PVC jacket, and is FDDI and OFNR rated. Duplex singlemode fiber is most commonly used in LAN applications.

Features

- Manufactured from 8.3/125 duplex (zipcord) fiber
- PVC jacket
- Length: 10M (32.8-ft.) Connectors: 2 LC and 2 LC connectors on each end
- Insertion loss testing performed on every connector (0.2db typical) and provided with cable
- Beveled edge on ends of glass makes insertion of plug a breeze
- Fiber made from glass (not a polymer)
- Fiber optic distributed data interface (FDDI) rated
- OFNR (riser rated)

Specifications

OVERVIEW		
UPC Code	037332122803	
Technology	Singlemode	
Optical Mode	OS2	
PHYSICAL		
Color	Yellow	

Highlights

- Premium PVC 8.3/125 micron singlemode patch cables
- Attenuation loss meets or exceeds the latest industry standards
- Twice the bandwidth throughput of multimode cable

System Requirements

 Any fiber optic hardware or NIC card requiring singlemode duplex cable with LC/LCconnectors

Package Includes

10-meter (30-33ft) Duplex
Singlemode Fiber Patch Cable,
LC/LC



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

[
Cable Jacket Rating	LSZH
Clad Diameter	125 micron
Core Diameter	8.3 micron
Number of Fibers	2
Cable Length (ft.)	32.8
Cable Length (m)	10
Cable Length (in.)	393.7
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50
Shipping Weight (kg)	0.09
Shipping Weight (lbs.)	0.19
ENVIRONMENTAL	
Operating Temperature Range	-4 to 140 °F (-20 to 60 °C)
Storage Temperature Range	-4 to 140 °F (-20 to 60 °C)
COMMUNICATIONS	
Network Speed	10Gbps
CONNECTIONS	
Side A - Connector 1	LC DUPLEX (MALE)
Side A - Connector 2	LC DUPLEX (MALE)
Side B - Connector 1	LC DUPLEX (MALE)
SPECIAL FEATURES	
Push/Pull Tabs	No
STANDARDS & COMPLIANCE	
Approvals	FDDI and OFNR rated
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fiber Optic Cable Assemblies category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below :

7-21002-9 760-1518 FA04390-50-M-72-LC-N MLB 501 V RED MLB 501 V YELLOW 8-21000-7 FXE3-10BM15 FXE3-10FM5 FZB3-NM1 1-3636-600-5208 ICD040GVP163D-07 2901797 1-6693182-0 1754898-1 F512D5-5F23Y F912B10-NM2 FAP12WFDBDBDLCZ 21055-6 FXBSCSCE2LM002 FXE3-10AM10 FXE3-10AM20 FXE3-10BM7 FXE3-10FM15 FXE3-10FM3 FXE3-10FM4 FXE3-10FM7 FXE3-10GM3 FZE10-10M6 FZOPE10-10M5 3000005 3-21053-2 MLB 200/1 V BLACK MLB 2001 V YELLOW MLB 501 V BLACK 5492011-6 106284-7000 5492011-5 5492011-8 5492011-9 CF-901201-007 7-21000-4 8-21007-5 8-21084-0 3-5106081-0 106386-4447 2-2064140-6 F92ELLNSNSNM003 2-2064140-3 6-2064140-3 2-2064140-2