

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Not for use in European Markets IEC-320-C13 to NEMA 5-15P Power Cord – Locking C13 Connector, 15A, 125V, 14 AWG, 3 ft., Black

MODEL NUMBER: P007-L03









Features

NEMA 5-15P to C13 Power Cable for Devices That Require a Heavy-Gauge ConnectionThis IEC-320-C13 to NEMA 5-15P power cord features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. You can use it to connect a computer, server, monitor, laser printer or drive to a PDU, UPS, surge protector or AC wall outlet. It can also replace or upgrade the standard power cord provided by the device's manufacturer. The three-foot length helps reduce cable clutter and minimize the risk of tripping.

Locking C13 Connector Helps Prevent Accidental Disconnection and Expensive DowntimeHaving a cable come loose accidentally can mean the loss of power and costly downtime. The locking C13 connector helps you avoid such danger, protecting critical equipment by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the power cord always stays connected.

Lifetime WarrantyThe P007-L03 is backed by a lifetime warranty, ensuring reliability and performance.

Highlights

- Recommended for powering larger servers, laser printers and other network devices
- 3 ft. length allows flexibility in placing devices, while avoiding cable clutter
- Thick 14 AWG wire gauge manages high power levels required for larger equipment
- Locking C13 connector maintains secure link to avoid loss of power and costly downtime

Applications

- Connect devices like computers, large servers and laser printers to a PDU up to 3 ft. away in your data center
- Extend an existing power connection up to 3 ft. to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

 P007-L03 IEC-320-C13 to NEMA 5-15P Power Cord, Locking C13 Connector, 3 ft., Black

Specifications

OVERVIEW	
UPC Code	037332218308



Country/Region	North America
INPUT	
Maximum Input Amps	15
Cable Length (ft.)	3
Cable Length (m)	0.9
Cable Length (in.)	36
Voltage Compatibility (VAC)	125
PHYSICAL	
Color	Black
Number of Conductors	3
Power Cord Jacket Type	SJT
Shipping Dimensions (hwd / cm)	25.40 x 18.01 x 1.27
Shipping Dimensions (hwd / in.)	10.00 x 7.09 x 0.50
Shipping Weight (kg)	0.19
Shipping Weight (lbs.)	0.41
Wire Gauge (AWG)	14
Wire Gauge (OD - mm ²)	2.08
ENVIRONMENTAL	
Operating Temperature Range	-4 to 221 F (-20 to 105 C)
Storage Temperature Range	-4 to 221 F (-20 to 105 C)
Relative Humidity	0-65% RH
CONNECTIONS	
Side A - Connector 1	NEMA 5-15P
Side B - Connector 1	IEC-320-C13 - LOCKING
SPECIAL FEATURES	
High Voltage	No
Heavy-Duty	Yes
Locking Plug	Yes
CERTIFICATIONS	
Certifications	UL Listed
WARRANTY	



Product Warranty Period (Worldwide)

Lifetime limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Cords category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below :

62500-1774 JP2P3-C2C-4I HFEC15U 312033-01 R7A-CAB005SR 523 BK078 374003-A01-L1 YP-61+YC12 YP21A+YC13 1689848-1 6601 1702002600 1700001947 1700018553 J2014003L001-CC SHELF IL13-EU1-H05-3100-300-S 366044-D01 PC20C19GY8 P28976-M45 ACC-500-215-R BB-3271V86 HFE/C19UO 390002-01 393001-01 318004-01 350050-LD01 369004-E01 370001-E01 VL-1024-23-300 6007.0214 1700001524 IL13-US1-SVT-3100-366 IL13-EU1-H05-3100-400 IL13-C14-H05-3100-200 IL13-US1-SVT-3100-275 IL13-SE-H05-3100-500 IL13-EU1-H05-3100-300 166S72 221001-03 223082-01 223083-01 232011-06 732-00/00 6000.0224 374003-A01 AC30UUK 373003-A01 AC30UEU 513 BK078 920 BK078