www.tripplite.com



DisplayPort to VGA Active Adapter Video Converter, DP ver 1.2 (M/F), 6-in. (15.24 cm), 50 pack

MODEL NUMBER: P134-06NVGAV2BP











Active adapter connects a VGA display to the DisplayPort (DP) 1.2 output on your laptop or desktop computer for playing 1080p video.

Features

DisplayPort to VGA Converters Connect DP Source to VGA DisplayThis set includes 50 Tripp Lite P134-06N-VGA-V2 DisplayPort to VGA active adapters. Each adapter connects a VGA monitor, television or projector to the DisplayPort 1.2 output on your PC, Mac, Chromebook, MacBook, Microsoft Surface or other compatible computer or tablet. They feature a male DP connector and a female HD15 connector, allowing you to continue using your existing VGA display and VGA cable to transmit video signals without the expense of a new DP display. They also are backward compatible with pre-1.2 DisplayPort generations.

Transmit Outstanding 1080p Video for High-Definition PresentationsIdeal for classrooms, lecture halls and anywhere else you may need to connect to a VGA monitor, these DisplayPort to VGA converters support computer video resolutions up to 1920 x 1200 (including 1080p) and HD video resolutions up to 1920 x 1080 (1080p). The active adapters convert both Single-Mode and Dual-Mode (DP++) DisplayPort output. They come recommended for use with graphics cards, such as AMD Eyefinity, that do not output DP++ signals.

Ready to Use Right Out of the PackageThe plug-and-play DP to VGA adapters require no software, drivers or external power, work with both Windows and Mac operating systems, and are compatible with laptops, tablets and other devices equipped with a female DisplayPort. With its small size and built-in cable, the P134-06N-VGA-V2 is recommended for stowing in your laptop bag and carrying to school or the office.

Highlights

- 50-piece bulk pack of P134-06N-VGA-V2 DisplayPort to VGA video adapters
- Delivers high-definition picture quality at resolutions up to 1920 x 1200 (1080p)
- Active adapter converts Singleand Dual-Mode DP++ output for viewing on VGA display
- Compact unit fits easily into briefcase or laptop bag for instant use anywhere
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect your newer laptop to an older VGA monitor in a lecture hall or conference room for a video presentation
- Add a secondary monitor to the PC or laptop in your office or home workspace
- Display menus, ads, promos, directions and other digital signage applications

System Requirements

- Source device with DisplayPort output
- Display device with HD15 input
- Not for use with MST Hubs

Package Includes

(50) P134-06N-VGA-V2
 DisplayPort to VGA Active
 Converters (M/F), 6 in.



Specifications

•		
OVERVIEW		
UPC Code	037332237743	
Technology	VGA/SVGA; DisplayPort	
VIDEO		
Max Supported Video Resolution	1920 x 1200 @ 60Hz	
INPUT		
Product Length (in.)	5.9	
Product Length (ft.)	0.49	
PHYSICAL		
Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	4.5mm	
Ferrite Core	No	
Material of Construction	ABS, PVC	
Shipping Dimensions (hwd / in.)	1.00 x 15.00 x 17.50	
Shipping Weight (kg)	1.77	
Unit Dimensions (hwd / in.)	1.46 x 0.57 x 1.77	
Unit Weight (kg)	0.10	
Unit Weight (lbs.)	0.22	
ENVIRONMENTAL		
Operating Temperature Range	32 to 158 F (0 to 70 C)	
Storage Temperature Range	14 to 176 F (-10 to 80 C)	
Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 90% RH, Non-Condensing	
CONNECTIONS		
Side A - Connector 1	DISPLAYPORT (MALE)	
Side B - Connector 1	HD15 (FEMALE)	
Connector Plating	Gold; Nickel	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Contact Plating	Gold; Nickel	
FEATURES & SPECIFICATIONS		
Displayport Specification	1.2	
Driver Required	No	
STANDARDS & COMPLIANCE		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Interface Modules category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

IFD8520 cPCI-3544 422CON ATX6022/14GP7 ATX6022/8 FC6A-EXM2 OPT8AP-AE 60006-016 96RMKVM-19V1C-A 60016-011 60016-014 60006-008 60016-015 60011-075 HPCI-14S12U cBP-3208 cBP-3062A FAB205-6P5 ATX6022/6 60016-012 96RMKVM-17V1C-A PCE-DP10-00A1E MOS-1120Y-0201E 96RMLCD-17V1-A 96RMKVM-17V8C-A 60004-005 60016-017 60006-019 60006-009 60016-035 60016-034 60016-031 60016-030 60016-026 60016-025 60016-024 60016-021 60016-018 60016-007 60016-006 60016-005 60016-004 60007-002 60006-018 60006-010 AXX10GBTWLHW3 382-BBEH 555-BDCL GW DEVICE SERVER 2E/4DB9 K6CMISZBI52