

DisplayPort to VGA/HDMI All-in-One Converter Adapter, DP ver 1.2, 4K 30 Hz HDMI, 50 Pack

MODEL NUMBER: P136-06N-HVV2BP









Passive adapter connects your DisplayPort (DP) computer to a VGA or HDMI display for playing 4K video without separate adapters.

Features

A Smart Solution for Displaying 4K Video in Business and Digital Signage ApplicationsThis set includes 50 Tripp Lite P136-06N-HV-V2 DisplayPort 1.2 to VGA/HDMI passive adapters. Each adapter allows you to play high-definition or Ultra High Definition video with audio from your DisplayPort computer to a VGA or HDMI display. No more carrying around separate adapters for various monitors, projectors and televisions. The simple all-in-one solution for displaying content on a larger screen, these units are an easy, inexpensive way to play high-quality video in classrooms, conference rooms, trade shows and other on-the-road presentations.

Ready to Use Right Out of the PackageIdeal for displaying video on a large monitor or digital sign, each adapter is perfectly sized for carrying in your pocket, briefcase, purse or laptop bag for convenient use anywhere. Just connect the male DP end to your computer's DisplayPort and the female VGA or HDMI connector to a compatible cable to begin sharing audio/video signals. Only one display may be connected at a time. The plug-and-play P136-06N-HV-V2 requires no software, drivers or external power. **Enjoy Outstanding Picture Quality up to 4K x 2K**The all-in-one unit contains separate female HD15 and HDMI ports. It supports video resolutions up to 1920 x 1200, including 1080p (HD15), and 4K x 2K (HDMI) at 24/30 Hz.

Passive Adapters Require DisplayPort++ for HDMI Pass ThroughBecause they are passive adapters, these units require that the connected source device have a DisplayPort++ (DP++) dual-mode port, which allows HDMI signals to pass through. Check your DisplayPort source's documentation for compatibility.

Highlights

- 50-piece bulk pack of P136-06N-HV-V2 DisplayPort 1.2 converter adapters
- HDMI port delivers UHD picture quality at 4K resolutions up to 3840 x 2160 @ 24/30 Hz
- VGA port supports HD video resolutions up to 1920 x 1200, including 1080p
- Compact unit fits easily into pocket, briefcase or laptop bag for use anywhere
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Play video from your DP laptop or PC on a large display, such as an HDTV
- Access documents and websites across multiple displays
- Design and edit graphics files or production video on a larger monitor
- Using a DisplayPort laptop to deliver presentations in a classroom or conference room
- Display menus, ads, promos, directions and other digital signage applications on an HD monitor

System Requirements

 Source device with DisplayPort output and DP++ port for HDMI pass-through (must support



audio to transmit audio signals)

 Display device with VGA or HDMI input

Package Includes

- (50) P136-06N-HV-V2
 DisplayPort 1.2 to VGA/HDMI
 All-in-One Converter Adapters
- Quick Start Guide

Specifications

OVERVIEW	
UPC Code	037332237675
Technology	HDMI; VGA/SVGA; DisplayPort
VIDEO	
Max Supported Video Resolution	HDMI: 3840 x 2160 @ 30Hz; VGA: 1920 x 1200 @ 60Hz
INPUT	
Product Length (in.)	5.9
Product Length (ft.)	0.49
PHYSICAL	
Color	Black
Cable Jacket Material	PVC
Cable Jacket Rating	VW-1
Cable Outer Diameter (OD)	4.5mm
Material of Construction	ABS, PVC
Shipping Dimensions (hwd / in.)	4.50 x 16.00 x 18.00
Shipping Weight (kg)	2.27
Unit Dimensions (hwd / in.)	2.36 x 0.55 x 1.57
Unit Weight (kg)	0.05
Unit Weight (lbs.)	0.1
ENVIRONMENTAL	
Operating Temperature Range	32 to 113 F (0 to 45 C)



Storage Temperature Range	14 to 176 F (-10 to 80 C)
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
CONNECTIONS	
Side A - Connector 1	DISPLAYPORT (MALE)
Side B - Connector 1	HD15 (FEMALE)
Side B - Connector 2	HDMI (FEMALE)
Connector Plating	Nickel
Contact Plating	Gold; Nickel
FEATURES & SPECIFICATIONS	
HDCP Specification	1.4
Driver Required	No
STANDARDS & COMPLIANCE	
Certifications	Tested to CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Interface Modules category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below :

 IFD8520
 CPCI-3544
 422CON
 ATX6022/14GP7
 ATX6022/8
 AX93221-24/48
 FC6A-EXM2
 OPT8AP-AE
 60006-016
 96RMKVM-19V1C

 A
 60016-011
 60016-014
 60006-008
 60016-015
 60011-075
 HPCI-14S12U
 cBP-3208
 cBP-3062A
 FAB205-6P5
 ATX6022/6
 60016-012

 96RMKVM-17V1C-A
 PCE-DP10-00A1E
 MOS-1120Y-0201E
 96RMLCD-17V1-A
 96RMKVM-17V8C-A
 60004-005
 60016-017
 60006

 019
 60006-009
 60016-035
 60016-034
 60016-031
 60016-026
 60016-025
 60016-021
 60016-018
 60016-007
 60016

 006
 60016-005
 60016-004
 60007-002
 60006-018
 60006-010
 AXX10GBTWLHW3
 382-BBEH
 555-BDCL
 GW DEVICE SERVER

 2E/4DB9

 60016-014
 60007-002
 60006-018
 60006-010
 AXX10GBTWLHW3
 382-BBEH
 555-BDCL
 GW DEVICE SERVER