

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

In most applications where the HDMI cable exceeds 16ft, a signal booster (B122-000-60) will need to be used with this cable to ensure a signal strong enough for your display

High-Speed HDMI Easy Pull Cable, Digital Video with Audio (M/M), 25 ft. (7.62 m)

MODEL NUMBER: P568-025-EZ



Description

Tripp Lite's 25-ft. (7.62 m) High Speed HDMI Easy Pull Monitor Cable w/ Connectors makes running long length video cables a snap. The pull-apart design allows the cable to be run through conduit or other tight areas that a HDMI connector wouldn't fit through. Diameter of the circular DIN end is only 7/8". Circular Easy Pull connector is threaded to ensure maximum security once the cable is reattached. Double shielding (foil and braid) provides maximum EMI/RFI protection. Both HDMI male ends are molded and have integral strain relief to provide long life. UL20276 Digital Video Cable supports 1080p. In most applications, a signal booster (B122-000-60) will need to be used with this cable to ensure a signal strong enough for your display.

Features

- Two-piece design runs through conduit or other tight areas
- Threaded circular DIN connector provides secure reattachment
- Superior-molded cables with foil and braid shielding for maximum EMI/RFI protection
- · High quality quad-shielded cable with Gold connectors and pins
- Bandwidth up to 10.2 Gbps Full 1080p resolution as specified by HDMI 1.2
- High Speed HDMI and HDCP compliant
- In most applications where the HDMI cable exceeds 16ft, a signal booster (B122-000-60) will need to be used with this cable to ensure a signal strong enough for your display
- HDMI male to male molded connectors
- UL20276 Digital Video Cable
- Supports High Definition (HD) video resolutions up to 1080p

Specifications

Highlights

- Two-piece design runs through conduit or other tight areas
- Threaded circular DIN connector provides secure reattachment
- Superior-molded cables with foil and braid shielding for maximum EMI/RFI protection
- Bandwidth up to 10.2 Gbps -Full 1080p resolution as specified by HDMI 1.2
- High Speed HDMI and HDCP
 compliant
- Supports High Definition (HD) video resolutions up to 1080p

Package Includes

 High Speed HDMI Easy Pull Cable, HD 1080p, Digital Video with Audio (M/M), 25-ft. (7.62 m)



OVERVIEW	
UPC Code	037332175564
Technology	HDMI
VIDEO	
Max Supported Video Resolution	1920 x 1080 @60Hz
PHYSICAL	
Color	Black
Wire Gauge (AWG)	28
Cable Length (ft.)	25
Cable Length (m)	7.6
Shipping Dimensions (hwd / cm)	2.54 x 17.53 x 22.35
Shipping Dimensions (hwd / in.)	1.00 x 6.90 x 8.80
Shipping Weight (kg)	0.41
Shipping Weight (lbs.)	0.90
CONNECTIONS	
Side A - Connector 1	HDMI (MALE)
Side B - Connector 1	HDMI (MALE)
FEATURES & SPECIFICATIONS	
HDMI Specification	1.2
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tripp Lite manufacturer:

Other Similar products are found below :

 79-653
 N001-015-YW
 N204-005-BL-UP
 N001-010-RD
 U152-003-M
 M100-006-WH
 79-519
 79-537
 PR40
 PV-400FC
 152-0199
 152-1380

 152-2404
 P022-015
 ISOBAR6
 RT-2
 3040
 SU1500RTXL2U
 PV1000HF
 B042-004
 INTERNET-OFFICE-280
 3251
 UL7408-6
 ULHC4-15

 DG115-SR
 P006-015
 CK-8455-L2
 SMART-1400-RM
 BC PERS300
 PS3612
 BCPRO600
 RS-0615-F
 RS-0615-R
 SUINT1000RTXL2U

 3310
 B078-101-USB-8
 SUINT1000LCD2U
 DCPU1
 DWT3270X
 DWM1742S
 DDR1327SDD
 TLM615NC20
 TLP806TELTAA
 PS3612

 20HW
 PDUMV30HV2
 OMNIVS800
 SMART1500RM2UN
 SU3000RTXLCD2U
 P005010
 SR14UBDP