

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## 4-Outlet Power Strip, 10 ft. (3.05 m) Cord, NEMA 5-15P Plug, 12 in.

## MODEL NUMBER: PS120410







Metal 12 in. power strip distributes power to multiple devices in an industrial, office, retail, rackmount, raceway, workbench or point-of-sale setting.

## Features

### **Ideal Power Distribution**

- Recommended for industrial, office, retail, rackmount, raceway, workbench and point-of-sale settings
- 4 NEMA 5-15R outlets with 1.77 in. center-to-center spacing
- 10-ft. (3.05 m) power cord with NEMA 5-15P plug
- Meets UL1363 (USA) and cUL (Canada) certifications

### **Premium Safety Features**

- 15A resettable circuit breaker prevents dangerous overloads
- Transparent switch cover eliminates accidental shutdowns
- · Lighted on/off switch confirms operation at a glance

### **Rugged All-Metal Housing**

- 12 in. length
- Hardware included for mounting on a wall, floor, workbench or under a counter

## **Specifications**

# OVERVIEW UPC Code 037332198525

## Highlights

- 4 NEMA 5-15R outlets with 1.77 in. center-to-center spacing
- 15A resettable circuit breaker
- Lighted on/off switch with
   transparent safety cover
- Heavy-duty all-metal housing
- 10-ft. (3.05 m) power cord with NEMA 5-15P plug

## Package Includes

- PS120410 4-Outlet Power Strip, 10-ft. (3.05 m) Cord, 12 in.
- Mounting hardware
- Owner's manual



INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A 120V
Input Cord Gauge Type	14 gauge; SJT
Voltage Compatibility (VAC)	120
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	10
Input Cord Length (m)	3.05
Integrated Cord Clip	No
OUTPUT	
Frequency Compatibility	50 / 60 Hz
Output (Watts)	1800
Output Receptacles	(4) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(2) Yes
Right-Angle Outlets	No
Outlet Spacing	1.77in.
USER INTERFACE, ALERTS & CON	TROLS
Switches	Lighted 2 position switch controls power to all outlets
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off
PHYSICAL	
Antimicrobial Coating	No
Color	Silver
Color (AC Line Cord)	Black
Form Factors Supported	Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications
Included Mounting Accessories	Includes mounting clips
Integrated Keyhole Mounting Slots	No
Material of Construction	Aluminum
Outlets Measurement (Center to Center)	1.77
Receptacle Color	Black
Shipping Dimensions (hwd / cm)	6.10 x 12.19 x 39.12
Shipping Dimensions (hwd / in.)	2.40 x 4.80 x 15.40



Shipping Weight (kg)	0.95	
Shipping Weight (lbs.)	2.10	
Unit Dimensions (hwd / cm)	3.18 x 4.12 x 30.48	
Unit Dimensions (hwd / in.)	1.25 x 1.62 x 12	
Unit Weight (kg)	0.58	
Unit Weight (lbs.)	1.28	
STANDARDS & COMPLIANCE		
Canada	cUL	
UL1363 (Power Tap)	UL1363	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tripp Lite manufacturer:

Other Similar products are found below :

 79-653
 N001-015-YW
 N204-005-BL-UP
 N001-010-RD
 U152-003-M
 M100-006-WH
 79-519
 79-537
 PR40
 PV-400FC
 152-0199
 152-1380

 152-2404
 P022-015
 ISOBAR6
 RT-2
 3040
 SU1500RTXL2U
 PV1000HF
 B042-004
 INTERNET-OFFICE-280
 3251
 UL7408-6
 ULHC4-15

 DG115-SR
 P006-015
 CK-8455-L2
 SMART-1400-RM
 BC PERS300
 PS3612
 BCPRO600
 RS-0615-F
 RS-0615-R
 SUINT1000RTXL2U

 3310
 B078-101-USB-8
 SUINT1000LCD2U
 DCPU1
 DWT3270X
 DWM1742S
 DDR1327SDD
 TLM615NC20
 TLP806TELTAA
 PS3612 

 20HW
 PDUMV30HV2
 OMNIVS800
 SMART1500RM2UN
 SU3000RTXLCD2U
 P005010
 SR14UBDP