

# For Patient-Care Vicinity–UL 60601-1 Medical-Grade Power Strip; 4 15A Hospital-Grade Outlets, Safety Covers, 6 ft. Cord

#### MODEL NUMBER: PS-406-HGULTRA











#### **Highlights**

- Approved for standalone use in all patient-care vicinities
- Complies with UL 60601-1 and UL 60950-1 specifications
- Patented protection circuit guards against shock hazards
- 4 NEMA 5-15R-HG hospital-grade outlets with locking safety covers
- 6 ft. cord with NEMA 5-15P-HG hospital-grade plug

#### Package Includes

- PS-406-HGULTRA UL 60601-1
   Medical-Grade Power Strip
- Owner's manual with maintenance requirements

#### Description

The PS-406-HGULTRA Medical-Grade Power Strip -- patent # 7,375,939 -- is designed with full 60601-1 compliance and agency listing, making it ideal for standalone use in all patient-care vicinities. This 120V, 50/60 Hz power strip features a NEMA 5-15P-HG hospital-grade plug and four NEMA 5-15R-HG hospital-grade outlets that include integrated locking safety covers.

A patented protection circuit guards against shock hazards by preventing power from reaching the unit's outlets in the presence of a fault. The protection circuit automatically resets itself and restores power once the fault threat is gone.

Mounting tabs and flanges let you install the PS-406-HGULTRA on a wide variety of surfaces. The all-metal housing ensures safety and is guaranteed to last a long time in demanding environments.

With a switchless design that prevents accidental shutoff and a 6-foot power cord that provides some flexibility in placing the power strip, the PS-406-HGULTRA is a recommended replacement for all non-compliant power strips.

#### **Features**

#### Power Distribution Anywhere in Any Medical Facility

- Ideal for standalone use in patient-care vicinities, therapy rooms, imaging environments and administrative areas
- Patented protection circuit guards against shock hazards with automatic site fault protection
- Circuit breaker resets itself once fault threat is gone
- 120V, 50/60 Hz power strip complies with UL 60601-1 and UL 60950-1 specifications
- Patent # 7,375,939

#### **Versatile Medical-Grade Solution**

- 4 NEMA 5-15R-HG hospital-grade outlets provide consistent power
- 6 ft. power cord provides ample reach to the power source



• Rugged all-metal housing for long life in demanding environments

#### **Premium Safety Features**

- Integrated locking outlet safety covers block access to unused outlets
- Built-in 15A circuit breaker protects against dangerous overloads
- Switchless design prevents accidental shut-off

#### Ready to Use Right Out of the Box

• Built-in mounting tabs and flanges for easy installation on a variety of surfaces

## **Specifications**

| OUTPUT                             |                                |  |
|------------------------------------|--------------------------------|--|
| Frequency Compatibility            | 60 Hz                          |  |
| Output Receptacles                 | (4) 5-15R-HG                   |  |
| Circuit Breaker (amps)             | 15                             |  |
| Overload Protection                | 15A resettable circuit breaker |  |
| Outlet Safety Covers               | Yes                            |  |
| Outlet Orientation                 | Single row of 4                |  |
| Right-Angle Outlets                | No                             |  |
| INPUT                              |                                |  |
| Nominal Input Voltage(s) Supported | 120V AC                        |  |
| Recommended Electrical Service     | 15A 120V                       |  |
| Input Connection Type              | NEMA 5-15P-HG                  |  |
| Input Cord Length (ft.)            | 6                              |  |
| Input Cord Length (m)              | 1.83                           |  |
| Voltage Compatibility (VAC)        | 120                            |  |
| USER INTERFACE, ALERTS & CONTROLS  |                                |  |
| Switches                           | No power switch                |  |
| PHYSICAL                           |                                |  |
| Unit Dimensions (hwd / in.)        | 1.5 x 13.75 x 2.5              |  |
| Unit Dimensions (hwd / cm)         | 3.8 x 34.9 x 6.4               |  |
| Unit Weight (lbs.)                 | 3.2                            |  |
| Unit Weight (kg)                   | 1.45                           |  |
| Material of Construction           | Metal                          |  |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| Integrated Keyhole Mounting Tabs                        | Yes  |  |
|---|--|--|
| Receptacle Color  | White  |  |
| Color (AC Line Cord)                                    | White  |  |
| Outlets Measurement (Center to Center)                  | 92mm   |  |
| Keyhole Slot Mounting<br>Measurement (Center to Center) | Distance between keyhole tabs = 261.92mm; Distance between end tabs = 334.01mm                                   |  |
| CERTIFICATIONS  |  |  |
| Approvals   | TUV tested to UL 60601-1 and UL 60950-1 (USA); TUV tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 (Canada) |  |
| Patented  | Patent # 7,375,939   |  |
| WARRANTY  |  |  |
| Product Warranty Period (Worldwide)                     | Lifetime limited warranty  |  |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Outlet Strips category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

G20IG606 1301430288 1301530208 1302100069 1301430321 1301530054 1447B163 1585T16A1RA UL602CB-6 UL7408-6 ULHC4-15

V20IG606 UL2063BD TSB 1301530203 4748.03 4309 UL7208-15 3083 3050F 3090 1301530132 1301530117 1301530164 1301530050

1301530141 1301430252 1301530179 1301530065 1301350158 1301530052 1301530068 1301530120 HB0B1L4BT08W1

VB0D2B2BM30P1 HA0A1D0CA10E1 HA0A1M2CM10E1 HA1A1D0CA10E1 VB0B1L2BN24H1 PN1A1C0BA10E1 HA0B1E0CA1081

HA0D2U0CA1081 HA0D2A0CA1081 HA1D2U0CA1081 HA1D2A0CA1081 HB1B2J0AA10M1 LZ1D2A0FA0AJ1 LZ1D2P0FA0AL1

VB0B1L4CN48M1 MA002