

# Power It! 7-Outlet Power Strip, 12-ft Cord, Diagnostic LED, Black Housing

MODEL NUMBER: PS712B





## **Highlights**

- 7 outlets
- 12 ft power cord
- Illuminated on/off switch
- 15 amp circut breaker
- · Keyhold mounting slots

## Package Includes

- PS712B Power Strip
- Instruction manual and warranty information

#### Description

Tripp Lite's PS712B power strip offers reliable, convenient and cost-effective power distribution for applainces, power tools, lighting and other electrical equipment. PS712B offers 7 total outlets, 12 foot cord. Attractive black housing with keyhole mounting slots and 1 designated transformer plug outlet. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket.

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/12 ft. AC line cord ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

#### **Features**

- 7 outlets / 12-ft cord
- Attractive black housing
- EMI/RFI noise filtering
- Can accommodate 1 transformer without blocking remaining outlets
- . Keyhole supports for wall mounting

# **Specifications**

ОИТРИТ	
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(7) 5-15R
Output (Watts)	1800
Circuit Breaker (amps)	15
Transformer Accommodation	Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 4 transformers total





Outlet Orientation	Single row
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input Connection Type	NEMA 5-15P
Input Cord Length (ft.)	12
Input Cord Length (m)	3.66
Input Cord Gauge Type	14 gauge, SJT
Voltage Compatibility (VAC)	120
Maximum Surge Amps	72000
USER INTERFACE, ALERTS & CON	TROLS
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch
DATALINE SURGE SUPPRESSION	Ι.,
Cable (Coax) Protection	No L.
Network (Ethernet) Protection	No
PHYSICAL	
Shipping Dimensions (hwd / in.)	13.78 x 4.92 x 2.36
Shipping Dimensions (hwd / cm)	35.00 x 12.50 x 5.99
Shipping Weight (lbs.)	1.92
Shipping Weight (kg)	0.87
Unit Dimensions (hwd / in.)	1.32 x 2.05 x 11.69
Unit Dimensions (hwd / cm)	3.35 x 5.21 x 29.69
Unit Weight (lbs.)	1.76
Unit Weight (kg)	0.80
Material of Construction	Plastic
Integrated Keyhole Mounting Tabs	Keyhole mounting slots enable wall mounting
Receptacle Color	Black
Color (AC Line Cord)	Black
Outlets Measurement (Center to Center)	Distance between standard outlets = 29mm; Distance between last standard outlet and transformer outlet = 33mm
Keyhole Slot Mounting Measurement (Center to Center)	Distance between slots = 151mm; Distance between slot height = 24mm



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

CERTIFICATIONS		
Additional International Approvals	RoHS	
NOM (Mexico)	NOM	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Outlet Strips category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

G20IG606 1301430288 1301530208 1302100069 1301430321 1301530054 1447B163 1585T16A1RA UL602CB-6 UL7408-6 ULHC4-15

V20IG606 UL2063BD TSB 1301530203 4748.03 4309 UL7208-15 3083 3050F 3090 1301530132 1301530117 1301530164 1301530050

1301530141 1301430252 1301530179 1301530065 1301350158 1301530052 1301530068 1301530120 HB0B1L4BT08W1

VB0D2B2BM30P1 HA0A1D0CA10E1 HA0A1M2CM10E1 HA1A1D0CA10E1 VB0B1L2BN24H1 PN1A1C0BA10E1 HA0B1E0CA1081

HA0D2U0CA1081 HA0D2A0CA1081 HA1D2U0CA1081 HA1D2A0CA1081 HB1B2J0AA10M1 LZ1D2A0FA0AJ1 LZ1D2P0FA0AL1

VB0B1L4CN48M1 MA002