

Protect It! 3-Outlet Surge Protector, Direct Plug-In, 660 Joules, 2 Diagnostic LEDs

MODEL NUMBER: SK3-0











Highlights

- 3 outlets/direct plug-in
- 660 joule rating
- Diagnostic LEDs

Package Includes

• SK3-0 surge suppressor

Description

The SK3-0 surge suppressor offers reliable surge and line noise protection. The compact direct plug-in design allows for easy portability and features 3 outlets and 660 joules of surge energy absorption.

Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged.

\$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 3 outlets / direct plug-in
- Surge suppression rating: 660 joules
- EMI/RFI noise filtering
- Diagnostic LEDs indicate Protected (green) & Grounded (red)
- \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

Specifications

OVERVIEW		
UPC Code	037332166319	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V	



Input Cord Length Details	Direct Plug-In
Voltage Compatibility (VAC)	120
Maximum Surge Amps	39000
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	0
Right-Angle Plug	No
Input Cord Length (m)	0.00
Integrated Cord Clip	No
ОИТРИТ	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(3) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(2) Yes
Right-Angle Outlets	No
USER INTERFACE, ALERTS & CON	ITROLS
Diagnostic LED(s)	Yes
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	660
AC Suppression Response Time	<1ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
Clamping Voltage (RMS)	150
AC Suppression Surge Current Rating	27,000
UL1449 Let Through Rating	500, 400, 500
EMI / RFI Filtering	Yes
Immunity	Conforms to IEE 587/ANSI C62.41
Automatic Shut-Off	Yes
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	





Antimicrobial Coating	No	
Housing Color	Light Gray	
Integrated Keyhole Mounting Slots	No	
Material of Construction	Plastic	
Receptacle Color	Light gray	
Shipping Dimensions (hwd / cm)	14.99 x 7.62 x 6.86	
Shipping Dimensions (hwd / in.)	5.90 x 3.00 x 2.70	
Shipping Weight (kg)	0.15	
Shipping Weight (lbs.)	0.32	
Unit Dimensions (hwd / cm)	6.35 x 9.7 x 5.33	
Unit Dimensions (hwd / in.)	2.5 x 3.8 x 2.1	
Unit Weight (kg)	0.09	
Unit Weight (lbs.)	.20	
SPECIAL FEATURES		
Rotatable Outlets	No	
STANDARDS & COMPLIANCE		
Approvals	RoHS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$5,000 Ultimate Lifetime Insurance	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Outlet Strips category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

G20IG606 1301430288 1301430321 1447B163 UL602CB-6 UL7408-6 ULHC4-15 V20IG606 UL2063BD TSB 4748.03 4309 UL720815 3083 3050F 3090 1301350158 1301350173 3085-10 DAPI-USEU 1583H8B1BKV 1589H77D1JV 1589H77G1JV 1589H8D1BKRRV
1589H8G1BKRRV DTEL2 TLP712B STRIKER TLM825SA UL620-15 3SP 1301370166 130143-0153 1301370216 602 6SP 1584B10
1589H48G1 1589T6D1 1301350185 1301350186 1301350187 1301350197 1301350233 1301350234 1301350201 1301350207
1301350209 1301350211 1301350213