6-Outlet Surge Protector w/2 USB-A (2.4A Shared) & 1 USB-C (3A) - 8 ft. Cord, 1080 Joules, Desk Clamp

MODEL NUMBER: **TLP648USBC**

6-outlet desk-clamp surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

Features

6-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics Ideal for your home or office workstation, this Protect It!® 6-outlet surge protector features a surge protection rating of 1080 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP648USBC protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

Spring-Loaded Desk Clamp Protects Equipment at Any Workstation This portable surge protector features a spring-loaded clamp that attaches to any flat, smooth surface up to 2.5 inches thick, so you can take it with you to the office, dorm, conference room, hotel or anywhere else you need to plug in your electronic devices. The eight-foot power cord with NEMA 5-15P plug pivots 90 degrees to accommodate installation to a horizontal or vertical surface.

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices Plug your computer, printer, wireless router, desk lamp or other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise.

3 USB Ports for Charging Mobile Devices This surge protector with 3 USB ports is ideal for keeping your devices at full capacity. Two USB-A ports share 2.4 amps for charging your smartphone, tablet and other USB mobile devices, which are also protected from the damaging effects of surges, spikes and line interference. In addition to the dual USB-A ports, a 3-amp USB-C port charges devices quickly and safely.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety Features The on/off switch provides one-touch control over connected equipment. Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required. A green LED confirms your connected equipment is protected.

Highlights

- 6 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 1080 joules protect your valuable electronics against dangerous surges and spikes
- 2 USB-A/1 USB-C ports for fast charging of phones, tablets and other mobile devices
- 8 ft. pivoting power cord with NEMA 5-15P plug easily adjusts to nearby wall outlets
- Spring-loaded clamp attaches to flat surface up to 2.5 in. thick for use anywhere

Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

Package Includes

- TLP648USBC Protect It! 6-Outlet Surge Protector with Desk Clamp
- Owner's manual

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Specifications

OVERVIEW	
UPC Code	037332231130

OUTPUT	
Charging Ports / Amps	(1) 3A; (2) 2.4A
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(6) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(2) Yes
Right-Angle Outlets	No

INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V
Input Cord Length Details	8 ft cord
Voltage Compatibility (VAC)	120
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	8
Right-Angle Plug	No
Input Cord Length (m)	2.44
Integrated Cord Clip	No

USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED(s)	Yes

SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	1080
AC Suppression Response Time	< 1ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
Clamping Voltage (RMS)	500
UL1449 Let Through Rating	500, 500, 600
EMI / RFI Filtering	Yes

2 / 3

Immunity	Conforms to IEE 587/ANSI C62.41
Auto Shut-Off	Yes

DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No

PHYSICAL	
Anti-Microbial Protected	No
Color	Light Gray
Color (AC Line Cord)	Gray
Housing Color	Cool Gray 4C
Integrated Keyhole Mounting Slots	No
Material of Construction	Plastic
Receptacle Color	Gray
Shipping Dimensions (hwd / in.)	5.43 x 4.72 x 6.73
Shipping Weight (kg)	0.88
Unit Dimensions (hwd / cm)	13.21 x 6.86 x 13.46
Unit Dimensions (hwd / in.)	5.2 x 2.7 x 5.3
Unit Weight (kg)	0.78
Unit Weight (lbs.)	1.72

CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
Approvals	RoHS

WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	$50,000 Ultimate Lifetime Insurance

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Outlet Strips *category:*

Click to view products by Tripp Lite *manufacturer:*

Other Similar products are found below :

G20IG606   1301430288   1301530208   1302100069   1301430321   1301530054   1447B163   1585T16A1RA   UL602CB-6   UL7408-6   ULHC4-15   V20IG606   UL2063BD   TSB   1301530203   4748.03   4309   UL7208-15   3083   3050F   3090   1301530132   1301530117   1301530164   1301530050   1301530141   1301430252   1301530179   1301530065   1301350158   1301530052   1301530068   1301530120   HB0B1L4BT08W1   VB0D2B2BM30P1   HA0A1D0CA10E1   HA0A1M2CM10E1   HA1A1D0CA10E1   VB0B1L2BN24H1   PN1A1C0BA10E1   HA0B1E0CA1081   HA0D2U0CA1081   HA0D2A0CA1081   HA1D2U0CA1081   HA1D2A0CA1081   HB1B2J0AA10M1   LZ1D2A0FA0AJ1   LZ1D2P0FA0AL1   VB0B1L4CN48M1   MA002