



ECO-Surge 7-Outlet Surge Protector, 6 ft. Cord, 1080 Joules, 6 Individually Controlled Outlets, Black Housing

MODEL NUMBER: TLP76MSGB











Environmentally friendly surge protector with individually controlled outlets safeguards your PC, printer, scanner, router, phone, fax, modem and other home/office electronics against dangerous surges, spikes and line noise.

Description

The TLP76MSGB ECO-Surge™ 7-Outlet Surge Protector protects more than just your vital electronics. It's an ideal green protection solution for your bottom line and the environment. Its energy-saving outlet configuration reduces waste (and costs) by cutting AC power to devices that aren't being used.

One NEMA 5-15R outlet is always on for a device that requires constant power, such as a router or DVR. The other six NEMA 5-15R outlets have individual on/off switches, so if you aren't using the device plugged into it, you can power off the outlet to save energy. Another illuminated on/off switch provides one-touch control to all outlets except the one that is always on.

Recommended for your home or office, the ECO-Surge Protector features 1080 joules to defend your components against even the strongest surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP76MSGB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

An integrated circuit breaker protects all outlets and automatically shuts down connected equipment in case of overload. The six-foot AC power cord with NEMA 5-15P plug allows the black surge protector to reach distant outlets.

Features

Highlights

- 7 NEMA 5-15R outlets—6 with individual on/off switches
- 1080-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- Automatic shutoff protects against dangerous overloads
- 6 ft. AC power cord with NEMA
 5-15P plug

Package Includes

- TLP76MSGB ECO-Surge 7-Outlet Surge Protector
- · Owner's manual



ECO-Surge Protector with Green Power-Saving Outlets⁶ NEMA 5-15R outlets have individual on/off switches to cut power to devices not being used, which saves energy and moneyOne NEMA 5-15R outlet stays powered on 24/7 for essential devices, such as a router or DVRMaster on/off switch provides one-touch control over all outlets except the "always on" outletAccommodates up to 4 bulky transformer plugs 1080-Joule Surge Protection for Home or Office Electronics*Protects your computer, printer, scanner, router, modem and other electronics against even the strongest surges and spikesFull normal mode (H-N) and common mode (N-G/H-G) line surge suppressionFilters out disruptive EMI/RFI line noise that can cause equipment damage or data lossExceeds IEEE 587 Category A and B surge suppression specifications

Premium Safety FeaturesAutomatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is requiredDiagnostic LEDs confirm surge protection status and "always on" connection at a glanceConforms to current UL 1449 3rd Edition safety standards

Fits Effortlessly Into Your Workstation6 ft. AC power cord with NEMA 5-15P plug conveniently reaches distant outletsKeyhole slots on bottom panel provide convenient wall or desk mounting optionsBlack plastic housing designed for long life

Backed by Tripp Lite's Ultimate Lifetime Insurance\$25,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

Specifications

OVERVIEW		
UPC Code	037332205810	
ОИТРИТ		
Output Volt Amp Capacity (VA)	120	
Output Watt Capacity (Watts)	1800	
Frequency Compatibility	60 Hz	
Output (Watts)	1800	
Output Receptacles	(7) 5-15R	
Transformer Accommodation	(4) Yes	
Right-Angle Outlets	Yes	
Individually Controllable Load Banks	Yes	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	72000	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	





No		
USER INTERFACE, ALERTS & CONTROLS		
Yes		
1 x Lighted Master Switch & 6 x Lighted Receptacle Switches		
Protected (Green)" & Always On Receptacle (Red)		
Trocolou (crossly a ranayo chi rosophasis (risa)		
SURGE / NOISE SUPPRESSION		
1080		
< 1 ns		
Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression.		
150		
400v		
Up to 40 dB		
Yes		
DATALINE SURGE SUPPRESSION		
No		
No		
No .		
No		
Black		
Black		
Yes		
Plastic		
Black		
5.08 x 10.67 x 43.18		
2.00 x 4.20 x 17.00		
0.82		
1.80		
3.56 x 8.64 x 38.1		
1.40 x 3.40 x 15		
0.70		
i		





Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
Canada	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Outlet Strips category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

G20IG606 1301430288 1301530208 1302100069 1301430321 1301530054 1447B163 1585T16A1RA UL602CB-6 UL7408-6 ULHC4-15

V20IG606 UL2063BD TSB 1301530203 4748.03 4309 UL7208-15 3083 3050F 3090 1301530132 1301530117 1301530164 1301530050

1301530141 1301430252 1301530179 1301530065 1301350158 1301530052 1301530068 1301530120 HB0B1L4BT08W1

VB0D2B2BM30P1 HA0A1D0CA10E1 HA0A1M2CM10E1 HA1A1D0CA10E1 VB0B1L2BN24H1 PN1A1C0BA10E1 HA0B1E0CA1081

HA0D2U0CA1081 HA0D2A0CA1081 HA1D2U0CA1081 HA1D2A0CA1081 HB1B2J0AA10M1 LZ1D2A0FA0AJ1 LZ1D2P0FA0AL1

VB0B1L4CN48M1 MA002