

## USB-C to RS232 (DB9) Serial Adapter Cable (M/M), 5 ft. (1.52 m)

MODEL NUMBER: U209-005-C



Connect a device with a 9-pin RS-232 serial port to the USB Type-C port on your computer, laptop, tablet or smartphone. Perfect for connecting modems, digital cameras, PDAs and ISDN terminals.

### Features

#### Connects a DB9 Device to a USB-C Device

- Ideal for connecting a modem, digital camera, PDA or ISDN terminal to your computer, laptop, tablet or smartphone
- Supports data transfer speeds up to 230 Kbps—twice as fast as a built-in serial port
- No external power source required
- Portable 5 ft. design fits perfectly into laptop bag

#### First-Rate Construction for Superior Signal Transfer

- Premium foil and braid shielding for EMI/RFI noise protection
- Molded nickel-plated connectors with gold-plated contacts for optimal signal quality
- Integral strain relief for long life
- Twisted 28/24 AWG data/power lines
- Flexible PVC jacket easy to install in tight spaces

#### Broad Compatibility

- Compatible with Windows, Mac, Linux and Android devices (see System Requirements for details)

## Specifications

### OVERVIEW

### Highlights

- Supports data transfer speeds up to 230 Kbps
- Premium foil and braid shielding reduces EMI/RFI interference
- Compatible with Windows®, Mac®, Linux® and Android™ devices
- No external power source required
- Portable 5 ft. design fits perfectly into laptop bag

### System Requirements

- Windows 2000 and later (including Windows 10), Mac OS X 10.6 through 10.12 or Linux Redhat 7.3 through 9.0 (Linux Kernel 2.4.31 and above include built-in drivers)
- Android devices with USB Host Mode (OTG) support and OS 3.2 and later. USB Host Mode (OTG) cable required.

### Package Includes

- U209-005-C USB-C to DB9 Serial Adapter Cable (M/M), 5 ft.
- Owner's manual



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

UPC Code	037332197573
Technology	Serial (RS232); USB
<b>PHYSICAL</b>	
Color	Black
Cable Length (ft.)	5
Cable Length (m)	1.52
Shipping Dimensions (hwd / cm)	3.10 x 11.18 x 11.68
Shipping Dimensions (hwd / in.)	1.22 x 4.40 x 4.60
Shipping Weight (kg)	0.09
Shipping Weight (lbs.)	0.20
<b>CONNECTIONS</b>	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	DB9 (MALE)
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Computer Cables](#) category:*

*Click to view products by [Tripp Lite](#) manufacturer:*

Other Similar products are found below :

[68809-0004](#) [8F36-AAA105-1.00](#) [IB63](#) [CB-716EB-RS](#) [CB-716P8P9-RS](#) [CBK-11-290K-00](#) [ACL-10550](#) [ACL-10568-2](#) [ACL-10568-5](#)  
[427522400-3](#) [32102-021500-200-RS](#) [426091300-3](#) [48000023](#) [10114976-P015002LF](#) [10111838-S444ALF](#) [88761-6101](#) [NT631C-CN321-EU](#)  
[ACL-10568NF-1](#) [MIKROE-2092](#) [PCL-101100R-2E](#) [1700009405](#) [PS/2 Cable](#) [NT31C-CN323-EU](#) [PCL-10168H-1E](#) [68801-1905](#) [111068-](#)  
[1015](#) [100436-1107](#) [68801-0630](#) [68801-3612](#) [68801-3618](#) [205058-1002](#) [PS2NK](#) [SATA cable](#) [96021-0000-00-0](#) [FAK-SMZSMZ 5M](#) [FAK-](#)  
[SMZSMZ-3M](#) [ACC-500-200-R](#) [iW-C40-PCIe08-C1](#) [1700001531](#) [96048-0000-00-0](#) [96054-0000-00-0](#) [SATA III cable 30cm, down/straight](#)  
[cab-Pico-ITX-LVDS](#) [PCL-101100SB-2E](#) [AXXSTCBLQAT](#) [NT31C-KBA05](#) [PCL-101100M-2E](#) [A2U4PSWCXCXK1](#) [2 port SATA to 5](#)  
[pin,L=200mm](#) [P782-006-DH](#)