

# USB 3.0 SuperSpeed Adapter - USB-A to USB-A, M/F, Up Angle, Black

## MODEL NUMBER: U324-000-UP





Converts a standard USB port into a more convenient up-angled USB port in tight spaces, such as

behind furniture or against a wall.

#### Features

**One-Piece Adapter Connects Computers, Printers, Modems and Other USB Equipment**This palmsized USB adapter connects your computer, laptop or other compatible USB-A device, such as a Chromebook or Surface Pro tablet, to a USB-A keyboard, printer, portable hard drive, flash drive, patch panel or other peripheral. It supports USB 3.0 data transfer speeds up to 5 Gbps, which is 10 times faster than USB 2.0. The fully molded piece is small enough to carry in your pocket, purse or laptop bag. **Up-Angle USB-A Port Makes Connecting and Disconnecting Easier in Tight Spaces**The female USB connector is designed at a 90-degree up angle, which makes it easier to reach in from above to connect cables where space is at a premium. This helps you, for instance, save space in your workspace by letting you push your PC flush against the wall or the back of a cabinet. Instead of leaving space in the rear for protruding USB cables, the U324-000-UP allows you to connect cables parallel to your computer.

### Highlights

- Recommended for powering computers, printers and other home/office peripherals
- 90-degree-angled form factor is ideal for tight spaces, such as flush against a wall
- Supports USB 3.0 SuperSpeed data transfer rates up to 5 Gbps—10x faster than USB 2.0
- Durable one-piece molded adapter fits easily in pocket or bag for connecting anywhere
- Plug-and-play operation with no software required for easy, immediate installation

#### Applications

- Connect devices like computers, servers and external hard drives in your data center, workspace or home theater
- Create a USB connection in a hard-to-reach space, such as against a wall or behind a desk

#### Package Includes

U324-000-UP USB 3.0
 SuperSpeed Adapter

# Specifications

OVERVIEW	
UPC Code	037332248671
Technology	USB 3.0 (SuperSpeed)
PHYSICAL	
Color	Black



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Material of Construction	PVC	
Shipping Dimensions (hwd / in.)	5.00 x 4.00 x 0.50	
Unit Packaging Type	Polybag	
ENVIRONMENTAL		
Operating Temperature Range	32 to 122 F (0 to 50 C)	
Storage Temperature Range	-4 to 140 F (-20 to 60 C)	
Relative Humidity	10 - 90%, Non-Condensing	
CONNECTIONS		
Side A - Connector 1	USB 3.0 A (MALE)	
Side B - Connector 1	USB 3.0 A (FEMALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.0 (up to 5 Gbps)	
STANDARDS & COMPLIANCE		
Certifications	Tested to RoHS and REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below :

 950
 A-USB A-LP-SMT-C
 A-USB B-TOP-C
 MUSBA511N5
 MUSBD11135
 217450-1
 KMBVX-TH-5S-B30
 896-30-004-00-000000

 KUSBX-AS2N-W
 KUSBX-SMT2AP1S-W30
 935
 957
 30-498-6
 SK-60A-2
 1734082-1
 CIR08AF-20-27S-F80-20
 CIR08F-20
 30-1574
 30 

 470
 30-489
 30-541
 30-572-3
 A-USB A-2P-C
 MIKROE-1451
 USBFTV2PEM2G
 USBFTVC6ZN
 USBFTVSCCG
 4689-1
 1-1734084-2

 CIR08F-20-27P-F80-VO
 USBF21ZNSCC
 USBBFTV6ZC
 MUSBB151341
 10135326-001LF
 M9177/3-1
 USB-A-S-F-B-VT
 925
 4198
 690 

 024-633-031
 UB-20PMFP-LC7001
 USBFTVC6MRG
 UA-20BMFA-SL8001
 17-200011
 USBFTVC7ZC
 UB-20AFMM-LL7A01

 USBFTVC2MN
 CAP-WCCMLPB1
 CAP-WCCMLPC1
 2041386-1
 2274475-3