



USB-C to USB-A Adapter (M/F), 3.1 Gen 1 (5 Gbps)

MODEL NUMBER: U428-000-F





Connects an existing USB Type-A device or cable to the USB-C port on your smartphone, tablet, Ultrabook or computer in order to share data or charge a mobile device.

Description

The U428-000-F USB 3.1 Gen 1 Adapter connects your new USB-C smartphones, tablets, Ultrabooks and computers to your existing USB-A devices or cables in order to share data or charge a mobile device. It supports USB 3.1 Gen 1 data transfer speeds up to 5 Gbps and power output up to 3A for fast charging of mobile devices. Unlike traditional USB connectors that can be attached only one way, the reversible USB-C male connector plugs into a USB port in either direction for fast, fumble-free connection every time. Nickel-plated molded end connectors and gold-plated copper contacts ensure superior conductivity and long life. Slim form supports evolving design trends toward smaller devices. Backward compatible with USB 2.0 devices.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum

Features

Supports USB 3.1 Gen 1Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0Supports power output up to 3A—perfect for fast charging most mobile devicesUses same USB-A female connector as USB 3.0 devicesBackward compatible with USB 2.0 devices

Reversible USB-C Male ConnectorFumble-free reversible plug ensures fast, easy connection every timeStrong enough for tablets, laptops and other larger platforms

Premium ConstructionGold-plated copper contacts and nickel-plated molded ends provide a lifetime of heavy use and superior conductivitySlim, sleek design tailored for emerging design trends toward smaller devices

Specifications

OVERVIEW	
UPC Code	037332190826
INPUT	

Highlights

- Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0
- Supports power output up to 3A for fast charging of mobile devices
- Fumble-free reversible USB-C plug on one end
- Backward compatible with USB 2.0 devices
- Slim design tailored for emerging trends toward smaller devices

System Requirements

- Device with USB-C port
- Device or cable with USB-A plug

Package Includes

 U428-000-F USB 3.1 Gen 1 (5 Gbps) Adapter, USB-C to USB-A M/F





Bus Powered	Yes
POWER	
Power Consumption (Watts)	0.10
CONNECTIONS	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	USB 3.0 A (FEMALE)
Connector Plating	Nickel
PHYSICAL	
Color	Black
Material of Construction	PVC
Shipping Dimensions (hwd / in.)	5.90 x 3.90 x 0.50
Shipping Weight (lbs.)	0.02
Unit Dimensions (hwd / in.)	5.900 x 3.900 x 0.500
Unit Packaging Type	Polybag
Unit Weight (lbs.)	0.01
Unit Weight (kg)	0.00
ENVIRONMENTAL	
Operating Temperature Range	32° to 158°F (0° to 70°C)
Storage Temperature Range	14° to 176°F (-10° to 80°C)
Relative Humidity	10% to 90 % RH, Non-Condensing
BTUs	0.34 BTU/Hr
Power Provided to Connected Device(s)	5V 3A (15W) Output
FEATURES & SPECIFICATIONS	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
UASP Support	Yes
Driver Required	No
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

950 A-USB A-LP-SMT-C A-USB B-TOP-C MUSBD11135 17-200721 217450-1 KMBVX-TH-5S-B30 KUSBX-AS2N-W KUSBX-SMT2AP1S-W30 935 957 30-498-6 SK-60A-2 1734082-1 30-470 30-489 30-541 MIKROE-1451 USBFTVSCCG 1-1734084-2 10135326-001LF USB3FTV7APEG 4198 1310-1023-02 690-024-633-031 UB-20PMFP-LC7001 17-200011 UB-20AFMM-LL7A01 1040870124 CAP-WCCMLPB1 2274475-3 UB-20BMFA-SL8001 UB-20BFM-SA7A02 UB-20BFM-SA7A05 914-614A2025S10200 MUSBR-AHD2-M41-SK ZX40-B-5S-1500-STDA(30) GSB3116344HR USB3FTV2SAZNF459 USBF21GSCC U221-041N-1WVS62-F5D HYCW153-USBD05-500B HYCW219-USBD05-075B HYCW148-USBD05-117B HYCW149-USBD05-740B HYCW204-USBD05-108B HYCW214-USBA04-113B HYCW213-USBA04-113B UB-20AMFM-SL7A01 KMMX-BSMT35S-1-B30TR