

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

USB-C Multiport Adapter, 4K HDMI, 3 USB-A Ports, 100W PD Charging, HDCP, Gray

MODEL NUMBER: U444-06N-H3U-C











4K USB-C adapter with PD Charging connects a 4K HDMI monitor and 3 USB peripherals to a USB-C or Thunderbolt 3 device.

Features

Mini Docking Station Connects an HDMI Monitor to Your USB-C or Thunderbolt 3 Device

This USB-C to HDMI cable helps you transmit digital audio and 4K video from your tablet, laptop, Chromebook, MacBook, smartphone or PC to an HDMI-enabled television, monitor or projector. It's an ideal tool for giving video presentations in conference rooms and classrooms, editing multiple documents on a larger screen, or streaming video for digital signage in crystal-clear 4K.

Supports USB-C DisplayPort Alternate Mode for Transmitting Audio/Video Signals

By connecting the built-in USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers.

Transmits Crystal-Clear 4K HDMI Video and Digital Audio

To send digital audio and Ultra High Definition video to a 4K-ready HDMI television, projector or monitor, connect the HDMI port to the display using an HDMI cable (such as Tripp Lite's P568-Series high-speed HDMI cables, sold separately). The USB to HDMI 4K adapter supports video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz. It's backward compatible with 1080p displays, allowing you to use it with older equipment.

USB Ports Transfer Data at Fast USB 3.1 Gen 1 Speeds

Three USB-A ports accept USB peripherals, such as a flash drive, keyboard and printer, and transfers data at speeds up to 5 Gbps, which is 10 times faster than USB 2.0. One port provides up to 5V/1.5A (7.5 watts) for charging and powering mobile devices. The USB Type-C adapter is backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices.

Note: Host must support USB OTG (On-the-Go)

PD Charging Port Charges Connected Device via AC Wall Charger

The USB-C Power Delivery 3.0 port provides power output up to 20V 5A (100W), which is more than sufficient for charging and powering the connected source device, such as a MacBook or Chromebook.

Note: USB-C PD port does not support Quick Charge (QC).

Built-In USB-C Cable Connects in Either Direction

Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Ready to Use Right Out of the Package

The plug-and-play USB 3.1 Type-C adapter is specifically designed for the MacBook, Google Chromebook Pixel and other laptops, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no software, drivers or external power. About the size of a credit card, the U444-06N-H3U-C fits easily into a pocket, purse or laptop bag for convenient connections on the go.

Highlights

- Transmits video signals from sources supporting USB-C DisplayPort Alt Mode
- Delivers UHD picture quality at resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz
- Power Delivery port provides
 20V 5A (100W) power output for charging connected device
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- 3 USB-A ports support USB 3.1
 Gen 1 speeds up to 5 Gbps for fast data transfers

Applications

- Play 4K video from your
 MacBook or Chromebook on a
 large-screen HDTV
- Give a video presentation at a meeting, training session or conference
- Write and edit multiple documents on a bigger monitor
- Stream 4K video for digital signage at a trade show
- Charge and power a USB-C or Thunderbolt 3 device
- Connect USB peripherals, such as an external hard drive, printer and hub

System Requirements

 Source device with USB-C or Thunderbolt 3 output that supports USB DisplayPort
 Alternate Mode



• Display device with HDMI input

Package Includes

- U444-06N-H3U-C USB 3.1 C
 Adapter with PD Charging, Gray
- Owner's manual

Specifications

| OVERVIEW | |
|--|--|
| UPC Code | 037332238771 |
| Technology | HDMI; USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1) |
| Host Connector | USB C (MALE) |
| VIDEO | |
| Max Supported Video Resolution | 3840 x 2160 @ 30 Hz |
| INPUT | |
| Built-In Cable Length (ft.) | 0.392 |
| Built-In Cable Length (m) | 0.119 |
| Built-In Cable Length (in.) | 4.7 |
| Built-In Cable Length (cm) | 11.938 |
| Bus Powered | Yes |
| Product Length (in.) | 8.3 |
| Product Length (cm.) | 21.08 |
| Product Length (ft.) | 0.692 |
| Product Length (m.) | 0.211 |
| POWER | |
| USB Power Delivery (PD) Charging Support | Yes |
| USER INTERFACE, ALERTS & CON | TROLS |
| LED Indicators | N/A |
| CHARGING | |
| Charging Ports / Amps | (1) 1.5A; (1) 5A |



| PHYSICAL | | |
|---------------------------------------|---|--|
| Color | Gray | |
| Cable Jacket Rating | VW-1 | |
| Material of Construction | Aluminum | |
| Unit Dimensions (hwd / in.) | .45 x 1.77 x 3.35 | |
| Unit Packaging Type | Box | |
| Unit Weight (kg) | 0.09 | |
| Unit Weight (lbs.) | 0.203 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | 32 to 113 F (0 to 45 C) | |
| Storage Temperature Range | 14 to 158 F (-10 to 70 C) | |
| Operating Humidity Range | 10% to 85% RH, non-condensing | |
| Storage Humidity Range | 5% to 90% RH, non-condensing | |
| Power Provided to Connected Device(s) | USB-C PD Charging = 20V 5A (100W), USB-A = 5V 1.5A (7.5W) | |
| CONNECTIONS | | |
| Ports | 5 | |
| Side A - Connector 1 | USB C (MALE) | |
| Side B - Connector 1 | HDMI (FEMALE) | |
| Side B - Connector 2 | USB A (FEMALE) | |
| Side B - Connector 3 | USB A (FEMALE) | |
| Side B - Connector 4 | USB A (FEMALE) | |
| Side B - Connector 5 | USB Type-C (FEMALE) | |
| Connector Plating | Nickel | |
| FEATURES & SPECIFICATIONS | | |
| HDCP Specification | 1.4 | |
| USB Hub Ports | Yes | |
| USB Specification | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps) | |
| Driver Required | No | |
| STANDARDS & COMPLIANCE | | |
| Certifications | Tested to CE, FCC, RoHS, REACH | |
| WARRANTY | | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| Product Warranty Period (Worldwide) | 3-year limited warranty |
|-------------------------------------|-------------------------|
|-------------------------------------|-------------------------|

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Interface Modules category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

8500-003 IFD8520 cPCI-3544 422CON ATX6022/14GP7 ATX6022/8 AX93221-24/48 FC6A-EXM2 OPT8AP-AE 96RMKVM-19V1C-A
60016-011 60016-014 60006-008 60011-075 HPCI-14S12U cBP-3208 cBP-3062A FAB205-6P5 ATX6022/6 60016-012 96RMKVM17V1C-A PCE-DP10-00A1E MOS-1120Y-0201E 96RMLCD-17V1-A 96RMKVM-17V8C-A 60004-005 60016-017 60006-009 60016-035
60016-034 60016-031 60016-030 60016-026 60016-024 60016-018 60016-007 60016-005 60007-002 60006-010 AXX10GBTWLHW3
382-BBEH 555-BDCL K6CMISZBI52 426451401-3 60011-093 MIC-3620/3-BE MPCIE-UART-KIT02-R20 RSM232 PCIE-1680-AE BBFOSTCDRI