

**TM3401MI**
**P-Channel Enhancement Mosfet**
**General Description**

- Low  $R_{DS(ON)}$
- RoHS and Halogen-Free Compliant




**Applications**

- Load switch
- PWM

**General Features**

$V_{DS} = -30V$   $I_D = -4.8A$   
 $R_{DS(ON)} = 38m\Omega$  (Typ.) @  $V_{GS}=10V$

100% UIS Tested  
100%  $R_g$  Tested



Marking: A19T OR 3401

**Absolute Maximum Ratings ( $T_c=25^\circ C$  unless otherwise noted)**

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	-30	V
$V_{GS}$	Gate-Source Voltage	$\pm 12$	V
$I_D @ T_A=25^\circ C$	Continuous Drain Current	-4.8	A
$I_D @ T_A=70^\circ C$	Continuous Drain Current	-4	A
$I_{DM}$	Pulsed Drain Current <sup>2</sup>	-20	A
$P_D @ T_A=25^\circ C$	Total Power Dissipation <sup>3</sup>	1.4	W
$P_D @ T_A=70^\circ C$	Total Power Dissipation <sup>3</sup>	0.9	W
$T_{STG}$	Storage Temperature Range	- 55 to 150	°C
$T_J$	Operating Junction Temperature Range	- 55 to 150	°C
$R_{eJA}$	Thermal Resistance Junction-Ambient <sup>1</sup>	125	°C/W
$R_{eJA}$	Thermal Resistance Junction-Ambient <sup>1</sup> ( $t \leq 10s$ )	85	°C/W

**TM3401MI**
**P-Channel Enhancement Mosfet**
**Electrical Characteristics ( $T_J=25^\circ C$ , unless otherwise noted)**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BVDSS	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=-250\mu A$	-30	-32	---	V
$\Delta BVDSS/\Delta T_J$	$BV_{DSS}$ Temperature Coefficient	Reference to $25^\circ C, I_D=-1mA$	---	-0.014	---	$V/^\circ C$
RDS(ON)	Static Drain-Source On-Resistance	$V_{GS}=-10V, I_D=-3A$	---	38	46	$m\Omega$
		$V_{GS}=-4.5V, I_D=-3A$	---	47	58	
		$V_{GS}=-2.5V, I_D=-2A$	---	75	85	
VGS(th)	Gate Threshold Voltage	$V_{GS}=V_{DS}, I_D=-250\mu A$	-0.5	-0.9	-1.1	V
$\Delta V_{GS(th)}$	$V_{GS(th)}$ Temperature Coefficient		---	2.6	---	$mV/^\circ C$
IDSS	Drain-Source Leakage Current	$V_{DS}=-24V, V_{GS}=0V, T_J=25^\circ C$	---	---	-1	$\mu A$
		$V_{DS}=-24V, V_{GS}=0V, T_J=55^\circ C$	---	---	-5	
IGSS	Gate-Source Leakage Current	$V_{GS}=\pm 12V, V_{DS}=0V$	---	---	$\pm 100$	nA
gfs	Forward Transconductance	$V_{DS}=-5V, I_D=-3A$	---	5.6	---	S
Qg	Total Gate Charge (-4.5V)	$V_{DS}=-15V, V_{GS}=-4.5V, I_D=-3A$	---	11.9	---	nC
Qgs	Gate-Source Charge		---	1.8	---	
Qgd	Gate-Drain Charge		---	3	---	
Td(on)	Turn-On Delay Time	$V_{DD}=-15V, V_{GS}=-4.5V, R_G=3.3\Omega, I_D=-3A$	---	6.6	---	ns
T <sub>r</sub>	Rise Time		---	27.8	---	
Td(off)	Turn-Off Delay Time		---	46.2	---	
T <sub>f</sub>	Fall Time		---	20.6	---	
Ciss	Input Capacitance	$V_{DS}=-15V, V_{GS}=0V, f=1MHz$	---	290	---	pF
Coss	Output Capacitance		---	73	---	
Crss	Reverse Transfer Capacitance		---	71	---	
IS	Continuous Source Current <sup>1,4</sup>	$V_G=V_D=0V$ , Force Current	---	---	-4.8	A
VSD	Diode Forward Voltage <sup>2</sup>	$V_{GS}=0V, I_S=-1A, T_J=25^\circ C$	---	---	-1.2	V

**Note :**

- 1.The data tested by surface mounted on a 1 inch 2 FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width  $\leq 300\mu s$  , duty cycle  $\leq 2\%$
- 3.The power dissipation is limited by  $150^\circ C$  junction temperature
- 4.The data is theoretically the same as  $I_D$  and  $I_{DM}$  , in real applications , should be limited by total power dissipation.

## TM3401MI

## P-Channel Enhancement Mosfet

### Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs. G-S Voltage




Fig.3 Forward Characteristics Of Reverse




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized  $V_{GS(th)}$  vs.  $T_J$






Fig.6 Normalized  $R_{DS(on)}$  vs.  $T_J$

## TM3401MI


## P-Channel Enhancement Mosfet




**Fig.7 Capacitance**




**Fig.8 Safe Operating Area**



**Fig.9 Normalized Maximum Transient Thermal Impedance**




**Fig.10 Switching Time Waveform**



**Fig.11 Gate Charge Waveform**

## Package Mechanical Data:SOT-23-3L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E1	1.500	1.700	0.059	0.067
E	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for MOSFET category:*

*Click to view products by Tritech-MOS manufacturer:*

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [BUK455-60A/B](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#) [IPS70R2K0CEAKMA1](#) [SQD23N06-31L-GE3](#)  
[TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [DMN1053UCP4-7](#) [SQJ469EP-T1-GE3](#) [NTE2384](#) [DMC2700UDMQ-7](#)  
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)  
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [DMN2990UFB-7B](#)  
[IPB80P04P405ATMA2](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [MCQ7328-TP](#) [NTMC083NP10M5L](#) [BXP7N65D](#) [BXP4N65F](#) [AOL1454G](#)  
[WMJ80N60C4](#) [BXP2N20L](#) [BXP2N65D](#) [BXT1150N10J](#) [BXT1700P06M](#) [TSM60NB380CP ROG](#) [RQ7L055BGTCR](#) [DMNH15H110SK3-13](#)  
[SLF10N65ABV2](#) [BSO203SP](#) [BSO211P](#) [IPA60R230P6](#)