

49 Series Electromechanical Totalizer



Economically priced 4 and 6 figure push-button reset, electromechanical counter designed for use where limited space is a factor and when reliability is critical. Rugged operating mechanisms require no lubrication or maintenance. Compact size and minimum space requirements make the Model 49 ideally suited for use in control panels, business machines, and test equipment.

Key Features

- Compact
- No maintenance
- Quick reset

- Options include:
 - Voltages
 - 4 or 6 figure

Applications

- Test Equipment
- Control Panels
- Business Machines
- Medical devices






Specifications


| Figures: | 4 or 6 figures, white on black, 0.16" [4mm] high | |
|-----------------|--|--|
| Reset: | Push-button | |
| Speed: | 600 counts/minute (min. 50ms - on, 50ms - off) | |
| Voltages: | 115VAC, 24VDC (+10% to - 15%) | |
| Power: | AC: 115VAC ~ 3 watts, DC: 24VDC ~ 2 watts | |
| Mounting: | Panel, base, or bail | |
| Termination: | (2) #22 AWG 105°C wire leads, 10'' [254mm] long | |
| Operating Life: | Beyond 100 million counts | |
| Temp. Range: | -15°F to +140°F [-26°C to +60°C] | |
| Approvals: | UL Recognized, CE Compliant, ROHS | |
| Weight : | 4 oz. [113g] (4 fig.), 5 oz. [142g] (6 fig.) | |


Dimensions




Panel cutout: 1.46" x 1.01" [37.1 x 25.7mm] Mounting holes: For #4 flat head screw

Panel Mount - 6 Figure






Bail Mount - 4 Figure




Panel cutout: 1.46" x 1.01" [37.1 x 25.7mm]

Bail Mount - 6 Figure




Panel cutout: 2.00" x 1.01" [50.8 x 25.7mm]

Base Mount - 4 Figure



Mounting holes: 0.12" x 0.20" [3.1 x 5.1mm] slots

Base Mount - 6 Figure



Mounting holes: 0.12" x 0.20" [3.1 x 5.1mm] slots

Part Numbers

| B2-4904 | 115VAC, 4 figure, bail mount | B8-4906 | 24VDC, 6 figure, bail mount |
|--------------------|--|-----------|---|
| B8-4904 | 24VDC, 4 figure, bail mount | D2-4906 | 115VAC, 6 figure, base mount |
| D2-4904* | 115VAC, 4 figure, base mount | P2-4906* | 115VAC, 6 figure, panel mount |
| P2-4904* | 115VAC, 4 figure, panel mount | P8-4906* | 24VDC, 6 figure, panel mount |
| P8-4904* | 24VDC, 4 figure, panel mount | P9-4906 | 12VDC, 6 figure, panel mount |
| P9-4904 B2-4906 | 12VDC, 4 figure, panel mount 115VAC, 6 figure, bail mount | P9-4906NR | 24VDC, 6 figure, panel mount, non reset |



Trumeter (The Americas) 6601 Lyons Rd, Suite H-7 Coconut Creek, Florida FL 33073, USA Tel: +1 954 725 6699 Email: sales.usa@trumeter.com

Trumeter (Europe) Pilot Mill

Alfred Street Bury, BL9 9EF Tel: +44 161 674 0960 Email: sales.uk@trumeter.com

Innovative Design Technologies Sdn. Bhd Lot 5881, Lorong Iks Bukit Minyak 1 Taman Perindustrian Iks, 14000 Bukit Tengah Penang, Malaysia Web: www.idtworld.com Tel: + 604 5015700 Email: sales.my@idtworld.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Counters & Tachometers category:

Click to view products by Trumeter manufacturer:

Other Similar products are found below :

LC2H-FE-2K-N SM155115300 LC24-F-N 81333-26 H7ER-NV1-H P8-4906 GPMZC-SET SM1557242K SM155724300 26546848 P2-4904 1-4615 1-4635 1.230.301.038 6.924.0101.3A0 P8-4904 SLC-30 R48 7000 7000AS 7922 8980-1 H127.010A01H H7CX-AUD1-N H7CX-AW-N 3.550.401.075 3.550.401.351 LC2H-C-2K-N LC2H-C-30-N LC4H-R4-AC240VS LC4H-R6-AC240V 1.150.510.012.550 1.150.510.013.550 1.150.510.054.550 1.150.510.056.550 6.520.012.300 6.560.010.300 SLE-73-1400-1-4-01 SLIK-94-1521-1-3-001 SLN-94-1421-1-3 6.924.0103.300 SPI-73-1411-1-3-011 SPI-73-1411-1-4-011 CT6S-1P4 Y-50 LC4H-R4-AC24V LC4H-R4-DC24V CT6S-2P4 LC2H-FE-FV-30 H127.010A01G H5KLR-11 12-48V AC/DC