

Hi-Reliability Optically Coupled Isolator

3C91C, 3C92C (TX), 3N243, 3N244, 3N245 (TX), 3N262



Features:

- TO-72 hermetically sealed package
- 1 kVDC electrical isolation
- High current transfer ratio
- TX devices processed to MIL-PRF-19500

Description:

Each device is a high reliability optically coupled isolator that consists of an infrared emitting diode and a NPN silicon phototransistor which are mounted in a hermetically sealed TO-72 package. The **3C91C** and **3C92C** have a 935 nm wavelength, whereas the **3N243**, **3N244**, **3N245** and **3N262** have an 880 nm wavelength. All devices have 0.50" (12.70 mm) leads. Electrical characteristics vary.

TX devices are processed to OPTEK's military screening program patterned after MIL-PRF-19500.


Please refer to Application Bulletins 208 and 210 for additional design information and reliability (degradation) data.

Contact your local representative or OPTEK for more information.


Applications:

- High-voltage isolation between input and output
- Electrical isolation in dirty environments
- Industrial equipment
- Medical equipment
- Office equipment

| Part Number | LED Peak Wavelength | Sensor | Isolation Voltage (,000) | CTR Min / Max | I _F (mA) Typ / Max | V _{CE} (V) Typ / Max | Lead Length |
|-------------|---------------------|------------|--------------------------|---------------|-------------------------------|-------------------------------|-------------|
| 3C91C | 935 nm | Transistor | 1 | 0.3 / 2.0 | 10 / 50 | 10 / 50 | 0.50" |
| 3C92C (TX) | | | | 0.15 / NA | 3 / 40 | 10 / 30 | |
| 3N243 | 0.3 / NA | | | | | | |
| 3N244 | 0.6 / NA | | | | | | |
| 3N245 (TX) | 1.0 / 5.0 | | | 1 / 40 | 5 / 30 | | |
| 3N262 | 880 nm | | | | | | |



Phototransistor Collector is connected to the Header-Base-Case for ALL versions



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Hi-Reliability Optically Coupled Isolator

3C91C, 3C92C (TX), 3N243, 3N244, 3N245 (TX), 3N262



Electrical Specifications

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| | |
|---|---------------------------|
| Operating Temperature Range | -55° C to +125° C |
| Storage Temperature Range | -65° C to +150° C |
| Input to Output Isolation Voltage | $\pm 1\text{ kVDC}^{(1)}$ |
| Lead Soldering Temperature [1/16 inch (1.6 mm) from case for 5 seconds with soldering iron] | 260° C ⁽²⁾ |

Input Diode


| | |
|--------------------|----------------------|
| Forward DC Current | 40 mA |
| Reverse Voltage | 2.0 V |
| Power Dissipation | 60 mW ⁽³⁾ |

Output Phototransistor

| | |
|------------------------------|-----------------------|
| Continuous Collector Current | 30 mA |
| Collector-Emitter Voltage | 30 V |
| Emitter-Collector Voltage | 5.0 V |
| Power Dissipation | 200 mW ⁽⁴⁾ |

Notes:

1. Measured with input leads shorted together and output leads shorted together.
2. RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering.
3. Derate linearly 2.0 mW/° C above 25° C.
4. Derate linearly 0.60 mW/° C above 65° C.



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Hi-Reliability Optically Coupled Isolator

3C91C, 3C92C (TX), 3N243, 3N244, 3N245 (TX), 3N262



Electrical Specifications

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|--------------------|--|--------------------------|-----|-----|---------------|--|
| Input Diode | | | | | | |
| V_F | Forward Voltage 3C91C, 3C92C (TX) | - | - | 1.2 | V | $I_F = 2\text{ mA}$ |
| | 3C91C, 3C92C (TX) | - | - | 1.5 | | $I_F = 50\text{ mA}$ |
| | 3N243, 3N244, 3N245 (TX) | 0.8 | - | 1.3 | | $I_F = 10\text{ mA}$ |
| | 3N243, 3N244, 3N245 (TX) | 1.0 | - | 1.5 | | $I_F = 10\text{ mA}, T_A = -55^\circ\text{C}$ |
| | 3N243, 3N244, 3N245 (TX) | 0.7 | - | 1.2 | | $I_F = 10\text{ mA}, T_A = -100^\circ\text{C}$ |
| | 3N262 | 0.8 | - | 1.5 | | $I_F = 10\text{ mA}$ |
| V_R | Reverse Voltage 3C91C, 3C92C (TX) | 7 | - | - | V | $I_R = 0.1\text{ mA}$ |
| | Reverse Current 3C91C, 3C92C (TX) | - | - | 1 | μA | $V_R = 3.0\text{ V}$ |
| | | 3N243, 3N244, 3N245 (TX) | - | - | | 100 |
| 3N262 | | - | - | 100 | | $V_R = 2.0\text{ V}$ |
| C_{IN} | Diode Capacitance 3C91C, 3C92C (TX) | - | 25 | - | pF | $V = 0, f = 1\text{ MHz}$ |

Output Phototransistor

| | | | | | | |
|---------------|--|----|---|-----|---------------|---|
| $V_{(BR)CEO}$ | Collector-Emitter Breakdown Voltage 3C91C, 3C92C (TX) | 50 | - | - | V | $I_C = 10.0\text{ mA}$ |
| | 3N243, 3N244, 3N245 (TX) | 30 | - | - | | $I_C = 1.0\text{ mA}$ |
| | 3N262 | 40 | - | - | | $I_C = 1.0\text{ mA}$ |
| $V_{(BR)ECO}$ | Emitter-Collector Breakdown Voltage 3C91C, 3C92C (TX) | 7 | - | - | V | $I_C = 10\text{ }\mu\text{A}$ |
| | 3N243, 3N244, 3N245 (TX) | 5 | - | - | | $I_E = 100\text{ }\mu\text{A}$ |
| | 3N262 | 7 | - | - | | $I_E = 100\text{ }\mu\text{A}$ |
| I_{CEO} | Collector Dark Current 3C91C, 3C92C (TX) | - | - | 10 | nA | $V_{CE} = 5\text{ V}$ |
| | 3C91C, 3C92C (TX) | - | - | 50 | nA | $V_{CE} = 50\text{ V}$ |
| | 3N243, 3N244, 3N245 (TX) | - | - | 100 | nA | $V_{CE} = 10.0\text{ V}$ |
| | 3N243, 3N244, 3N245 (TX) | - | - | 100 | μA | $V_{CE} = 10.0\text{ V}, T_A = 100^\circ\text{C}$ |
| | 3N262 | - | - | 100 | μA | $V_{CE} = 10.0\text{ V}$ |
| | 3N262 | - | - | 100 | μA | $V_{CE} = 10.0\text{ V}, T_A = 100^\circ\text{C}$ |

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTeK Technology
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Hi-Reliability Optically Coupled Isolator

3C91C, 3C92C (TX), 3N243, 3N244, 3N245 (TX), 3N262



Electrical Specifications

Electrical Characteristics (T_A = 25° C unless otherwise noted)

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|----------------------|--------------------------------------|-----|-----|-----|--|--|
| Coupled | | | | | | |
| I _{C(ON)} | On-State Collector Current | | | | | |
| | 3C91C, 3C92C (TX) | 4.0 | - | - | | I _F = 10 mA , V _{CE} = 5 V |
| | 3C91C, 3C92C (TX) | 3.0 | - | 20 | | I _F = 10 mA , V _{CE} = 0.4 V |
| | 3N243 | 1.5 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V |
| | 3N243 | 0.3 | - | - | | I _F = 3 mA , V _{CE} = 10.0 V |
| | 3N243 | 0.5 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V, T _A = 55° C |
| | 3N243 | 0.5 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V, T _A = 100° C |
| | 3N244 | 3.0 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V |
| | 3N244 | 0.8 | - | - | | I _F = 3 mA , V _{CE} = 10.0 V |
| | 3N244 | 1.0 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V, T _A = 55° C |
| | 3N244 | 1.0 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V, T _A = 100° C |
| | 3N245 (TX) | 6.0 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V |
| | 3N245 (TX) | 1.5 | - | - | | I _F = 3 mA , V _{CE} = 10.0 V |
| | 3N245 (TX) | 1.5 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V, T _A = 55° C |
| | 3N245 (TX) | 1.5 | - | - | | I _F = 10 mA , V _{CE} = 10.0 V, T _A = 100° |
| 3N262 | 1.0 | - | 5 | | I _F = 1 mA , V _{CE} = 5.0 V | |
| 3N262 | 1.4 | - | - | | I _F = 2.0 mA , V _{CE} = 5.0 V, T _A = 55° C | |
| 3N262 | 1.0 | - | - | | I _F = 2.0 mA , V _{CE} = 5.0 V, T _A = 100° C | |
| V _{CE(SAT)} | Collector-Emitter Saturation Voltage | | | | | |
| | 3C91C, 3C92C (TX) | - | - | 0.4 | | I _F = 50 mA , I _C = 10 mA |
| | 3N243, 3N244, 3N245 (TX) | - | - | 0.3 | | I _F = 20 mA , I _C = 1.50 mA |
| | 3N243, 3N244, 3N245 (TX) | - | - | 0.3 | | I _F = 20 mA , I _C = 3.0 mA |
| | 3N243, 3N244, 3N245 (TX) | - | - | 0.3 | | I _F = 20 mA , I _C = 6.0 mA |
| | 3N262 | - | - | 0.3 | | I _F = 2.0 mA , I _C = 0.50 mA |
| | 3N262 | - | - | 0.3 | | I _F = 2.0 mA , I _C = 1.0 mA |
| 3N262 | - | - | 0.3 | | I _F = 2.0 mA , I _C = 2.0 mA | |
| t _{ON} | Turn-on Time 3C91C, 3C92C (TX) | - | - | 9 | μs | V _{CC} = 5 V, I _C = 2 mA, R _L = 100 Ω |
| t _{OFF} | Turn-off Time 3C91C, 3C92C (TX) | - | - | 6 | μs | V _{CC} = 5 V, I _C = 2 mA, R _L = 100 Ω |

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Hi-Reliability Optically Coupled Isolator

3C91C, 3C92C (TX), 3N243, 3N244, 3N245 (TX), 3N262





Electrical Specifications

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|----------------|---|--------|-----|-----|---------------|---|
| Coupled | | | | | | |
| C_{IO} | Input-to-Output Capacitance 3C91C, 3C92C (TX) 3N243, 3N244, 3N245 (TX) 3N262 | - | 2 | 2.5 | pF | $f = 1\text{ MHz}$ $V_{IO} = 0\text{ V}, f = 1.00\text{ MHz}^{(1)}$ $V_{IO} = 0\text{ V}, f = 1.00\text{ MHz}^{(1)}$ |
| I_{IO} | Leakage Input -to-Output 3N243, 3N244, 3N245 (TX) 3N262 | - | - | 100 | nA | $V_{IO} = \pm 1.00\text{ kVDC}^{(1)}$ $V_{IO} = \pm 1.00\text{ kVDC}^{(1)}$ |
| R_{IO} | Isolation Resistance 3C91C, 3C92C (TX) | 10^9 | - | - | Ω | $V_{IO} = +1\text{ kV}$ |
| t_r | Output Rise Time 3N243, 3N244, 3N245 (TX) 3N262 | - | - | 10 | μs | $V_{CC} = 10.0\text{ V}, I_F = 10.0\text{ mA}, R_L = 100\ \Omega^{(2)}$ $V_{CC} = 10.0\text{ V}, I_F = 5.0\text{ mA}, R_L = 100\ \Omega^{(2)}$ |
| t_f | Output Fall Time 3N243, 3N244, 3N245 (TX) 3N262 | - | - | 10 | μs | $V_{CC} = 10.0\text{ V}, I_F = 10.0\text{ mA}, R_L = 100\ \Omega^{(2)}$ $V_{CC} = 10.0\text{ V}, I_F = 5.0\text{ mA}, R_L = 100\ \Omega^{(2)}$ |

Notes:

- Measured with input leads shorted together and output leads shorted together.
- The input waveform is supplied by a generator with the following characteristics: $Z_{OUT} = 50\ \Omega$, $t_r \leq 15\text{ ns}$, duty cycle $\sim 1\%$, pulse width $\sim 100\text{ ms}$.



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTeK Technology
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Transistor Output Optocouplers](#) category:

Click to view products by [TT Electronics](#) manufacturer:

Other Similar products are found below :

[LTV-814S-TA](#) [LTV-824HS](#) [66095-001](#) [6N136-X017T](#) [MCT6-X007](#) [MOC8101-X017T](#) [PS2561A-1-W-A](#) [PS2561B-1-L-A](#) [PS2561L-1-V-A](#)
[MRF658](#) [IL755-1X007](#) [ILD2-X006](#) [ILD74-X001](#) [ILQ615-2X017](#) [ILQ615-3X016](#) [LDA102S](#) [LDA110S](#) [PS2561-1-V-W-A](#) [PS2561AL-1-V-](#)
[A](#) [PS2561L1-1-L-A](#) [PS2701A-1-F3-P-A](#) [PS2801-1-F3-P-A](#) [PS2911-1-L-AX](#) [CNY17-2X017](#) [CNY17-4X001](#) [CNY17-4X017](#) [CNY17F-](#)
[1X007](#) [CNY17F-2X017](#) [CNY17F-4X001](#) [CNY17G-1](#) [LTV-214](#) [LTV-702VB](#) [LTV-733S](#) [LTV-816S-TA](#) [LTV-825S](#) [TCET1113](#) [TCET2100](#)
[4N25-X007T](#) [IL215AT](#) [ILD615-1X007](#) [ILQ2-X007](#) [VOS615A-2T](#) [WPPC-A11066AA](#) [WPPC-A11066AD](#) [WPPC-A11084ASS](#) [WPPC-](#)
[A21068AA](#) [WPPC-D11066AA](#) [WPPC-D21068ED](#) [WPPC-D410616EA](#) [WPPC-D410616ED](#)