


## E-Beam Welded Shunt 8518

### EBW8518

- Electron-beam welded technology
- Low thermal EMF
- Low measurement inductance
- Robust copper terminals for busbar mounting
- AEC-Q200 qualified



All parts are Pb-free and comply with EU Directive 2011/65/EU amended by (EU) 2015/863 (RoHS3)

### Electrical Data

		EBW8518		
Power rating at 70°C	W	36		
Resistance range	$\mu\Omega$	50 to 250		
Resistance tolerance	%	50 $\mu\Omega$ : $\pm 3, \pm 5$	100 $\mu\Omega$ : $\pm 2, \pm 5$	>100 $\mu\Omega$ : $\pm 1, \pm 5$
TCR (resistive alloy)	ppm/°C	$\pm 10$		
TCR (measurement)	ppm/°C	50 $\mu\Omega$ : $\pm 150$	>50 $\mu\Omega$ : $\pm 100$	
Standard values	$\mu\Omega$	50, 100, 125, 200, 250		
Thermal EMF	$\mu V/^\circ C$	<1		
Inductance (measurement)	nH	<5		
Ambient temperature range	°C	-65 to +170		

### Physical Data Dimensions in mm and weight in g

Resistance Value ( $\mu\Omega$ )	A nom.	B $\pm 0.2$	C $\pm 0.2$	Wt nom.
50	4.6	7.7	2.2	40.2
100	9.1	12.2	2.2	39.5
125	10.5	13.5	2.0	39.0
200	16.5	19.7	2.0	38.0
250	21.0	24.2	2.0	37.2

### Construction

A manganese alloy resistance element is e-beam welded between two copper terminations.

### Marking

The components are unmarked.

### Plating

The component can be supplied with or without Sn plating.


### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

## Performance Data

Test	Method	±ΔR% max.
Load Life	1000 hours, cyclic load at Pr	1.0
Short Term Overload	5 seconds, 5 x Pr	1.0
High Temperature Exposure	1000 hours, +170°C	1.0
Temperature Cycle	1000 cycles, -55 to +150°C, 30 minute dwell	0.5
Low Temperature Storage	24 hours, -65°C	0.5
Biased Humidity	1000 hours, +85°C, 85%RH, 10% of Pr	0.5
Moisture Resistance	MIL-STD-202 Method 106, no load	0.5
Vibration	MIL-STD-202 Method 204, 5g for 20 mins, 12 cycles, 10-2000Hz	0.2
Mechanical Shock	MIL-STD-202 Method 213, 100g for 6ms, half sine	0.2
Resistance to Solder Heat	MIL-STD-202 Method 210, solder dip 260°C for 10s	0.5
Solderability	J-STD-002	95% coverage

## Thermal Performance



## Voltage Sense Terminal Style

The following voltage sense terminal styles are examples of custom options which can be made available on request.

Voltage Sense Terminal Option	Style	Figure	Availability
No sense terminals	NT		Standard
Through hole Ø3.2mm	T2	1	Custom
Tapped hole M3 x 0.6	M3	2	
Tapped hole M4 x 0.7	M4		
“With dimple” location points	WD	3	
Dowel fit pins	DF	4	
Pressed pins	PP	5	
Stress-relief pins	SP	6	

### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Performance Data

Figure 1 – Through Hole (T2 Style)




Figure 2 – Tapped Hole (M3 & M4 Style)




Figure 3 – With Dimple (WD Style)




Figure 4 – Dowel Fit Pin (DF Style)





Figure 5 – Pressed Pin (PP Style)



PP Style Pin Detail






Figure 6 – Stress-relief Pin (SP Style)



SP Style Pin Detail



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

E-Beam Welded Shunt 8518

EBW8518

## Packaging

Standard EBW8518 shunts are supplied bulk packed in vacuum sealed plastic bags of 100 pieces. Custom voltage sense terminal styles may be tray packed.

### Recommended Storage Conditions (packed):

Temperature 25°C to 35°C, humidity 30 to 80% RH.

## Ordering Procedure

**Example: EBW8518PNT-L050JB** (50 micro-ohms ±5%, plated, no sense terminals, bulk packed, Pb-free)

E	B	W	8	5	1	8	P	N	T	-	L	0	5	0	J	B
1		2			3	4	5				6	7				

1 Type	2 Size	3 Finish	4 Sense Style	5 Value	6 Tolerance		7 Packaging
EBW	8518	P = Sn Plated	NT = No terminals	L050 = 50μΩ	F = ±1%	(>100μΩ only)	B = Bulk
		U = Un-plated	Request availability of custom styles	L100 = 100μΩ	G = ±2%	(100μΩ only)	
		L125 = 125μΩ		H = ±3%	(50μΩ only)		
		L200 = 200μΩ		J = ±5%	All values		
			L250 = 250μΩ				

### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* [Planar Resistors - Chassis Mount](#) *category:*

*Click to view products by* [TT Electronics](#) *manufacturer:*

Other Similar products are found below :

[20-100RP](#) [BAB326622R0KE](#) [BDS2A10033RK](#) [TAP800K68RE](#) [BB326610R0KE](#) [TL88J136C](#) [TL122KU221RE](#) [TGHDV100RJE](#)  
[TL71F9K40C](#) [FPA100 47K J](#) [RCEC750HV6802JB](#) [TAP650J4R7E](#) [TGHHV100RJE](#) [TGHHV33R0JE](#) [TGHHV500RJE](#) [TGHHV5K00JE](#)  
[TGHHV5R00JE](#) [TGHHV680RJE](#) [TGHLV100RJE](#) [TGHLV150RJE](#) [TGHLV1K00JE](#) [TGHLV1R00JE](#) [TGHLV500RJE](#) [TGHLV5K00JE](#)  
[TGHLVR100JE](#) [HTS-14-12-40-3/4.8](#) [HTS-14-24-40-3/4.8](#) [HTS-15-230-100-1](#) [HTS-15-230-100-3/4.8](#) [HTS-15-230-100-3/6.3](#) [HTS-15-230-150-3/6.3](#) [FPA100 100R J](#) [FPA100 1K5 J](#) [FPA100 3R3 J](#) [FPA100 4R7 J](#) [LPS0600HR400KB](#) [LPS0800L1001KB](#) [GBR-605-230-20-1](#) [GBR-605-230-60-2](#) [GBR-612-12-40-1](#) [GBR-612-24-40-1](#) [GBR-618-24-10-2](#) [GBR-618-24-5-2](#) [GBR-618-3-5-2](#) [GBR-618-9-5-2](#) [GBR-619-230-60-2](#)  
[FPA100-1RJ](#) [FPA100 470R J](#) [HTS-14-230-100-3/4.8](#) [RCEC400GS2702KB](#)