



Pin 1 –  $V_{IN}$   
 Pin 2 –  $V_{OUT}$   
 Case – Ground

**H Package – TO-39**



Pin 1 –  $V_{IN}$   
 Pin 2 – Ground  
 Pin 3 –  $V_{OUT}$

**SMD 1  
 CERAMIC SURFACE MOUNT**



**8 Pin J Package**

**Order Information**

Part Number	H-Pack (TO-39)	J-Pack CERDIP	SG-Pack SMD	Temp. Range
IP78MxxAzz	✓	✓	✓	-55 to +150°C
IP78Mxxzz	✓	✓	✓	"
IP140MAzz-xx	✓		✓	"
IP140Mzz-xx	✓		✓	"

**Note:**

xx = Voltage Code (05, 12, 15)  
 zz = Package Code (H, J, SG)  
 eg. IP78M05J IP140MAH-12

**0.5 AMP  
 POSITIVE  
 VOLTAGE REGULATOR**

**FEATURES**

- **OUTPUT CURRENT UP TO 0.5A**
- **OUTPUT VOLTAGES OF 5, 12, 15V**
- **0.01% / V LINE REGULATION**
- **0.3% / A LOAD REGULATION**
- **THERMAL OVERLOAD PROTECTION**
- **SHORT CIRCUIT PROTECTION**
- **OUTPUT TRANSISTOR SOA PROTECTION**
- **1% VOLTAGE TOLERANCE (-A VERSIONS)**

**DESCRIPTION**

The IP140MA and IP78M00A series of voltage regulators are fixed output regulators intended for local, on-card voltage regulation. These devices are available in 5, 12, and 15 volt options and are capable of delivering in excess of 500mA over temperature.

The A-suffix devices are fully specified at 0.5A, provide 0.01% / V line regulation, 0.3% / A load regulation, and ±1% output voltage tolerance at room temperature. Protection features include safe operating area, current limiting and thermal shutdown.

**ABSOLUTE MAXIMUM RATINGS** ( $T_C = 25^\circ\text{C}$  unless otherwise stated)

$V_I$	DC Input Voltage (for $V_O = 5, 12, 15\text{V}$ )	35V
$P_D$	Power Dissipation	Internally limited <sup>1</sup>
$R_{\theta JC}$	Thermal Resistance Junction to Case – H Package	20°C / W
$R_{\theta JC}$	Thermal Resistance Junction to Case – SG Package	TBA °C / W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient – J Package	119°C / W
$T_J$	Operating Junction Temperature Range	-55 to 150°C
$T_{stg}$	Storage Temperature	-65 to 150°C

Note 1. Although power dissipation is internally limited, these specifications are applicable for maximum power dissipation  $P_{MAX}$  of 2W for the H-Package, 1.05W for the J-Package and 15W for the SG-Package.

## ELECTRICAL CHARACTERISTICS

Parameter	Test Conditions	IP78M05A IP140MA-05			IP78M05 IP140M-05			Units	
		Min.	Typ.	Max.	Min.	Typ.	Max.		
$V_O$ Output Voltage	$I_O = 100\text{mA}$ $V_{IN} = 10\text{V}$	4.95	5	5.05	4.8	5	5.2	V	
	$I_O = 5\text{mA to } 350\text{mA}$ $P_D \leq P_{MAX}$ $V_{IN} = 7.5\text{V to } 20\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	4.85			5.15				4.75
$\Delta V_O$ Line Regulation	$I_O = 200\text{mA}$	$V_{IN} = 7\text{V to } 25\text{V}$	3		10		50		mV
		$V_{IN} = 8\text{V to } 25\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	3		10		25		
	$I_O = 500\text{mA}$ $V_{IN} = 8\text{V to } 12\text{V}$	3		10		50			
$\Delta V_O$ Load Regulation	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = 10\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	5		50		50		mV	
$I_Q$ Quiescent Current	$V_{IN} = 10\text{V}$ $I_O = 350\text{mA}$ $T_J = -55\text{ to } 150^\circ\text{C}$	4		6		4		6	mA
$\Delta I_Q$ Quiescent Current Change	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = 10\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	0.1		0.5		0.5		mA	
	$I_O = 200\text{mA}$ $V_{IN} = 8\text{V to } 25\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	0.2		0.8		0.8			
$V_N$ Output Noise Voltage	$f = 10\text{Hz to } 100\text{kHz}$	40		200		40		200	$\mu\text{V}$
$\frac{\Delta V_{IN}}{\Delta V_O}$ Ripple Rejection	$f = 120\text{Hz}$ $V_{IN} = 8\text{V to } 18\text{V}$	$I_O = 300\text{mA}$	65		80		62		dB
		$I_O = 100\text{mA}$ $T_J = -55\text{ to } 150^\circ\text{C}$	65		80		62		
Dropout Voltage	$I_O = 350\text{mA}$	2		2.5		2.5		V	
$I_{SC}$ Short Circuit Current	$V_{IN} = 35\text{V}$	300		600		300		600	mA
$I_{pk}$ Peak Output Current	$V_{IN} = 10\text{V}$	0.7	1.0	1.4	0.7	1.0	1.6	A	
Average Temperature Coefficient of $V_O$	$I_O = 5\text{mA}$	0.5		2.0		0.5		$\text{mV}/^\circ\text{C}$	

1) All characteristics are measured with a capacitor across the input of  $0.22\mu\text{F}$  and a capacitor across the output of  $0.1\mu\text{F}$ .  
 All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.

2) Test Conditions unless otherwise stated:  $T_J = 25^\circ\text{C}$   
 $P_{MAX} = 2\text{W}$  for H Package (TO-39)  
 $P_{MAX} = 1.05\text{W}$  for J Package (CERDIP)  
 $P_{MAX} = 15\text{W}$  for SG Package (SMD1)

## ELECTRICAL CHARACTERISTICS

Parameter	Test Conditions	IP78M12A IP140MA-12			IP78M12 IP140M-12			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
$V_O$ Output Voltage	$I_O = 100\text{mA}$ $V_{IN} = 19\text{V}$	11.88	12	12.12	11.50	12	12.50	V
	$I_O = 5\text{mA to } 350\text{mA}$ $P_D \leq P_{MAX}$ $V_{IN} = 14.8\text{V to } 27\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$	11.64		12.36	11.40		12.60	
$\Delta V_O$ Line Regulation	$I_O = 200\text{mA}$ $V_{IN} = 14.5\text{V to } 30\text{V}$		4	18			60	mV
		$V_{IN} = 16\text{V to } 30\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		4	18		30	
	$I_O = 500\text{mA}$ $V_{IN} = 16\text{V to } 22\text{V}$		4	18			120	
$\Delta V_O$ Load Regulation	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = 19\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		10	60			120	mV
$I_Q$ Quiescent Current	$V_{IN} = 19\text{V}$ $I_O = 350\text{mA}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		4	6		4	6	mA
$\Delta I_Q$ Quiescent Current Change	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = 19\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		0.1	0.5			0.5	mA
	$I_O = 200\text{mA}$ $V_{IN} = 14.8\text{V to } 30\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		0.2	0.8			0.8	
$V_N$ Output Noise Voltage	$f = 10\text{Hz to } 100\text{kHz}$		75	480		75	480	$\mu\text{V}$
$\frac{\Delta V_{IN}}{\Delta V_O}$ Ripple Rejection	$f = 120\text{Hz}$ $V_{IN} = 15\text{V to } 25\text{V}$	$I_O = 300\text{mA}$	58	72		55		dB
		$I_O = 100\text{mA}$ $T_J = -55 \text{ to } 150^\circ\text{C}$	58	72		55		
Dropout Voltage	$I_O = 350\text{mA}$		2	2.5			2.5	V
$I_{SC}$ Short Circuit Current	$V_{IN} = 35\text{V}$		300	600		300	600	mA
$I_{pk}$ Peak Output Current	$V_{IN} = 19\text{V}$	0.7	1.0	1.4	0.7	1.0	1.6	A
Average Temperature Coefficient of $V_O$	$I_O = 5\text{mA}$		1.2	4.8		1.2		$\text{mV}/^\circ\text{C}$

1) All characteristics are measured with a capacitor across the input of  $0.22\mu\text{F}$  and a capacitor across the output of  $0.1\mu\text{F}$ .  
 All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.

2) Test Conditions unless otherwise stated:  $T_J = 25^\circ\text{C}$   
 $P_{MAX} = 2\text{W}$  for H Package (TO-39)  
 $P_{MAX} = 1.05\text{W}$  for J Package (CERDIP)  
 $P_{MAX} = 15\text{W}$  for SG Package (SMD1)

## ELECTRICAL CHARACTERISTICS

Parameter	Test Conditions	IP78M15A IP140MA-15			IP78M15 IP140M-15			Units	
		Min.	Typ.	Max.	Min.	Typ.	Max.		
$V_O$ Output Voltage	$I_O = 100\text{mA}$ $V_{IN} = 23\text{V}$	14.85	15	15.15	14.40	15	15.60	V	
	$I_O = 5\text{mA to } 350\text{mA}$ $P_D \leq P_{MAX}$ $V_{IN} = 18\text{V to } 30\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	14.55			15.45				14.25
$\Delta V_O$ Line Regulation	$I_O = 200\text{mA}$ $V_{IN} = 17.5\text{V to } 30\text{V}$ $V_{IN} = 20\text{V to } 30\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	4			22			60	mV
		4			22			30	
	$I_O = 500\text{mA}$ $V_{IN} = 20\text{V to } 26\text{V}$	4			22			150	
$\Delta V_O$ Load Regulation	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = 23\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	12		75		150		mV	
$I_Q$ Quiescent Current	$V_{IN} = 23\text{V}$ $I_O = 350\text{mA}$ $T_J = -55\text{ to } 150^\circ\text{C}$	4		6		4		6	mA
$\Delta I_Q$ Quiescent Current Change	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = 23\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	0.1		0.5		0.5		mA	
	$I_O = 200\text{mA}$ $V_{IN} = 18\text{V to } 30\text{V}$ $T_J = -55\text{ to } 150^\circ\text{C}$	0.2		0.8		0.8			
$V_N$ Output Noise Voltage	$f = 10\text{Hz to } 100\text{kHz}$	90		600		90		600	$\mu\text{V}$
$\frac{\Delta V_{IN}}{\Delta V_O}$ Ripple Rejection	$f = 120\text{Hz}$ $V_{IN} = 18.5\text{V to } 28.5\text{V}$	$I_O = 300\text{mA}$	57	70	54			dB	
		$I_O = 100\text{mA}$ $T_J = -55\text{ to } 150^\circ\text{C}$	57	70	54				
Dropout Voltage	$I_O = 350\text{mA}$	2		2.5		2.5		V	
$I_{SC}$ Short Circuit Current	$V_{IN} = 35\text{V}$	300		600		300		600	mA
$I_{pk}$ Peak Output Current	$V_{IN} = 23\text{V}$	0.7	1.0	1.4	0.7	1.0	1.6	A	
Average Temperature Coefficient of $V_O$	$I_O = 5\text{mA}$	1.5		6.0		1.5		$\text{mV}/^\circ\text{C}$	

1) All characteristics are measured with a capacitor across the input of  $0.22\mu\text{F}$  and a capacitor across the output of  $0.1\mu\text{F}$ .

All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.

2) Test Conditions unless otherwise stated:  $T_J = 25^\circ\text{C}$

$P_{MAX} = 2\text{W}$  for H Package (TO-39)

$P_{MAX} = 1.05\text{W}$  for J Package (CERDIP)

$P_{MAX} = 15\text{W}$  for SG Package (SMD1)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LDO Voltage Regulators](#) category:*

*Click to view products by [TT Electronics](#) manufacturer:*

Other Similar products are found below :

[M38D29FFHP#U1](#) [702103A](#) [717726C](#) [742457H](#) [MP20051DN-LF-Z](#) [R5F111PGGFB#30](#) [AP7363-SP-13](#) [NCP103AMX285TCG](#)  
[NCV8664CST33T3G](#) [NCV8752AMX28TCG](#) [L9454](#) [AP7362-HA-7](#) [LX13043CLD](#) [TCR3DF185,LM\(CT](#) [TCR3DF24,LM\(CT](#)  
[TCR3DF285,LM\(CT](#) [TCR3DF31,LM\(CT](#) [TCR3DF45,LM\(CT](#) [TLF4949EJ](#) [L9708](#) [L970813TR](#) [030014BB](#) [059985X](#) [EAN61387601](#)  
[EAN61573601](#) [NCP121AMX173TCG](#) [NCP4687DH15T1G](#) [NCV8703MX30TCG](#) [701326R](#) [702087BB](#) [755078E](#) [TCR2EN28,LF\(S](#)  
[LM1117DT-1.8/NO](#) [LT1086CM#TRPBF](#) [AZ1085S2-1.5TRE1](#) [TLE4279GXUMA2](#) [MAX15101EWL+T](#) [NCV8170AXV250T2G](#)  
[SCD337BTG](#) [TCR3DF27,LM\(CT](#) [TCR3DF19,LM\(CT](#) [TCR3DF125,LM\(CT](#) [TCR2EN18,LF\(S](#) [MAX15103EWL+T](#) [TS2937CZ-5.0 C0](#)  
[MAX8878EUK30-T](#) [MAX663CPA](#) [NCV4269CPD50R2G](#) [NCV8716MT30TBG](#) [AZ1117IH-1.2TRG1](#)