RF Transformer

0.08 to 200 MHz

T1-1T-KK81+ T1-1T-KK81



CASE STYLE: KK81 PRICE: \$4.45 ea. QTY (1-9)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Maximum Ratings

Operating Temperature	-20°C to 85°C		
Storage Temperature	-55°C to 100°C		
RF Power	0.25W		
DC Current	30mA		
Permanent damage may occur if any	of these limits are exceede		

Pin Connections

PRIMARY DOT	4
PRIMARY	6
SECONDARY DOT	3
SECONDARY	1
SECONDARY CT	2
NOT USED	5


Outline Drawing



Outline Dimensions (inch)

J	Н	G	F	Е	D	С	В	Α
.05	.05	.100	.020	.042	.010	.23	.27	.30
1.27	1.27	2.54	0.51	1.07	0.25	5.84	6.86	7.62
wt	S	R	Q	Р	N	M	L	K
grams	.100	.050	.125	.600	.575	.26	.036	.020
0.50	2.54	1.27	3.18	15.24	14.61	6.60	0.91	0.51

Config. A



Features

- wideband, 0.08 to 200 MHz
- excellent return loss
- also available with plug-in (X65)
- flat-pack (W38) leads

Applications

- VHF
- receivers/transmitters


Transformer Electrical Specifications


Ω RATIO	FREQUENCY (MHz)	INSERTION LOSS*		
		3 dB MHz	2 dB MHz	1 dB MHz
1	0.08-200	.08-200	0.15-150	0.2-80

^{*}Insertion Loss is referenced to mid-band loss, 0.3 dB tvp.

Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	INPUT R. LOSS (dB)	
0.05	2.78	1.64	
0.08	1.18	4.39	
0.20	0.52	9.45	
0.50	0.38	16.31	
1.00	0.36	19.67	
80.00	0.64	9.96	
99.33	0.76	8.80	
150.00	1.23	5.83	
192.51	1.60	4.60	
200.00	1.63	4.55	





- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

 C. The parts covered by this specification document are subject to Mini-Circuit satandard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Infrared Emitters - High Power category:

Click to view products by TT Electronics manufacturer:

Other Similar products are found below:

QED123UL TSHA6201 TSHA6202 SFH 4030 SFH 4060 SFH 4775S A01 SFH 4726AS SFH 4725AS VSMY2853SLX01

VSMY2853RGX01 VSMY2853GX01 VSMY2850GX01 IN-P281ASGHIR IN-P281ASGIR VSMY2890GX01 VSMY2890RGX01 SFH

4728AS A01 SST-10-IRD-B130H-S940 SST-10-IRD-B50H-S940 QEE123 TSHA6200 TSML1030 VTE1291W-2H LL-304IRC4B-2AD

LL-503HIRT2E-1CC LL-503IRC2E-2AC LL-503IRC2V-2AD LL-503IRT2E-2AC LL-503IRT2E-2AE LL-503SIRC2E-1BD LL-S170IRC
2A SFH 4259 OS5RKAZ5D1P OSB56LZE31D OSG58AZ5D1P OSI3CA5111A OSI3NAS1C1A OSI5LA56A1A OSI5XNE3E1E

OSIXCA5121A OSIXCAS1C1A OSM54LZ5D1P OSM5D3Z2C1P OSMR43Z2C1P OSO5PAZ161D OSOR7161D OSPW7161D

OSPW71B1P OSR5PAZE31D OSR9XAE3E1E