

Vertical Cavity Surface Emitting Laser in Lateral Package



OPV382

Features:

- 850 nm VCSEL technology
- High thermal stability
- Low drive current
- High output power
- Narrow beam angle



Description:




The OPV382 is a Vertical Cavity Surface Emitting Laser (VCSEL) packaged in a dome lens lateral package. VCSELs offer many advantages in sensing applications when compared to infrared LEDs. These devices require substantially lower drive currents to obtain the same amount of output power as LEDs. This feature allows VCSELs to be used in low power consumption applications such as battery operated equipment.

The dome lens packaging creates a narrow beam angle from the device. Long distance applications may benefit from this feature as secondary optics may be eliminated, reducing total system cost. The OPV382 is optically and spectrally compatible with Optek's standard detector products such as the OP500 series phototransistors, OP530 series photodarlingtons and the OP900 series photodiodes.

Applications:

- Non-contact position sensing
- Photoelectric sensors
- Optical encoders
- Light curtains

| OPV382 | |
|--------|------------|
| Pin | Connection |
| 1 | Cathode |
| 2 | Anode |



LEAD FREE



Additional laser safety information can be found on the Optek website. See application bulletin #221.

Classification is not marked on the device due to space limitations. See package outline for centerline of optical radiance. Operating devices beyond maximum rating may result in hazardous radiation exposure.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Optek Technology, Inc.
1645 Wallace Drive, Ste. 130, Carrollton, TX USA 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Vertical Cavity Surface Emitting Laser in Lateral Package



OPV382

Electrical Specifications

| Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted) | |
|--|-----------------------|
| Storage Temperature Range | -40° to +100° C |
| Operating Temperature Range | 0° to +85° C |
| Lead Soldering Temperature [1/16 inch (1.6mm) from case for 5 sec with soldering iron] | 260° C ⁽¹⁾ |
| Maximum Forward Peak Current, Continuous | 12 mA |
| Maximum Reverse Voltage | 5 V |
| Maximum Forward Current, pulsed (1 μ s P.W., 10% D.C.) | 48 mA |

| Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted) | | | | | | |
|---|--------------------------------------|------|-----------|------|---------|---------------------|
| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
| P_{OT} | Total Power Out | 1.5 | | | mW | $I_F = 7\text{ mA}$ |
| I_{TH} | Threshold Current | | | 3.0 | mA | Note 2 |
| V_F | Forward Voltage | | | 2.2 | V | $I_F = 7\text{ mA}$ |
| I_R | Reverse Current | | | 100 | nA | $V_R = 5\text{ V}$ |
| R_S | Series Resistance | 20 | | 55 | ohms | Note 3 |
| η | Slope Efficiency | 0.28 | | | mW/mA | Note 4 |
| λ | Wavelength | 840 | | 860 | nm | |
| $\Delta\lambda$ | Optical Bandwidth | | | 0.85 | nm | |
| θ | Beam Divergence | | 6 | | Degrees | FWHM |
| $\Delta\eta/\Delta T$ | Temp Coefficient of Slope Efficiency | | -0.50 | | %/°C | (0° - 70°C), Note 4 |
| $\Delta\lambda/\Delta T$ | Temp Coefficient of Wavelength | | 0.06 | | nm/°C | (0° - 70°C) |
| ΔI_{TH} | Temp Variance of Threshold Current | | ± 1.0 | | mA | (0° - 70°C), Note 2 |
| $\Delta V_F/\Delta T$ | Temp Coefficient for Forward Voltage | | -2.5 | | mV/°C | (0° - 70°C) |

NOTES:

- (1) RMA flux is recommended. Solder dwell time can be increased to 10 seconds when flow soldering.
- (2) Threshold Current is based on the two line intersection method specified in Telcordia GR-468-Core. Line 1 from 4 mA to 6 mA. Line 2 from 0 mA to 0.5 mA.
- (3) Series Resistance is the slope of the Voltage-Current line from 5 to 8 mA.
- (4) Slope efficiency, is the slope of the best fit LI line from 5 mA to 8 mA with 0.25mA test intervals.

General Note



TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Optek Technology, Inc.
 1645 Wallace Drive, Ste. 130, Carrollton, TX USA 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Vertical Cavity Surface Emitting Laser in Lateral Package



OPV382



NOTICE

This component is sensitive to electrostatic discharge (ESD). To prevent ESD-induced damage and/or degradation to equipment, take normal ESD precautions when handling this product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [VCSEL Lasers](#) category:

Click to view products by [TT Electronics](#) manufacturer:

Other Similar products are found below :

[OPV380](#) [ATBX-00-MQ](#) [ASBX-00-MQ](#) [ASCX-00-MQ](#) [ASDX-00-MQ](#) [ATDX-00-MQ](#) [ATCX-00-MQ](#) [OPV300](#) [OPV302](#) [OPV310Y](#)
[OPV314AT](#) [OPV314YBT](#) [OPV315AT](#) [OPV330](#) [159353940B1300](#) [159353940A6300](#) [V102C121A-850](#) [OPV314](#) [OPV314Y](#) [OPV322](#)
[OPV382](#)