

## Category 6A 6C Outlet



### **Category 6A 6C outlet, black (SGKSsu6-45bk)**

This Category 6A outlet is perfect for use with "6C" 25 x 38 faceplates and POD/GOP boxes.

#### **Features**

- High performance compliant with TIA/EIA 568-B.2-10 at component level
- Quick and easy tool-free lever termination
- Fully shielded die-cast socket body is robust as well as offering outstanding performance in eliminating alien cross-talk
- Compliant with IEC60512-99-001 – suitable for use with IEEE 802.3at (PoE+) applications
- Angled presentation minimizes issues with bend radius
- Window and paper labelling feature

#### **Specifications**

- Weight: 30 grams approx.
- Dimensions: 34 x 25 x 43 mm approx.
- Colour: Silver and black (faceplate adaptor also available in white)
- Materials:
  - Socket housing: Zinc alloy
  - RJ45 contacts: 50µ"/1.27µm gold plating over nickel over phosphor bronze
  - Faceplate adaptor: ABS UL94-V0
- Supplied with hinged shutter, to reduce dust ingress, and a cable tie.
- Supplied as a kit.
- Packaging: In individual poly bag with instructions then bagged in 20's
- EAN number: 5055386506597

## **Category 6A “Euro” Outlet**



### **Category 6A “Euro” Outlet, white (SGKSsu-45wh)**

This Category 6A outlet is designed for use with industry standard “Euro” faceplates with 25 x 50 mm openings.

#### **Features**

- High performance compliant with TIA/EIA 568-B.2-10 at component level
- Quick and easy tool-free lever termination
- Fully shielded die-cast socket body is robust as well as offering outstanding performance in eliminating alien cross-talk
- Compliant with IEC60512-99-001 – suitable for use with IEEE 802.3at (PoE+) applications
- Angled presentation minimizes issues with bend radius
- Supplied with a shuttered front aperture to reduce dust ingress
- Window and paper labelling feature

#### **Specifications**

- Weight: 32 grams
- Colour: White and silver (faceplate adaptor also available in black, to order)
- Dimensions: 54 x 40 x 25 mm
- Materials:
  - Socket housing: Zinc alloy
  - RJ45 contacts: 50µm/1.27 µm gold plating over nickel over phosphor bronze
  - Faceplate adaptor: ABS UL94-V0
- Supplied with cable tie and supplied as a kit
- Packaging: In individual poly bag with instructions, then bagged in 20's
- EAN number: 5055386506580

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Tuk](#) manufacturer:*

Other Similar products are found below :

[SP1GN](#) [SP2GN](#) [SJKWHB](#) [SLJWHPM](#) [SEKH1](#) [SKFRD](#) [KCUAA2BKDPM](#) [KOCSDPM](#) [SGPDL1GY](#) [SP10YW](#) [FACBK](#) [KPH1BK](#)  
[SEKEI-45WH](#) [SP0.5GN](#) [KBNC50DPM](#) [SGKH2](#) [SEPZ5YW](#) [SGPZ3BK](#) [KOCM](#) [KBNC75PM](#) [KOLSMDPM](#) [MGOPPL25](#) [KCHD90WH](#)  
[KUA2WH](#) [LJNTE5A](#) [FJ445](#) [3L32BK](#) [SKH1LJ](#) [SP5RD](#) [KH1](#) [SP1RD](#) [AAVNTECC](#) [SGKSJEPM](#) [SP2YW](#) [T2079](#) [SGKSSU-45WH](#) [SG78](#)  
[KRCAWHWH](#) [KRCAWHWHPM](#) [SEKEIPM](#) [ADQ88](#) [SKFWHPM](#) [SP0.5RD](#) [SP10GY](#) [SACSLJ](#) [KA6-45BKEP](#) [KOLSMDXPM](#) [SKH2](#)  
[TSY](#) [KSH66WH](#)