
TUNGSRAM

Innovation is our heritage EST. 1896







Spotlight G1 5W

LED Spotlight G1 TU WRA IP20 5W 840

93100527

Product information

The Tungsram Recessed Spotlight G1 5W range has functional and minimalistic design with fix and adjustable versions. These LED Spotlights are ideal for small areas to make your ceilings seem higher, or when you are looking for directional lighting. Never was the installations easier and quicker with these products. The Recessed Spotlight G1 5W range offers all the benefits of LED lighting to our customers – fresh light quality, reduced energy consumption and less maintenance.



Spotlight G1 5W LED Spotlight G1 TU WRA IP20 5W 840 T 93100527

Product data

Description LED Spotlight G1 TU WRA IP20 5W 840 T TUNGSRAM - Spotlight G1 5W - 420lm - 5W - 4000K - 80CRI - 93100527[SKU] - Recessed Brand TUNGSRAM Product category Recessed Spotlight 5W Product family Downlighters Application areas Hospitality, Offices, Residential Light source LED Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] 0,117 Body color White, RAL9003 Product dimensions (Length) x (Width) x (Height) In a 85 x Dia 85 x 54	Product code	93100527
Brand TUNGSRAM Product category Recessed Spotlight 5W Product family Downlighters Application areas Hospitality, Offices, Residential Light source LED Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] 0,117 Body color White, RAL9003 Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54	Description	LED Spotlight G1 TU WRA IP20 5W 840 T
Product category Product family Downlighters Application areas Hospitality, Offices, Residential Light source LED Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] O,117 Body color White, RAL9003 Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54	DIALux description	
Product family Application areas Light source Sensor No sensor Emergency option Mounting type Weight [kg] Body color Product dimensions (Length) x (Width) x (Height) Downlighters Hospitality, Offices, Residential LED No sensor Recessed No EM No EM Recessed White, RAL9003	Brand	TUNGSRAM
Application areas Hospitality, Offices, Residential Light source LED Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] 0,117 Body color White, RAL9003 Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54	Product category	Recessed Spotlight 5W
Light source Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] O,117 Body color White, RAL9003 Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54	Product family	Downlighters
Sensor Emergency option No EM Mounting type Recessed Weight [kg] Body color White, RAL9003 Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54	Application areas	Hospitality, Offices, Residential
Emergency optionNo EMMounting typeRecessedWeight [kg]0,117Body colorWhite, RAL9003Product dimensions (Length) x (Width) x (Height)Dia 85 x Dia 85 x 54	Light source	LED
Mounting typeRecessedWeight [kg]0,117Body colorWhite, RAL9003Product dimensions (Length) x (Width) x (Height)Dia 85 x Dia 85 x 54	Sensor	No sensor
Weight [kg] 0,117 Body color White, RAL9003 Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54	Emergency option	No EM
Body color White, RAL9003 Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54	Mounting type	Recessed
Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54	Weight [kg]	0,117
	Body color	White, RAL9003
		Dia 85 x Dia 85 x 54
Operating temperature min [°C] -10	Operating temperature min [°C]	-10
Operating temperature max [°C] 40	Operating temperature max [°C]	40
Rated ambient temperature (tq) [°C] 25	Rated ambient temperature (tq) [°C]	25
Cooling Passive	Cooling	Passive
Certifications CE	Certifications	CE
General warranty [year] 3	General warranty [year]	3

Spotlight G1 5W LED Spotlight G1 TU WRA IP20 5W 840 T 93100527

Performance data

System power [W]	5
Nominal luminous flux [lm]	420
Rated efficacy [lm/W]	84
Rated life L70/B50 [h]	20000
IP front (optical)	20
IP back (electrical)	20
IP Rating	20
Energy efficiency class (EEC)	A+

Photometrical data

Photometric distribution	Narrow Flood
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	>=80
Nominal beam angle [°]	36
UGR value (4H8H)	21,2
Colour consistency in MacAdam steps SDCM	≤4
Photobioligical risk	RG0


Electrical data


IEC protection class	Class II
Operating voltage [V]	220-240V
Rated frequency or frequency range [Hz]	50/60Hz
Lamp input current [mA]	30
Nominal lamp power factor	>=0.8
Controllability	Triac


Logistic data

Box quantity	1
Shipment	Standard
Product status	Available

Light distribution







Downloads & Links

Go to the catalog site (HTTP)

Datasheet (PDF)

Installation guide (PDF)

Images (HTTP)

DoC Document (PDF)

Dimmer Compatibility List (PDF)

Datasheet (FR) (PDF)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Replacement Lamps - Based LEDs category:

Click to view products by TUNGSRAM manufacturer:

Other Similar products are found below:

LAPD-1A LAPD-1R LAPD-2R LAPD-6W LSTD-M4S SSP-1156B153S12 SSP-1157B156U12 SSP-LXS110818BA 560-0101F 560-0103F

LAPD-1W LAPD-6R 560-0104F 585-1113 SSP-LXC1283S24 SSP-3MB96U12G SLL-05EY 1.90.690.684/0000 560-0203F 586-2206
205F SSP-LXS1826U16A LATD-2JW 24LS4-G1 24LS4-R1 MF200-NFW5H MB403-W60-CW-BP 1819LS2-G-CG 387LP-B 387LP-W

6S6LS155-CWR 130MBLS-G-CG 5000404LAMP E10SB12A E10SB130A E10SB24A E10SG12A E10SG130A E10SR12A E10SR130A

E10SW12A E10SY12A E10SY130A 6S6LS130-CWW MF200-BCG12H MF200-NFR5H 24L4-B1 120PSBL-NWW MF200-NKG120

5SB-NFG24H MF200C-NFW28H