

5 and 6-Wire Receptacles, Front Mount, 1/2-14 NPT Threads

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout																		
FK .. 14.5/NPT Typical panel cutout is 22.5 mm.	FK 4.5-* /14.5/NPT	FS 4.5-* /14.5/NPT	5x22 AWG, 105°C, 250 V, 4 A, mates with 5-pin cordsets	<p>Female</p> <table> <tr><td>4</td><td>5</td></tr> <tr><td>3</td><td>1</td></tr> <tr><td>2</td><td></td></tr> </table> <p>Male</p> <table> <tr><td>5</td><td>4</td></tr> <tr><td>1</td><td>3</td></tr> <tr><td>2</td><td></td></tr> </table>	4	5	3	1	2		5	4	1	3	2							
4	5																					
3	1																					
2																						
5	4																					
1	3																					
2																						
FS ..14.5/NPT Typical panel cutout is 22.5 mm.	FK 4.6-* /14.5/NPT	FS 4.6-* /14.5/NPT	6x22 AWG, 105°C, 250 V, 4 A, mates with 6-pin cordsets	<p>Female</p> <table> <tr><td>4</td><td>5</td><td>6</td></tr> <tr><td>3</td><td>1</td><td>2</td></tr> <tr><td>2</td><td></td><td></td></tr> </table> <p>Male</p> <table> <tr><td>6</td><td>5</td><td>4</td></tr> <tr><td>1</td><td>3</td><td>2</td></tr> <tr><td>2</td><td></td><td></td></tr> </table>	4	5	6	3	1	2	2			6	5	4	1	3	2	2		
4	5	6																				
3	1	2																				
2																						
6	5	4																				
1	3	2																				
2																						
	FK 6-* /14.5/NPT	FS 6-* /14.5/NPT	6x24 AWG, 105°C, 60 VAC/75 VDC, 2 A, mates with 6-pin cordsets	<p>Female</p> <table> <tr><td>5</td><td>6</td></tr> <tr><td>4</td><td>3</td></tr> <tr><td>3</td><td>2</td></tr> <tr><td>2</td><td>1</td></tr> </table> <p>Male</p> <table> <tr><td>6</td><td>5</td></tr> <tr><td>1</td><td>4</td></tr> <tr><td>2</td><td>3</td></tr> </table>	5	6	4	3	3	2	2	1	6	5	1	4	2	3				
5	6																					
4	3																					
3	2																					
2	1																					
6	5																					
1	4																					
2	3																					

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.
Standard housing material is nickel plated brass "FS.."; "FSV.." indicates stainless steel.
To specify PVC jacketed cable, add "/S717" to the end of the part number.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for turck manufacturer:

Other Similar products are found below :

[BI10-M30-AP6X-H1141](#) [BI2-G12-AZ33X-7M](#) [BS4151-0/13.5](#) [NI12U-G18-ADZ30X2-B1331](#) [NI12U-M18-AN4X](#) [BI1.5-G08K-AN6X](#) [BI5-G18-AZ3X](#) [BI5-G18-AZ3X-B1331-50MM](#) [VB20](#) [B 5143-0](#) [BMWS 8151-0/9](#) [BI30U-CK40-AP6X2-H1141](#) [NI12U-M18-AP6X-H1141](#) [NI4U-EG08-AN6X-H1341](#) [BS 4151-0/9](#) [NI5-G12-AP6X-H1141](#) [NI14-G18-ADZ30X2](#) [FEN20-4DIP-4DXP-DIN](#) [BC10-QF5.5-RN6X2](#) [PKG 3M-4/S90](#) [FCS-N1/2A4P-AP8X-H1141](#) [FKFD 4.5](#) [RK40-2M](#) [BI5-G18-AP6X-B1441/S34](#) [NI3-EG08K-Y1-H1341](#) [RI360P0-QR24M0-INCRX2-H1181](#) [BCF5-S18-RP4X/S90](#) [BI5-M18-Y0X-H1141](#) [NI35U-CK40-ADZ30X2-B3131 W/BS4](#) [WK 4T-2](#) [IM1-22EX-T](#) [RK 4T-10 BI 2-EG08K-AP6X-V1131](#) [NI12U-MT18-AP4X-H1141](#) [BI1.5-EG08-AP6X-H1341](#) [BC 5-Q08-AP6X2-V1131](#) [BC5-S18-Y1X](#) [CT 2-A30/M C10-T13X/024VDC](#) [FDN20-4S-4XSG-E](#) [FKV-CC](#) [FSFD 8](#) [CMBS 8141-0](#) [BI10-M30-AN6X-H1141](#) [CMB 8151-0](#) [WK 4.5T-2/S618](#) [VB80-P7X9-8/CS12](#) [FKFD 8](#) [NI4U-EG08-RP6X-V1131](#) [PKW 3M-6](#)