



鋁 電 解 電 容 器
ALUMINIUM ELECTROLYTIC CAPACITORS

承 認 書

SPECIFICATION FOR APPROVAL

客 戶	
CUSTOMER:	立创商城
料 號	
P/N:	
型 號	
SERIES:	SMR SERIES
規 格	
SPECIFICATION:	470 μ F25V/ Φ 8*14
日 期	
DATE:	2021 年 06 月 24 日

客 戶 承 認 欄 APPROVAL COLUMN			

承 制 SUPPLIER		
	黃永福	唐晓军

□伯鸿电子公司

地址：广东省佛山市南海桂城季华东路
万科金域蓝湾红霞苑 2 座 1502
TEL: 757-86368545 FAX: 757-86233516
BOR HURNG ELECTRONIC CO., LTD.

ADD: Guangdong Province, Foshan City
Nanhai Guicheng Jihua road Vanke
Golden Mile Island 2 1502 yuan
Hongxia
TEL: 757-86368545 FAX: 757-86233516

□伯鸿电子公司

地址：广东省东莞市长安长盛西路莲花
苑 D 区芙蓉阁 A 座 401
TEL: 769-85312879 FAX: 769-85416647
BOR HURNG ELECTRONIC CO., LTD.

ADD: Dongguan City, Changan Province,
Guangdong Chang Sheng Road, lotus
garden D District lotus Pavilion A
block 401
TEL: 769-85312879 FAX: 769-85416647

□伯鸿电子(肇庆)有限公司

地址：广东省肇庆市端州一路沙湖工业区。
TEL: 758-2710158 FAX: 758-2734058
BOR HURNG ELECTRONIC (ZHAOQING)
CO., LTD.

ADD: SHAHU INDUSTRIAL ZONE DUANZHOU 1
RD., ZHAOQING CITY GUANGDONG PR-
OVINCE.
TEL: 758-2710158 FAX: 758-2734058



承认内容
FOR APPROVAL

客户

CUSTOMER: 立创商城

料号 P/N: CG471ME814BP		系列 Electrolytic Capacitors Series SMR			规格 Specif. 470 μ F25V/ φ 8*14																
电性能 Electric characteristics																					
工作电压 W. V. (V-DC)	标称容量 Nom. Cap. (μF)	容量允差 Cap. Tol. (%) At 100/120Hz/25°C	外形尺寸 Case Size D×L(mm)	漏电流 L. C. (μA) 2minutes/25°C	损失角 D. F. At 100/120Hz/25°C																
25	470	±20%	8*14	117.5	0.14																
ESR 值 E. S. R. (Ω) At 100kHz/25°C	浪涌电压 S. V. (V-DC)	使用温度 Oper. Temp. (°C)	纹波电流 Rip. Cur (mA) At 100/120Hz/105°C	高温负荷 Load Life (HRS/105°C)	高温贮存 Shelf Life (HRS/105°C)																
/	30	-40~+105	364	2000	500																
高温负荷特性 Load Life	在 105°C 环境中对电容器施加额定工作电压连续 2000 小时, 经恢复后于常温 25°C 测试, 其性能符合下表要求 After applying rated working voltage for 2000 hours at 105°C and then being stabilized at +25°C, capacitors shall meet following limits																				
	静电容量变化率 Capacitance change	初测值的 ± 20% 以内 Within ±20% of the initial measured value																			
	损失角正切值 Dissipation Factor	不大于规定值的 200% Less than 200% of the specified value																			
	漏电流 Leakage Current	不大于规定值 Within specified value																			
高温贮存特性 Shelf Life	在 105°C 环境中(不加电压)放置 500 小时, 经恢复后于常温 25°C 测试, 其性能符合下表要求 After storage for 500 hours at 105°C With no voltage applied and then being stabilized at +25°C, capacitors shall meet following limits																				
	静电容量变化率 Capacitance change	初测值的 ± 20% 以内 Within ±20% of the initial measured value																			
	损失角正切值 Dissipation Factor	不大于规定值的 200% Less than 200% of the specified value																			
	漏电流 Leakage Current	不大于规定值的 200% Less than 200% of the specified value																			
纹波电流修正系数 coefficient	频率系数 Frequency coefficient						温度系数 Temperature coefficient														
	W.V (V)	Freq(Hz) Cap.(uF)	50 (60)	100 (120)	1K	10K	100K	温度(°C) Temperature	+105	+85	+65										
	6.3~10	≤1000 >1000	0.8	1.0	1.1	1.2	1.2	系数 Factor	1.0	1.7	2.1										
			0.8	1.0	1.5	1.7	1.7														
	25~35	≤1000 >1000	0.8	1.0	1.2	1.3	1.3														
			0.8	1.0	1.6	1.9	1.9														
50~100	≤1000 >1000	0.8	1.0	1.2	1.3	1.9															
		0.8	1.0	1.2	1.3	1.9															
160~450		0.8	1.0	1.3	1.5	1.6															
尺寸 Diagram: (Unit:mm)																					
				<table border="1"> <tr><td>D</td><td>8</td></tr> <tr><td>L</td><td>14</td></tr> <tr><td>F</td><td>3.5</td></tr> <tr><td>d</td><td>0.5</td></tr> <tr><td>a</td><td>1.5</td></tr> </table>								D	8	L	14	F	3.5	d	0.5	a	1.5
D	8																				
L	14																				
F	3.5																				
d	0.5																				
a	1.5																				
作成 Designer	罗家玲		审核 Auditor	唐晓军		核准 Approved	黄永福														
客户承认 CUSTOMER SIGNATURE																					

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - Radial Leaded](#) category:

Click to view products by [TWBOR](#) manufacturer:

Other Similar products are found below :

[LXY50VB4.7M-5X11](#) [RFO-100V471MJ7P#](#) [ECE-A1EGE220](#) [B41041A2687M8](#) [B41041A7226M8](#) [B41044A7157M6](#)
[EKXG201EC3101ML20S](#) [EKZM160ETD471MHB5D](#) [NCD681K10KVY5PF](#) [NEV1000M25EF-BULK](#) [NEV100M35DC](#) [NEV100M63DE](#)
[NEV220M25DD-BULK](#) [NEV.33M100AA](#) [NEV4700M50HB](#) [NEV.47M100AA](#) [NEVH1.0M250AB](#) [NEVH3.3M250BB](#) [NEVH3.3M450CC](#)
[KM4700/16](#) [KME50VB100M-8X11.5](#) [SG220M1CSA-0407](#) [ES5107M016AE1DA](#) [ESMG160ETD102MJ16S](#) [ESX472M16B](#)
[SZ010M1500A5S-1015](#) [227RZS050M](#) [476CKH100MSA](#) [477RZS050M](#) [UVX1V101KPA1FA](#) [UVX1V222MHA1CA](#) [KME25VB100M-](#)
[6.3X11](#) [VTL100S10](#) [VTL470S10](#) [VTL470S16A](#) [511D336M250EK5D](#) [052687X](#) [ECE-A1CF471](#) [EKMA500ELL4R7ME07D](#) [NRE-](#)
[S560M16V6.3X7TBSTF](#) [RGA221M1CTA-0611G](#) [ERZA630VHN182UP54N](#) [UPL1A331MPH](#) [SK035M0100AZS-0611](#) [MAL214658821E3](#)
[NEV1000M6.3DE](#) [NEV100M16CB](#) [NEV100M50DD-BULK](#) [NEV2200M16FF](#) [NEV220M50EE](#)