




REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD
1	△	Size changes	26/APR/21	KATE	JOHNNY

Electrical

Current Rating: 2.0A AC(rms)/DC  
Voltage Rating: 100V AC(rms)/DC  
Contact Resistance: 10 mΩ Max  
Insulation Resistance: 1000 MΩ MIN  
Withstanding Voltage: 800V AC r.m.s  
Temperature Range—Operating: -25°C~+85°C

Material and Plating


Housing: PA66( UL 94V-2)  
Contact Pin: Brass  
Plating: Tin Plated



Ordering Information

FWF 200 01 - S XX S 2 2 W1 B  
1 2 3 4 5 6 7 8 9 10

1   Category FWF-Wafer	2   Series Number 200-Pitch2.0mm	3   Distinction No. 01	4   Row Option S-Single Row	5   Circuits XX	6   Entry Angle S-180° Vertical
7   Plating 2-Tin Plated	8   Material-Resin 2-PA66	9   Color-Resin W1-White	10   Packaging B-PE Bag		



Recommended P.C.Board Layout

 THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 18/JUN/13	PART NO. FWF20001-SXXS22W1B	ITEM NO. FWF20001	 Leader Of Industry	
	DESIGN UNITS Inch (metric)	X.±.012(0.30) X.X±.008(0.20)	X.'±5' X.'±2'	CHECKED BY JACOB	DATE 18/JUN/13	TITLE Wire to Board (Wafer) Pitch 2.0mm 180° Vertical (DIP)		REV 1
SCALE 5:1	SIZE A4	X.XX±.006(0.15) X.XXX±.004(0.10)	.XX'±1' .XXX'±0.5'	DRAWN BY CHERRY	DATE 18/JUN/13	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

1 2 3 4 5 6 7 8

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

Circuits (n)	Part No.	Dimensions(in/mm)		
		A	B $\triangle$	C
2	FWF20001-S02S22W1B	.079(2.00)	.240(6.10)	.197(5.00)
3	FWF20001-S03S22W1B	.157(4.00)	.319(8.10)	.157(7.00)
4	FWF20001-S04S22W1B	.236(6.00)	.398(10.10)	.354(9.00)
5	FWF20001-S05S22W1B	.315(8.00)	.476(12.10)	.433(11.00)
6	FWF20001-S06S22W1B	.394(10.00)	.555(14.10)	.512(13.00)
7	FWF20001-S07S22W1B	.472(12.00)	.634(16.10)	.591(15.00)
8	FWF20001-S08S22W1B	.551(14.00)	.713(18.10)	.670(17.00)
9	FWF20001-S09S22W1B	.630(16.00)	.791(20.10)	.748(19.00)
10	FWF20001-S10S22W1B	.709(18.00)	.870(22.10)	.827(21.00)
11	FWF20001-S11S22W1B	.787(20.00)	.949(24.10)	.906(23.00)
12	FWF20001-S12S22W1B	.866(22.00)	1.028(26.10)	.984(25.00)
13	FWF20001-S13S22W1B	.945(24.00)	1.106(28.10)	1.063(27.00)
14	FWF20001-S14S22W1B	1.024(26.00)	1.185(30.10)	1.142(29.00)
15	FWF20001-S15S22W1B	1.102(28.00)	1.264(32.10)	1.220(31.00)
16	FWF20001-S16S22W1B	1.181(30.00)	1.343(34.10)	1.299(33.00)

A

B

C

D

E

F

A



B

C

D

E

F

 THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 18/JUN/13	PART NO. FWF20001-SXXS22W1B	ITEM NO. FWF20001	 Leader Of Industry	
	DESIGN UNITS Inch (metric)	X.±.012(0.30) X.X±.008(0.20)	X.±5' X.±2'	CHECKED BY JACOB	DATE 18/JUN/13	TITLE Wire to Board (Wafer) Pitch 2.0mm 180° Vertical (DIP)		REV 1
	SCALE 5:1	SIZE A4	X.XX±.006(0.15) X.XXX±.004(0.10)	DRAWN BY CHERRY	DATE 18/JUN/13	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

1 2 3 4 5 6 7 8

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TXGA](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)