

CH0016

Technical Datasheet



Features

- · LED status indicator
- · Contains charger, universal power supply and line cord

Benefits

- · Specifically designed to charge Ultralife LI-7 (UBBL03) battery safely & efficiently
- · Safety circuit protects against charging shorted packs

Applications

Charger for LI-7 (UBBL03) Battery

Technical Specifications	
Part No.	CH0016
DC Input	19-30VDC
DC Output	16.8V
Charge Rate	3.0A
Battery Types	Li-ion
User Interface	Off: No battery detected Green blinking: Charging Green stead on: Charge complete Red blinking: Error - shorted terminals, invalid pack chemistry
Connectors	Input: 2.5mm DC connector Output: Souriau - JBXFN1G05MCSDSMR
Color	Black
Finish	ABS G1SM
Size	Charger: 92mm (3.63in) x 58mm (2.27in) x 52mm (2.04in) Charger Cable: 61cm (24in)
Weight	170g (6.0oz)
Operating Temperature	0°C to 45°C
Storage Temperature	-25°C to 70°C
Export Control Classification	3A611.x
Harmonized Tariff Schedule	8507.90.8000
Accessories Included	Power Supply - PS2524 Input Voltage: 100-250VAC, 50-60Hz Output Voltage: 24VDC Input Connector: IEC-320 Output Cable: 18Awg, 1.83m (6ft) Weight: 425g (15oz) Line Cord - UL/CSA 3 prong (North America), length 1.83m (6ft)
Accessories Optional	CA0003: Vehicle Power Adapter Line cords: USA: 1090-01-0002 AUS: 1090-01-0004 EUR: 1090-01-0008 UK: 1090-01-0010

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Battery Chargers category:

Click to view products by Ultralife manufacturer:

Other Similar products are found below:

CH0011 CB1210A PS-034052 GP X411 AA/AAA + 4X R6 2700MAH RECYKO CB243A CB123A CB12245A DA60U-240A-R DA84U-240A-R DA200U-250A-R MC2 MC1 VP4 PLUS DRAGON LCD MULTI CHARGER MINI-CHARGER 5V 2.1A PB320 PB50 PB550 + 4XAA 2700MAH VC4 POCKET-CHARGER + 4XAA 2100MAH PB-300P-12 MINI CHARGER + 2XAA 2100MAH CHFC3 GC30U-5P1J TSP-BCM48 SBP-001 PB-300N-12 GC30B-11P1J GC220A12-AD1 DBU-3200-24 RRC-SMB-MBC TSP-BCM12 TSP-BCMU360 TSP-BCM48A H-TRONIC AL 2000PLUS H-TRONIC HTDC 5000 ES240J ES360A LS-CR45-PQ LS-CR45-PD WHITE 5V 1A MC3 PB2 BLUE SC1 SC2 VC2S X2 X4 CEF14 2XAA 2XAAA