

UCA0114: Smart 2590 Data & Power Cable

Technical Datasheet



Technical Specifications

Part No.	UCA0114
Cable	Power - (4) 16AWG conductors Communication - (7) 22AWG conductors
Max. Voltage	36VDC
Max. Current	30V Mode: 6.0A continuous 15V Mode: 12.0A continuous
Temperature Rating	-40°C to 70°C
Length	1.828m (72.0in)
Termination	Flying leads
Weight	0.45kg
Material	SVT, UL2464 jacketed
Color	Black

Features

- Durable molded housing with mating connector for Ultralife Smart 2590 Batteries
- Full wrap-around nylon strap for secure connection in rugged environment

Benefits

- Low profile design - conforms to surface of battery
- Access information in a remote environment
- Versatile cable to be used with Ultralife Smart 2590 Batteries (UBBL10 and UBBL13)
- Water resistant housing
- Flying lead connectors allow charging with a power supply and discharging with any electronic device
- Flying lead connectors allow flexibility for customers to terminate ends to match their device's connector

Applications

- Field access to SMBus information (state of charge, voltage, temperature, calibration status, etc.)
- Diagnostics and testing
- Bench-top charging and discharging of Ultralife Smart 2590 Batteries

Pin Configuration	Power Side Cable (Black)
	Black Batt A -
	Red Batt A +
	Green Batt B -
	White Batt B +
Communication Side Cable (Grey)	
	Brown Batt A -
	Blue Batt B -
	Gray Batt B Data
	Violet Batt B Clock
	Yellow Batt A Data
	Orange Batt A Clock
	Pink Batt Pin 3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Cords](#) category:

Click to view products by [Ultralife](#) manufacturer:

Other Similar products are found below :

[172-4000](#) [172-4101](#) [172-7443-E](#) [21033836407](#) [2J-1865A](#) [2R7006A20A120](#) [426055400-3](#) [MN47A4BC01M010](#) [H-OU-2](#) [CA0002](#)
[420680840-3](#) [426451500-3](#) [P162PT4-36](#) [1-832692-4](#) [FJ-VSP 3M](#) [96CB-POWER-B-1.8M2](#) [426040200](#) [CA0006](#) [H-OU-27](#) [1700019464](#) [FJ-](#)
[VSP 10M](#) [MN47B4BC01M040](#) [H-OU-20](#) [2-836917-8](#) [867566-1](#) [804001P03M050G](#) [2050KH1-BK](#) [426013710-3](#) [58257-1069](#) [216603-0037](#)
[1011147](#) [1011324](#) [1012028](#) [862545-5](#) [BXC-10567](#) [172-2555](#) [32102-022800-200-RS](#) [P29000-M2](#) [P29004-M2](#) [DC.CAB.0201.0150](#)
[DC.CAB.0301.0150](#) [DC.CAB.0610.0150](#) [DC.CAB.0700.0150](#) [DC.CAB.1000.0300](#) [DC.CAB.1100.0150](#) [DC.CAB.1400.0150](#)
[DC.CAB.1410.0150](#) [DC.CAB.1500.0150](#) [DC.CAB.1811.0150](#) [DC.CAB.1900.0150](#)