

UCH0040

Technical Datasheet



0	3	м	ш	7	3	2

- · Ultra light weight, ultra compact Solar charger for most small USB devices
- Proprietary charging circuitry maximizes charge into the AA batteries provided with the Solar charger
- · LED status indicator
- · Full charge in four hour of full sun
- · Six grommets are built into the charger to allow for secure fastening to a pack or to the ground
- · Folds up compactly to fit into pocket

Applications

· Charges most small USB devices

Technical Specifications				
Part No	UCH0040-01: Desert Camouflage UCH0040-02: Digital Camouflage			
Solar Operating Current	400mA			
USB Charging Voltage	5.0V			
USB Charging Current	Up to 500mA			
Battery Types	NiMH or NiCD AA batteries (1800-2500mAh)			
User Interface	LED Solid light: Fully charged LED Blinking light: Charging LED Rapid pulse: Battery fault LED Off: Replace batteries if no light appears			
Size	Folded: 83mm(3.25in) x 140mm(5.5in) x 35mm(1.38in) Unfolded: 620mm(24in) x 140mm(5.5)			
Weight	139 grams (4.9oz)			
Storage	AA Batteries may be stored overnight in the battery compartment. For extended storage, remove the AA batteries from the compartment.			
Connectors	Output: USB connector			
Accessories Included	Rechargeable AA batteries			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Battery Chargers category:

Click to view products by Ultralife manufacturer:

Other Similar products are found below:

CH0011 CB1210A PS-034052 GP X411 AA/AAA + 4X R6 2700MAH RECYKO CB123A CB12245A DA60U-240A-R DA200U-250A-R MC2 MC1 BQ-CC55E VP4 PLUS DRAGON LCD MULTI CHARGER MINI-CHARGER 5V 2.1A PB320 PB50 PB550 + 4XAA 2700MAH VC4 POCKET-CHARGER + 4XAA 2100MAH PB-300P-12 VC2 MINI CHARGER + 2XAA 2100MAH CHFC3 GC30U-5P1J TSP-BCM48 SBP-001 PB-300N-12 GC30B-11P1J GC220A12-AD1 PSC-122000A-C TSP-BCM12 TSP-BCMU360 TSP-BCM48A H-TRONIC AL 2000PLUS H-TRONIC HTDC 5000 ES240J ES360A LS-CR45-PQ LS-CR45-PD WHITE 5V 1A PB2 BLUE SC1 SC2 X2 X4 CEF14 2XAA 2XAAA CEF27 2XAA 2XAAA CL14.4VDC-0.4A CL14.4VDC-0.7A