

# Voltage tester 220 - 250 V

#### 630VDE



#### **Profiles**




#### Standards

DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018

#### **Product features**

- dimension 140 with clip
- made according to standard DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018



	axb	C	L	
617659	0.5 x 3.0	60	140	13
617660	0.6 x 3.5	90	180	24

<sup>\*</sup> Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

### Usage (pictures)



Ergonomic handle design for protecting your hands.



Large hand contact area for more torque power.



## Safety tips



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Screwdrivers, Nut Drivers & Socket Drivers category:

Click to view products by UNIOR manufacturer:

Other Similar products are found below:

1406504-2 272012M 271001M 30246 HMM-HH 32024 TL10416 612020B 35-045 6951 83 9977 EMF 99833 RB1 S3166V X103V XTD10TP X108N HS7N HS618N LN25MMN HS18N XST1010N P4N R146N P12SN R5324N 99764N P8N 99312N R3163N SX101N LN22N XTD10N 9955MMN 995MMN 996MMN LN25N THS9N R3166N R144N RB2N HS10N 99964BPN HS11N HS12N THS8N TL12N LN23BPN