

## 2SA1627A

## PNP SILICON TRANSISTOR


## PNP EPITAXIAL SILICON TRANSISTOR

## ■ DESCRIPTION

The UTC 2SA1627A is designed for general purpose amplifier and high speed switching applications.

## ■ FEATURES

- \* High voltage
- \* Low collector saturation voltage.
- \* High-speed switching



## ■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
2SA1627AL-x-AA3-R	2SA1627AG-x-AA3-R	SOT-223	B	C	E	Tape Reel
2SA1627AL-x-TM3-T	2SA1627AG-x-TM3-T	TO-251	B	C	E	Tube
2SA1627AL-x-TN3-R	2SA1627AG-x-TN3-R	TO-252	B	C	E	Tape Reel
2SA1627AL-x-T60-K	2SA1627AG-x-T60-K	TO-126	E	C	B	Bulk
2SA1627AL-x-T6C-K	2SA1627AG-x-T6C-K	TO-126C	E	C	B	Bulk

Note: Pin Assignment: E: Emitter    C: Collector    B: Base

	(1)K: Bulk, R: Tape Reel, T: Tube (2)AA3: SOT-223, TM3: TO-251, TN3: TO-252 T6C: TO-126C, T60: TO-126 (3)x: reference to Classification of $h_{FE1}$ (4)G: Halogen Free and Lead Free, L: Lead Free
--	---

## ■ MARKING

PACKAGE	MARKING
SOT-223	
TO-251 / TO-252	
TO-126 / TO-126C	

■ ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	$V_{CBO}$	-600	V
Collector-Emitter Voltage	$V_{CEO}$	-600	V
Emitter-Base Voltage	$V_{EBO}$	-7.0	V
Collector Power Dissipation	SOT-223	0.8	W
	TO-251/TO-252	1.9	W
	TO-126/TO-126C	1.0	W
Collector Current (DC)	$I_C$	-1.0	A
Collector Current (Pulse) (Note 2)	$I_{CP}$	-2.0	A
Junction Temperature	$T_J$	+150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2.  $P_W \leq 10\text{ms}$ , Duty Cycle  $\leq 50\%$

■ ELECTRICAL CHARACTERISTICS ( $T_A=25^\circ\text{C}$ , unless otherwise specified)







PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Cut-Off Current	$I_{CBO}$	$V_{CB} = -600\text{V}$ , $I_E = 0$			-10	$\mu\text{A}$
Emitter Cut-Off Current	$I_{EBO}$	$V_{EB} = -7.0\text{V}$ , $I_C = 0$			-10	$\mu\text{A}$
DC Current Gain (Note 2)	$h_{FE1}$	$V_{CE} = -5.0\text{V}$ , $I_C = -0.1\text{A}$	30		120	
	$h_{FE2}$	$V_{CE} = -5.0\text{V}$ , $I_C = -0.5\text{A}$	4			
Collector-Emitter Saturation Voltage (Note)	$V_{CE(SAT)}$	$I_C = -0.3\text{A}$ , $I_B = -0.06\text{A}$		-0.28	-1.5	V
Base-Emitter Saturation Voltage (Note)	$V_{BE(SAT)}$	$I_C = -0.3\text{A}$ , $I_B = -0.06\text{A}$		-0.85	-1.2	V
Gain Bandwidth Product	$f_T$	$V_{CE} = -10\text{V}$ , $I_E = 0.1\text{A}$	10	28		MHz
Output Capacitance	$C_{OB}$	$V_{CB} = -10\text{V}$ , $I_E = 0$ , $f = 1.0\text{MHz}$	42	50		$\text{pF}$
Turn-On Time	$t_{ON}$	$I_C = -0.5\text{A}$ , $R_L = 500\Omega$ , $I_{B1} = -I_{B2} = -0.1\text{A}$ , $V_{CC} = -250\text{V}$		0.1	0.5	$\mu\text{s}$
Storage Time	$T_{SYG}$			3.5	5.0	$\mu\text{s}$
Fall Time	$t_F$			0.08	0.5	$\mu\text{s}$

Note: Pulsed  $P_W \leq 350\mu\text{s}$ , Duty Cycle  $\leq 2\%$


■ CLASSIFICATION OF  $h_{FE1}$ 

RANK	M	L	K
RANGE	30-60	40-80	60-120

■ TYPICAL CHARACTERISTICS



## ■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Bipolar Transistors - BJT category:***

***Click to view products by Unisonic manufacturer:***

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MMBT-2369-TR](#) [BC546/116](#) [BC557/116](#) [BSW67A](#) [NJVMJD148T4G](#) [NTE123AP-10](#) [NTE153MCP](#) [NTE16](#)  
[NTE195A](#) [NTE92](#) [2N4401-A](#) [2N6728](#) [2SA1419T-TD-H](#) [2SA2126-E](#) [2SB1204S-TL-E](#) [2SC2712S-GR,LF](#) [SP000011176](#) [2N2907A](#) [2N3904-](#)  
[NS](#) [2N5769](#) [2SC2412KT146S](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [MJE340](#) [Jantx2N5416](#) [US6T6TR](#) [NJL0281DG](#) [732314D](#) [CPH3121-TL-E](#)  
[CPH6021-TL-H](#) [873787E](#) [IMZ2AT108](#) [MMST8098T146](#) [UMX21NTR](#) [MCH6102-TL-E](#) [NJL0302DG](#) [30A02MH-TL-E](#) [NTE13](#) [NTE26](#)  
[NTE282](#) [NTE323](#) [NTE350](#) [NTE81](#) [STX83003-AP](#) [JANTX2N2920L](#) [JANSR2N2222AUB](#) [CMLT3946EG TR](#) [2SA1371D-AE](#)