




BC817

NPN SILICON TRANSISTOR


NPN GENERAL PURPOSE AMPLIFIER

DESCRIPTION

The UTC **BC817** is designed for general purpose medium power amplifiers and switches requiring collector currents to 1.2A.



SOT-23
(JEDEC TO-236)



SOT-323

ORDERING INFORMATION

Ordering Number	Package	Pin Assignment			Packing
		1	2	3	
BC817G-xx-AE3-R	SOT-23	E	B	C	Tape Reel
BC817G-xx-AL3-R	SOT-323	E	B	C	Tape Reel

Note: Pin Assignment: C: Collector B: Base E: Emitter

<p>BC817G-xx-AE3-R</p> <p>(1) Packing Type (2) Package Type (3) Rank (4) Green Package</p>	<p>(1) R: Tape Reel (2) AE3: SOT-23, AL3: SOT-323 (3) xx: refer to Classification of hFE1 (4) G: Halogen Free and Lead Free</p>
--	---

MARKING

BC817-16	BC817-25	BC817-40

■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Base Voltage		V_{CES}	50	V
Collector-Emitter Voltage		V_{CEO}	45	V
Emitter-Base Voltage		V_{EBO}	5.0	V
Collector Current -Continuous	Continuous	I_C	1.5	A
	Peak	I_{CM}	1.7	A
Collector Dissipation	SOT-23	P_C	310	mW
	SOT-323		200	mW
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-65 ~ +150	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.







■ ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C=10\text{mA}, I_B=0$	45			V
Collector-Base Breakdown Voltage	BV_{CES}	$I_C=100\mu\text{A}, I_E=0$	50			V
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E=10\mu\text{A}, I_C=0$	5			V
Collector Cut-OFF Current	I_{CBO}	$V_{CB}=20\text{V}$			100	nA
		$V_{CB}=20\text{V}, T_A=150^{\circ}\text{C}$			5	μA
Collector Cutoff Current	I_{CEO}	$V_{CE}=45\text{V}$			100	nA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=5\text{V}$			100	nA
ON CHARACTERISTICS						
DC Current Gain	h_{FE1}	$I_C=100\text{mA}, V_{CE}=1.0\text{V}$	See Classification			
	h_{FE2}	$I_C=500\text{mA}, V_{CE}=1.0\text{V}$	40			
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$			0.7	V
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$			1.2	V
Base-Emitter On Voltage	$V_{BE(ON)}$	$I_C=500\text{mA}, V_{CE}=1.0\text{V}$			1.2	V



■ CLASSIFICATION OF h_{FE1}

RANK	16	25	40
RANGE	100-250	160-400	250-600

TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [Unisonic manufacturer](#):

Other Similar products are found below :

[BC559C](#) [MCH4017-TL-H](#) [MMBT-2369-TR](#) [BC546/116](#) [NJVMJD148T4G](#) [NTE16](#) [NTE195A](#) [IMX9T110](#) [2N4401-A](#) [2N6728](#) [2SA1419T-TD-H](#) [2SB1204S-TL-E](#) [2SC5488A-TL-H](#) [FMC5AT148](#) [2N2369ADCSM](#) [2N2907A](#) [2N3904-NS](#) [2N5769](#) [2SC4618TLN](#) [CPH6501-TL-E](#) [US6T6TR](#) [BAX18/A52R](#) [BC556/112](#) [IMZ2AT108](#) [MMST8098T146](#) [MCH6102-TL-E](#) [BC846B-13-F](#) [2N3879](#) [30A02MH-TL-E](#) [NTE13](#) [NTE282](#) [NTE323](#) [NTE350](#) [NTE81](#) [JANTX2N2920L](#) [JANSR2N2907AUB](#) [CMLT3946EG TR](#) [SNSS40600CF8T1G](#) [CMLT3906EG TR](#) [GRP-DATA-JANS2N2907AUB](#) [GRP-DATA-JANS2N2222AUA](#) [MMDT3946FL3-7](#) [2N4240](#) [JANS2N3019](#) [MSB30KH-13](#) [2N2221AUB](#) [2SD1815T-TL-E](#) [2N6678](#) [2N2907Ae4](#) [JAN2N3507](#)