

## LM2940

## LINEAR INTEGRATED CIRCUIT

## 1A LOW-DROPOUT POSITIVE VOLTAGE REGULATOR

## ■ DESCRIPTION

The UTC **LM2940** is a low dropout regulator designed to provide output current up to 1A with a typically 500mV dropout Voltage and a maximum of 1V. It is capable of reducing the ground current when the differential between the input voltage and the output voltage outrun 3V.

UTC **LM2940** offers low quiescent current (typically 30mA at 1A and an input-output differential of 5V). Higher quiescent currents only exist when the regulator is in the dropout mode ( $V_{IN}-V_{OUT} \leq 3V$ ).

## ■ FEATURES


- \* 500mV Typically Dropout at 1A
- \* Output Current in Excess of 1A
- \* Low Quiescent Current
- \* Reversed-Battery Protection
- \* Current Limit and Thermal Shutdown.
- \* Mirror Image Insertion Protection

## ■ ORDERING INFORMATION



Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
-	LM2940G-xx-AA3-R	SOT-223	I	G	O	Tape Reel
LM2940L-xx-TA3-T	LM2940G-xx-TA3-T	TO-220	I	G	O	Tube
LM2940L-xx-TF3-T	LM2940G-xx-TF3-T	TO-220F	I	G	O	Tube
LM2940L-xx-TN3-R	LM2940G-xx-TN3-R	TO-252	I	G	O	Tape Reel
LM2940L-xx-TQ2-R	LM2940G-xx-TQ2-R	TO-263	I	G	O	Tape Reel
LM2940L-xx-TQ2-T	LM2940G-xx-TQ2-T	TO-263	I	G	O	Tube
LM2940L-xx-TQ3-R	LM2940G-xx-TQ3-R	TO-263-3	I	G	O	Tape Reel
LM2940L-xx-TQ3-T	LM2940G-xx-TQ3-T	TO-263-3	I	G	O	Tube

Notes: 1. xx: Output Voltage, refer to Marking Information.

2. Pin Assignment: I:  $V_{IN}$  G: GND O: $V_{OUT}$

 LM2940G-xx-AA3-R	(1)Packing Type	(1) R: Tape Reel, T: Tube
	(2)Package Type	(2) AA3: SOT-223, TA3: TO-220, TF3: TO-220F
	(3)Output Voltage Code	TN3: TO-252, TQ2: TO-263, TQ3: TO-263-3
	(4)Green Package	(3) xx: refer to Marking Information
		(4) G: Halogen Free and Lead Free, L: Lead Free

### ■ MARKING INFORMATION

PACKAGE	VOLTAGE CODE	MARKING
SOT-223	50 : 5V 60 : 6V 80 : 8V 90 : 9V 10 : 10V 12 : 12V 15 : 15V	 <p>LM2940G</p> <p>Voltage Code ← Date Code</p> <p>1 2 3</p>
TO-220 TO-252 TO-263 TO-263-3		 <p>UTC</p> <p>LM2940</p> <p>Voltage Code ← L: Lead Free Lot Code ← G: Halogen Free</p> <p>Date Code</p> <p>1 2 3</p>

### ■ ABSOLUTE MAXIMUM RATINGS

PARAMETER		SYMBOL	RATINGS	UNIT
Input Voltage		V <sub>IN</sub>	26	V
Power Dissipation		P <sub>D</sub>	Internally limited	
Junction Temperature		T <sub>J</sub>	+150	°C
Ambient Operating Temperature	TO-220/TO-220F	T <sub>OPR</sub>	-40 ~ +125	°C
	TO-263-3/TO-263			
	SOT-223/ TO-252		-40 ~ +85	
Storage Temperature		T <sub>STG</sub>	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

### ■ THERMAL DATA

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	SOT-223	θ <sub>JA</sub>	174	°C/W
	TO-220/TO-220F		60	
	TO-263/TO-263-3		80	
	TO-252		125	
Junction to Case	TO-220/TO-263	θ <sub>JC</sub>	4	°C/W
	TO-263-3		6	
	TO-220F		12	
	TO-252		15	
	SOT-223			

### ■ ELECTRICAL CHARACTERISTICS

(T<sub>A</sub>=T<sub>J</sub> =25°C, V<sub>IN</sub>=V<sub>OUT</sub>+5V, I<sub>OUT</sub>=1A and C<sub>OUT</sub>=22μF, unless otherwise specified.)

#### For LM2940-5.0V

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V <sub>OUT</sub>	6.25V ≤ V <sub>IN</sub> ≤ 26V, 5mA ≤ I <sub>OUT</sub> ≤ 1A	4.85	5.00	5.15	V
Line Regulation	△V <sub>OUT</sub>	V <sub>OUT</sub> +2V ≤ V <sub>IN</sub> ≤ 26V, I <sub>OUT</sub> =5mA		20	50	mV
Load Regulation	△V <sub>OUT</sub>	50mA ≤ I <sub>OUT</sub> ≤ 1A		35	50	mV
Output Impedance	R <sub>OUT</sub>	100 mA DC and 20mA <sub>RMS</sub> , f <sub>O</sub> =120Hz		35		mΩ
Quiescent Current	I <sub>Q</sub>	V <sub>OUT</sub> +2V ≤ V <sub>IN</sub> ≤ 26V, I <sub>OUT</sub> =5mA		10	15	mA
Output Noise Voltage	e <sub>N</sub>	10Hz-100kHz, I <sub>OUT</sub> =5mA		150		μV <sub>RMS</sub>
Ripple Rejection	RR	f <sub>O</sub> =120Hz, 1V <sub>RMS</sub> , I <sub>OUT</sub> =100mA	54	72		dB
Long Term Stability				20		mV/1000Hr
Dropout Voltage	V <sub>D</sub>	I <sub>OUT</sub> =1A		0.5	0.8	V
		I <sub>OUT</sub> =100mA		0.13	0.15	
Short Circuit Current	I <sub>SC</sub>	(Note)		2.5		A
Maximum Line Transient	T <sub>IN</sub>	R <sub>OUT</sub> =100Ω, T ≤ 100ms	60	75		V
Reverse Polarity DC Input Voltage	V <sub>RIN</sub>	R <sub>OUT</sub> =100Ω	-15	-30		V
Reverse Polarity Transient Input Voltage	V <sub>TRRI</sub>	R <sub>OUT</sub> =100Ω, T ≤ 100ms	-50	-75		V

## ■ ELECTRICAL CHARACTERISTICS(Cont.)

## For LM2940-6.0V

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	$V_{OUT}$	$7.5V \leq V_{IN} \leq 26V, 5mA \leq I_{OUT} \leq 1A$	5.82	6.00	6.18	V
Line Regulation	$\Delta V_{OUT}$	$V_{OUT}+2V \leq V_{IN} \leq 26V, I_{OUT}=5mA$		20	60	mV
Load Regulation	$\Delta V_{OUT}$	$50mA \leq I_{OUT} \leq 1A$		40	60	mV
Output Impedance	$R_{OUT}$	100 mA DC and 20mA <sub>RMS</sub> , $f_O=120Hz$		40		mΩ
Quiescent Current	$I_Q$	$V_{OUT}+2V \leq V_{IN} \leq 26V, I_{OUT}=5mA$		10	15	mA
Output Noise Voltage	$e_N$	10Hz-100kHz, $I_{OUT}=5mA$		180		µV <sub>RMS</sub>
Ripple Rejection	RR	$f_O=120Hz, 1V_{RMS}, I_{OUT}=100mA$	60	72		dB
Long Term Stability				20		mV/1000Hr
Dropout Voltage	$V_D$	$I_{OUT}=1A$ $I_{OUT}=100mA$		0.5 0.13	0.8 0.15	V
Short Circuit Current	$I_{SC}$	(Note)		2.5		A
Maximum Line Transient	$T_{IN}$	$R_{OUT}=100\Omega, T \leq 100ms$	60	75		V
Reverse Polarity DC Input Voltage	$V_{RIN}$	$R_{OUT}=100\Omega$	-15	-30		V
Reverse Polarity Transient Input Voltage	$V_{TRRI}$	$R_{OUT}=100\Omega, T \leq 100ms$	-50	-75		V

## For LM2940-8.0V

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	$V_{OUT}$	$9.4V \leq V_{IN} \leq 26V, 5mA \leq I_{OUT} \leq 1A$	7.76	8.00	8.24	V
Line regulation	$\Delta V_{OUT}$	$V_{OUT}+2V \leq V_{IN} \leq 26V, I_{OUT}=5mA$		20	80	mV
Load Regulation	$\Delta V_{OUT}$	$50mA \leq I_{OUT} \leq 1A$		55	80	mV
Output Impedance	$R_{OUT}$	100 mA DC and 20mA <sub>RMS</sub> , $f_O=120Hz$		55		mΩ
Quiescent Current	$I_Q$	$V_{OUT}+2V \leq V_{IN} \leq 26V, I_{OUT}=5mA$		10	15	mA
Output Noise Voltage	$e_N$	10Hz-100kHz, $I_{OUT}=5mA$		240		µV <sub>RMS</sub>
Ripple Rejection	RR	$f_O=120Hz, 1V_{RMS}, I_{OUT}=100mA$	54	66		dB
Long Term Stability				32		mV/1000Hr
Dropout Voltage	$V_D$	$I_{OUT}=1A$ $I_{OUT}=100mA$		0.5 0.13	0.8 0.15	V
Short Circuit Current	$I_{SC}$	(Note)		2.5		A
Maximum Line Transient	$T_{IN}$	$R_{OUT}=100\Omega, T \leq 100ms$	60	75		V
Reverse Polarity DC Input Voltage	$V_{RIN}$	$R_{OUT}=100\Omega$	-15	-30		V
Reverse Polarity Transient Input Voltage	$V_{TRRI}$	$R_{OUT}=100\Omega, T \leq 100ms$	-50	-75		V

## For LM2940-9.0V

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	$V_{OUT}$	$10.5V \leq V_{IN} \leq 26V, 5mA \leq I_{OUT} \leq 1A$	8.73	9.00	9.27	V
Line regulation	$\Delta V_{OUT}$	$V_{OUT}+2V \leq V_{IN} \leq 26V, I_{OUT}=5mA$		20	90	mV
Load Regulation	$\Delta V_{OUT}$	$50mA \leq I_{OUT} \leq 1A$		60	90	mV
Output Impedance	$R_{OUT}$	100 mA DC and 20mA <sub>RMS</sub> , $f_O=120Hz$		60		mΩ
Quiescent Current	$I_Q$	$V_{OUT}+2V \leq V_{IN} \leq 26V, I_{OUT}=5mA$		10	15	mA
Output Noise Voltage	$e_N$	10Hz-100kHz, $I_{OUT}=5mA$		270		µV <sub>RMS</sub>
Ripple Rejection	RR	$f_O=120Hz, 1V_{RMS}, I_{OUT}=100mA$	52	64		dB
Long Term Stability				34		mV/1000Hr
Dropout Voltage	$V_D$	$I_{OUT}=1A$ $I_{OUT}=100mA$		0.5 0.13	0.8 0.15	V
Short Circuit Current	$I_{SC}$	(Note)		2.5		A
Maximum Line Transient	$T_{IN}$	$R_{OUT}=100\Omega, T \leq 100ms$	60	75		V
Reverse Polarity DC Input Voltage	$V_{RIN}$	$R_{OUT}=100\Omega$	-15	-30		V
Reverse Polarity Transient Input Voltage	$V_{TRRI}$	$R_{OUT}=100\Omega, T \leq 100ms$	-50	-75		V

# LM2940

## LINEAR INTEGRATED CIRCUIT

### ■ ELECTRICAL CHARACTERISTICS(Cont.)

For LM2940-10V

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	$V_{OUT}$	$11.5V \leq V_{IN} \leq 26V, 5mA \leq I_{OUT} \leq 1A$	9.70	10.00	10.30	V
Line regulation	$\Delta V_{OUT}$	$V_{OUT} +2V \leq V_{IN} \leq 26V, I_{OUT} =5mA$		20	100	mV
Load Regulation	$\Delta V_{OUT}$	$50mA \leq I_{OUT} \leq 1A$		65	100	mV
Output Impedance	$R_{OUT}$	100mA DC and 20mA <sub>RMS</sub> , $f_O=120Hz$		65		mΩ
Quiescent Current	$I_Q$	$V_{OUT} +2V \leq V_{IN} \leq 26V, I_{OUT} =5mA$		10	15	mA
Output Noise Voltage	$e_N$	10Hz-100kHz, $I_{OUT} =5mA$		300		µV <sub>RMS</sub>
Ripple Rejection	RR	$f_O=120Hz, 1V_{RMS}, I_{OUT} =100mA$	51	63		dB
Long Term Stability				36		mV/1000Hr
Dropout Voltage	$V_D$	$I_{OUT} =1A$ $I_{OUT} =100mA$		0.5 0.13	0.8 0.15	V
Short Circuit Current	$I_{SC}$	(Note)		2.5		A
Maximum Line Transient	$T_{IN}$	$R_{OUT}=100\Omega, T \leq 100ms$	60	75		V
Reverse Polarity DC Input Voltage	$V_{RIN}$	$R_{OUT}=100\Omega$	-15	-30		V
Reverse Polarity Transient Input Voltage	$V_{TRRI}$	$R_{OUT}=100\Omega, T \leq 100ms$	-50	-75		V

UTC LM2940-12V

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	$V_{OUT}$	$13.6V \leq V_{IN} \leq 26V, 5mA \leq I_{OUT} \leq 1A$	11.64	12.00	12.36	V
Line regulation	$\Delta V_{OUT}$	$V_{OUT} +2V \leq V_{IN} \leq 26V, I_{OUT} =5mA$		20	120	mV
Load Regulation	$\Delta V_{OUT}$	$50mA \leq I_{OUT} \leq 1A$		55	120	mV
Output Impedance	$R_{OUT}$	100mA DC and 20mA <sub>RMS</sub> , $f_O=120Hz$		80		mΩ
Quiescent Current	$I_Q$	$V_{OUT} +2V \leq V_{IN} \leq 26V, I_{OUT} =5mA$		10	15	mA
Output Noise Voltage	$e_N$	10Hz-100kHz, $I_{OUT} =5mA$		360		µV <sub>RMS</sub>
Ripple Rejection	RR	$f_O=120Hz, 1V_{RMS}, I_{OUT} =100mA$	54	66		dB
Long Term Stability				48		mV/1000Hr
Dropout Voltage	$V_D$	$I_{OUT} =1A$ $I_{OUT} =100mA$		0.5 0.11	0.8 0.15	V
Short Circuit Current	$I_{SC}$	(Note)		2.5		A
Maximum Line Transient	$T_{IN}$	$R_{OUT}=100\Omega, T \leq 100ms$	60	75		V
Reverse Polarity DC Input Voltage	$V_{RIN}$	$R_{OUT}=100\Omega$	-15	-30		V
Reverse Polarity Transient Input Voltage	$V_{TRRI}$	$R_{OUT}=100\Omega, T \leq 100ms$	-50	-75		V


## ■ ELECTRICAL CHARACTERISTICS(Cont.)

## UTC LM2940-15V

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	$V_{OUT}$	$16.75V \leq V_{IN} \leq 26V$ , $5mA \leq I_{OUT} \leq 1A$	14.55	15.00	15.45	V
Line regulation	$\Delta V_{OUT}$	$V_{OUT} +2V \leq V_{IN} \leq 26V$ , $I_{OUT} =5mA$		20	150	mV
Load Regulation	$\Delta V_{OUT}$	$50mA \leq I_{OUT} \leq 1A$		70	150	mV
Output Impedance	$R_{OUT}$	100mA DC and $20mA_{RMS}$ , $f_O=120Hz$		100		$m\Omega$
Quiescent Current	$I_Q$	$V_{OUT} +2V \leq V_{IN} \leq 26V$ , $I_{OUT} =5mA$		10	15	mA
Output Noise Voltage	$e_N$	10Hz-100kHz, $I_{OUT} =5mA$		450		$\mu V_{RMS}$
Ripple Rejection	RR	$f_O=120Hz$ , $1V_{RMS}$ , $I_{OUT} =100mA$	52	64		dB
Long Term Stability				60		mV/1000Hr
Dropout Voltage	$V_D$	$I_{OUT} =1A$ $I_{OUT} =100mA$		0.5 0.11	0.8 0.15	V
Short Circuit Current	$I_{SC}$	(Note)		2.5		A
Maximum Line Transient	$T_{IN}$	$R_{OUT}=100\Omega$ , $T \leq 100ms$	60	75		V
Reverse Polarity DC Input Voltage	$V_{RIN}$	$R_{OUT}=100\Omega$	-15	-30		V
Reverse Polarity Transient Input Voltage	$V_{TRRI}$	$R_{OUT}=100\Omega$ , $T \leq 100ms$	-50	-75		V







Note: Output current will decrease with temperature increase but will not drop below 1A at the maximum specified temperature.

### ■ TYPICAL APPLICATION









Note: 1.  $C_I$  is required if regulator is located far from power supply filter.  
2.  $C_O$  must be higher than 22  $\mu$ F for stability, and locate as close as possible to the regulator.







## ■ TYPICAL CHARACTERISTICS









## ■ TYPICAL CHARACTERISTICS (Cont.)





■ TYPICAL CHARACTERISTICS (Cont.)



## ■ TYPICAL CHARACTERISTICS (Cont.)



- TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for LDO Voltage Regulators category:***

***Click to view products by Unisonic manufacturer:***

Other Similar products are found below :

[M38D29FFHP#U1](#) [702103A](#) [717726C](#) [742457H](#) [MP20051DN-LF-Z](#) [R5F111PGGFB#30](#) [AP7363-SP-13](#) [NCP103AMX285TCG](#)  
[NCV8664CST33T3G](#) [NCV8752AMX28TCG](#) [L9454](#) [AP7362-HA-7](#) [LX13043CLD](#) [TCR3DF185,LM\(CT](#) [TCR3DF24,LM\(CT](#)  
[TCR3DF285,LM\(CT](#) [TCR3DF31,LM\(CT](#) [TCR3DF45,LM\(CT](#) [TLF4949EJ](#) [L9708](#) [L970813TR](#) [030014BB](#) [059985X](#) [EAN61387601](#)  
[EAN61573601](#) [NCP121AMX173TCG](#) [NCP4687DH15T1G](#) [NCV8703MX30TCG](#) [701326R](#) [702087BB](#) [755078E](#) [TCR2EN28,LF\(S](#)  
[LM1117DT-1.8/NO](#) [LT1086CM#TRPBF](#) [AZ1085S2-1.5TRE1](#) [MAX15101EWL+T](#) [NCV8170AXV250T2G](#) [SCD337BTG](#)  
[TCR3DF27,LM\(CT](#) [TCR3DF19,LM\(CT](#) [TCR3DF125,LM\(CT](#) [TCR2EN18,LF\(S](#) [MAX15103EWL+T](#) [TS2937CZ-5.0 C0](#) [MAX8878EUK30-T](#) [MAX663CPA](#) [NCV4269CPD50R2G](#) [NCV8716MT30TBG](#) [AZ1117IH-1.2TRG1](#) [MP2013GQ-P](#)